

# Package ‘alabaster.sfe’

April 5, 2026

**Type** Package

**Title** Language agnostic on disk serialization of  
SpatialFeatureExperiment

**Version** 1.2.0

**Description** Builds upon the existing ArtifactDB project, expanding alabaster.spatial for  
language agnostic on disk serialization of SpatialFeatureExperiment.

**Depends** SpatialFeatureExperiment (>= 1.9.3), alabaster.base

**Imports** alabaster.sce, alabaster.spatial (>= 1.5.2), EBImage,  
jsonlite, methods, RBioFormats, S4Vectors, sfarrow,  
SingleCellExperiment, spatialreg, spdep, SummarizedExperiment,  
terra, xml2

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.3.2

**Suggests** BiocStyle, fs, knitr, rmarkdown, scater, sf, SFEData,  
testthat (>= 3.0.0), Voyager (>= 1.9.1)

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**URL** <https://pachterlab.github.io/alabaster.sfe/>

**biocViews** DataRepresentation, Spatial

**BugReports** <https://github.com/pachterlab/alabaster.sfe/issues>

**git\_url** <https://git.bioconductor.org/packages/alabaster.sfe>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** cb337e4

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-04-05

**Author** Lambda Moses [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-7092-9427>>)

**Maintainer** Lambda Moses <dl3764@columbia.edu>

## Contents

readBioFormatsImage . . . . .	2
readExtImage . . . . .	3
readSF . . . . .	4
readSpatialFeatureExperiment . . . . .	4
readSpatRaster . . . . .	5
saveObject,BioFormatsImage-method . . . . .	6
saveObject,ExtImage-method . . . . .	7
saveObject,sf-method . . . . .	8
saveObject,SpatialFeatureExperiment-method . . . . .	8
saveObject,SpatRaster-method . . . . .	9

<b>Index</b>	<b>11</b>
--------------	-----------

---

readBioFormatsImage	<i>Read BioFormatsImage from alabaster on disk representation</i>
---------------------	---

---

## Description

Reads the metadata and `imgSource` will point to the file within the on disk representation of SFE. The image itself should not be moved or the `BioFormatsImage` object will no longer work.

## Usage

```
readBioFormatsImage(path, metadata = NULL, ...)
```

## Arguments

<code>path</code>	String containing a path to a directory, itself created with a <code>saveObject</code> method.
<code>metadata</code>	Named list containing metadata for the object - most importantly, the <code>type</code> field that controls dispatch to the correct loading function. If <code>NULL</code> , this is automatically read by <code>readObjectFile(path)</code> .
<code>...</code>	Ignored, but used for other methods.

## Value

A `BioFormatsImage` object for SFE.

## See Also

Other `readObject-SFE-image`: `readExtImage()`, `readSpatRaster()`

## Examples

```
library(SFEData)
fp <- tempfile()
x1 <- XeniumOutput(dataset = "v1", file_path = file.path(fp, "xenium1"))
x2 <- XeniumOutput("v2", file_path = file.path(fp, "xenium2"))

# Single file OME-TIFF
fsave <- file.path(fp, "bfi1")
sfe <- readXenium(x1)
```

```

bfi <- getImg(sfe)
bfi <- affineImg(bfi, M = matrix(c(cos(pi/6), sin(pi/6), -sin(pi/6), cos(pi/6)), nrow = 2),
                             v = c(0,0))
saveObject(bfi, fsave)
bfi2 <- readObject(fsave)

unlink(fsave, recursive = TRUE)

# Multi file OME-TIFF
fsave <- file.path(fp, "bfi2")
sfe <- readXenium(x2)
bfi <- getImg(sfe)
saveObject(bfi, fsave)
bfi2 <- readObject(fsave)
unlink(fsave, recursive = TRUE)

```

---

readExtImage	<i>Read ExtImage from disk</i>
--------------	--------------------------------

---

## Description

Read ExtImage from disk

## Usage

```
readExtImage(path, metadata = NULL, ...)
```

## Arguments

path	String containing a path to a directory, itself created with a <a href="#">saveObject</a> method.
metadata	Named list containing metadata for the object - most importantly, the type field that controls dispatch to the correct loading function. If NULL, this is automatically read by <a href="#">readObjectFile</a> (path).
...	Arguments passed to <a href="#">readImage</a> .

## Value

A [ExtImage](#) object for SFE.

## See Also

Other readObject-SFE-image: [readBioFormatsImage\(\)](#), [readSpatRaster\(\)](#)

## Examples

```

library(SFEData)
fp <- tempfile()
fsave <- file.path(fp, "exi")
x1 <- XeniumOutput(dataset = "v1", file_path = file.path(fp, "xenium1"))
sfe <- readXenium(x1)
bfi <- getImg(sfe)
exi <- toExtImage(bfi)
saveObject(exi, fsave)

```

```
exi2 <- readObject(fsave)
unlink(fsave, recursive = TRUE)
```

---

readSF	<i>Read sf from alabaster on disk representation</i>
--------	--

---

### Description

Read the GeoParquet file into R. GeoParquet should also work in any programming language that supports arrow. Newer version of GDAL with Parquet driver is not strictly necessary if the geometry's WKB can be converted to whichever language specific object such as `sfc` in R.

### Usage

```
readSF(path, metadata = NULL)
```

### Arguments

<code>path</code>	String containing a path to a directory, itself created with a <a href="#">saveObject</a> method.
<code>metadata</code>	Named list containing metadata for the object - most importantly, the <code>type</code> field that controls dispatch to the correct loading function. If <code>NULL</code> , this is automatically read by <a href="#">readObjectFile</a> ( <code>path</code> ).

### Value

An sf data frame

### Examples

```
library(sf)
fp <- tempfile()
df <- as.data.frame(matrix(rnorm(10), ncol = 2))
df <- st_as_sf(df, coords = names(df), crs = NA)
saveObject(df, path = fp)
df2 <- readObject(fp)
```

---

readSpatialFeatureExperiment	<i>Read SFE object from alabaster on disk representation</i>
------------------------------	--

---

### Description

Read SFE object from alabaster on disk representation

### Usage

```
readSpatialFeatureExperiment(path, metadata = NULL, ...)
```

**Arguments**

path	String containing a path to a directory, itself created with a <a href="#">saveObject</a> method.
metadata	Named list containing metadata for the object - most importantly, the type field that controls dispatch to the correct loading function. If NULL, this is automatically read by <a href="#">readObjectFile</a> (path).
...	Further arguments to pass to individual methods.

**Value**

A SpatialFeatureExperiment object

**Examples**

```
library(SFEData)
fp <- tempfile()
fn <- file.path(fp, "vizgen")
d <- VizgenOutput(dataset = "cellpose", file_path = fn)
suppressWarnings(sfe <- readVizgen(d))
fsave <- file.path(fp, "sfe_save")
saveObject(sfe, fsave)
sfe2 <- readObject(fsave)
```

---

readSpatRaster	<i>Read SpatRaster from alabaster on disk representation</i>
----------------	--

---

**Description**

Not the same as `terra::rast`; here this function also reads the metadata file.

**Usage**

```
readSpatRaster(path, metadata = NULL, ...)
```

**Arguments**

path	String containing a path to a directory, itself created with a <a href="#">saveObject</a> method.
metadata	Named list containing metadata for the object - most importantly, the type field that controls dispatch to the correct loading function. If NULL, this is automatically read by <a href="#">readObjectFile</a> (path).
...	Arguments passed to <a href="#">rast</a> , character method.

**Value**

A [SpatRasterImage](#) object for SFE.

**See Also**

Other readObject-SFE-image: [readBioFormatsImage](#)(), [readExtImage](#)()

## Examples

```
library(SFEData)
fp <- tempfile()
fn <- file.path(fp, "vizgen")
d <- VizgenOutput(dataset = "cellpose", file_path = fn)
suppressWarnings(sfe <- readVizgen(d))
img <- getImg(sfe)
class(img)
fsave <- file.path(fp, "img")
saveObject(img, fsave)
img2 <- readObject(fsave)
```

---

saveObject,BioFormatsImage-method

*Save BioFormatsImage for alabaster*

---

## Description

This function copies the original file to a pre-defined location within the directory that stores the on disk representation of the SFE object for data sharing. Since `BioFormatsImage` is essentially just some metadata in memory and it never loads the image into memory (once the image is loaded into memory it becomes `ExtImage`), once the original image is moved, the `BioFormatsImage` object will no longer work, which is why the pre-defined location is important. This function also saves the metadata, which includes spatial extent and affine transformations.

## Usage

```
## S4 method for signature 'BioFormatsImage'
saveObject(x, path, ...)
```

## Arguments

<code>x</code>	A Bioconductor object of the specified class.
<code>path</code>	String containing the path to a directory in which to save <code>x</code> .
<code>...</code>	Ignored

## Value

`x` is saved into `path` and `NULL` is invisibly returned.

## See Also

Other `saveObject`-SFE-image: [saveObject,ExtImage-method](#), [saveObject,SpatRaster-method](#)

## Examples

```
library(SFEData)
fp <- tempfile()
fsave <- file.path(fp, "bfi2")
x1 <- XeniumOutput(dataset = "v1", file_path = file.path(fp, "xenium1"))
sfe <- readXenium(x1)
bfi <- getImg(sfe)
saveObject(bfi, fsave)
bfi2 <- readObject(fsave)
unlink(fsave, recursive = TRUE)
```

---

saveObject,ExtImage-method

*Save ExtImage to disk for alabaster*

---

## Description

Save ExtImage to disk for alabaster

## Usage

```
## S4 method for signature 'ExtImage'
saveObject(x, path, ...)
```

## Arguments

x	A Bioconductor object of the specified class.
path	String containing the path to a directory in which to save x.
...	Extra arguments passed to <a href="#">writeImage</a> .

## Value

x is saved into path and NULL is invisibly returned.

## See Also

Other saveObject-SFE-image: [saveObject,BioFormatsImage-method](#), [saveObject,SpatRaster-method](#)

## Examples

```
library(SFEData)
fp <- tempfile()
fsave <- file.path(fp, "exi")
x1 <- XeniumOutput(dataset = "v1", file_path = file.path(fp, "xenium1"))
sfe <- readXenium(x1)
bfi <- getImg(sfe)
exi <- toExtImage(bfi)
saveObject(exi, fsave)
exi2 <- readObject(fsave)
unlink(fsave, recursive = TRUE)
```

---

saveObject, sf-method *Save sf to disk for alabaster*

---

### Description

sf data frames are saved as GeoParquet.

### Usage

```
## S4 method for signature 'sf'
saveObject(x, path)
```

### Arguments

x                    A Bioconductor object of the specified class.  
 path                String containing the path to a directory in which to save x.

### Value

x is saved into path and NULL is invisibly returned.

### Examples

```
library(sf)
fp <- tempfile()
df <- as.data.frame(matrix(rnorm(10), ncol = 2))
df <- st_as_sf(df, coords = names(df), crs = NA)
saveObject(df, path = fp)
```

---

saveObject, SpatialFeatureExperiment-method

*Save a SpatialFeatureExperiment object*

---

### Description

Save SFE objects to disk in an interoperable, language agnostic format that may also facilitate out of memory operations via HDF5 (non-spatial, inherited from `alabaster.sce`) and Apache Parquet (geometries).

### Usage

```
## S4 method for signature 'SpatialFeatureExperiment'
saveObject(x, path, ...)
```

### Arguments

x                    A Bioconductor object of the specified class.  
 path                String containing the path to a directory in which to save x.  
 ...                Additional named arguments to pass to specific methods.

## Details

There's no new arguments for ... for the SFE, SpatialExperiment, and SingleCellExperiment methods, but there is an argument that can be specified for ... in the SummarizedExperiment method of saveObject.

At present, spatial results in featureData for geometries and dimension reductions (see [colFeatureData](#)) and parameters of spatial analyses (see [getParams](#)) are not save because those parts of the SFE object are more experimental and are subject to change. colFeatureData where global spatial results are stored for columns of colData(x) is saved by the alabaster saveObject method for DataFrame.

## Value

x is saved into path and NULL is invisibly returned.

## Examples

```
library(SpatialFeatureExperiment)
library(Voyager)
library(SFEData)
library(SingleCellExperiment)
library(scater)

fp <- tempfile()
fn <- file.path(fp, "vizgen")
d <- VizgenOutput(dataset = "cellpose", file_path = fn)
suppressWarnings(sfe1 <- readVizgen(d, add_molecules = TRUE))

colGraph(sfe1, "knn5") <- findSpatialNeighbors(sfe1, method = "knearneigh", k = 5)
SpatialFeatureExperiment::centroids(sfe1)$foo <- rnorm(ncol(sfe1))
sfe1 <- logNormCounts(sfe1)
sfe1 <- runMoransI(sfe1, colGraphName = "knn5")
sfe1 <- colDataMoransI(sfe1, features = c("transcript_count", "anisotropy",
                                       "perimeter_area_ratio", "solidity"))
sfe1 <- colGeometryMoransI(sfe1, colGeometryName = "centroids", features = "foo")
sfe1 <- runPCA(sfe1, ncomponents = 10)
sfe1 <- reducedDimMoransI(sfe1, components = 1:10)

sfe1 <- runUnivariate(sfe1, type = "localmoran", features = rownames(sfe1)[1])

fsave <- file.path(fp, "sfe_vizgen")
saveObject(sfe1, fsave)
sfe2 <- readObject(fsave)

unlink(fsave, recursive = TRUE)
```

## Description

Intended for SpatRasterImage which really is SpatRaster that also inherits from SPE's SpatialImage. Besides writeRaster, this function also writes a metadata file in the alabaster framework. If the image is not loaded into memory and the original file is already spatially registered, e.g. it has a spatial extent, then the original file is copied to a pre-defined place in the on-disk representation of SFE and writeRaster is not called.

## Usage

```
## S4 method for signature 'SpatRaster'  
saveObject(x, path, ...)
```

## Arguments

x	A Bioconductor object of the specified class.
path	String containing the path to a directory in which to save x.
...	Extra parameters passed to <a href="#">writeRaster</a> .

## Value

x is saved into path and NULL is invisibly returned.

## See Also

Other saveObject-SFE-image: [saveObject, BioFormatsImage-method](#), [saveObject, ExtImage-method](#)

## Examples

```
library(SFEData)  
fp <- tempfile()  
fn <- file.path(fp, "vizgen")  
d <- VizgenOutput(dataset = "cellpose", file_path = fn)  
suppressWarnings(sfe <- readVizgen(d))  
img <- getImg(sfe)  
class(img)  
fsave <- file.path(fp, "img")  
saveObject(img, fsave)  
img2 <- readObject(fsave)
```

# Index

- \* **readObject-SFE-image**
  - readBioFormatsImage, [2](#)
  - readExtImage, [3](#)
  - readSpatRaster, [5](#)
- \* **saveObject-SFE-image**
  - saveObject, BioFormatsImage-method, [6](#)
  - saveObject, ExtImage-method, [7](#)
  - saveObject, SpatRaster-method, [9](#)
  
- BioFormatsImage, [2](#)
  
- colFeatureData, [9](#)
  
- ExtImage, [3](#)
  
- getParams, [9](#)
  
- rast, [5](#)
- readBioFormatsImage, [2](#), [3](#), [5](#)
- readExtImage, [2](#), [3](#), [5](#)
- readImage, [3](#)
- readObjectFile, [2-5](#)
- readSF, [4](#)
- readSpatialFeatureExperiment, [4](#)
- readSpatRaster, [2](#), [3](#), [5](#)
  
- saveObject, [2-5](#)
- saveObject, BioFormatsImage-method, [6](#)
- saveObject, ExtImage-method, [7](#)
- saveObject, sf-method, [8](#)
- saveObject, SpatialFeatureExperiment-method, [8](#)
- saveObject, SpatRaster-method, [9](#)
- SpatRasterImage, [5](#)
  
- writeImage, [7](#)
- writeRaster, [10](#)