

Package ‘nethet’

April 6, 2026

Type Package

Title A bioconductor package for high-dimensional exploration of biological network heterogeneity

Version 1.42.0

Date 2020-09-27

Author Nicolas Staedler, Frank Dondelinger

Maintainer Nicolas Staedler <staedler.n@gmail.com>, Frank Dondelinger <fdondelinger.work@gmail.com>

Description Package nethet is an implementation of statistical solid methodology enabling the analysis of network heterogeneity from high-dimensional data. It combines several implementations of recent statistical innovations useful for estimation and comparison of networks in a heterogeneous, high-dimensional setting. In particular, we provide code for formal two-sample testing in Gaussian graphical models (differential network and GGM-GSA; Stadler and Mukherjee, 2013, 2014) and make a novel network-based clustering algorithm available (mixed graphical lasso, Stadler and Mukherjee, 2013).

Imports glasso, mvtnorm, GeneNet, huge, CompQuadForm, ggm, mclust, parallel, GSA, limma, multtest, ICSNP, glmnet, network, ggplot2, grDevices, graphics, stats, utils

Suggests knitr, xtable, BiocStyle, testthat

biocViews Clustering, GraphAndNetwork

VignetteBuilder knitr

License GPL-2

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/nethet>

git_branch RELEASE_3_22

git_last_commit bc1b9c9

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-04-05

Contents

NetHet-package	4
agg.pval	4
agg.score.iriz.scale	5
agg.score.iriz.shift	5
aggpval	6
aic.glasso	6
beta.mat	7
beta.mat.diffregr	8
bic.glasso	8
buildDotPlotDataFrame	9
bwprun_mixglasso	10
cv.fold	11
cv.glasso	12
diffnet_multisplit	13
diffnet_pval	15
diffnet_singlesplit	16
diffregr_multisplit	18
diffregr_pval	20
diffregr_singlesplit	22
dot_plot	24
error.bars	25
est2.my.ev2	25
est2.my.ev2.diffregr	26
est2.my.ev3	27
est2.my.ev3.diffregr	28
est2.ww.mat.diffregr	29
est2.ww.mat2	30
est2.ww.mat2.diffregr	30
export_network	31
EXPStep.mix	32
func.uinit	33
generate_2networks	34
generate_inv_cov	35
getinvcov	35
ggmsa_multisplit	36
ggmsa_singlesplit	38
glasso.invcov	39
glasso.invcov	39
glasso.parcov	40
gsea.highdimT2	40
gsea.iriz	41
gsea.iriz.scale	42
gsea.iriz.shift	43
gsea.t2cov	44
het_cv_glasso	44
hugepath	45
inf.mat	46
invcov2parcov	47
invcov2parcov_array	47
lambda.max	48

lambdagrid_lin	48
lambdagrid_mult	49
loglik_mix	49
logratio	50
logratio.diffregr	51
make_grid	51
mcov	52
mixglasso	52
mixglasso_init	55
mixglasso_ncomp_fixed	56
mle.ggm	57
MStepGlasso	58
my.ev2.diffregr	59
my.p.adjust	59
my.ttest	60
my.ttest2	60
mytrunc.method	61
perm.diffregr_pval	61
perm.diffregr_teststat	62
plot.diffnet	63
plot.diffregr	63
plot.gmgmsa	64
plot.nethetclustering	64
plotCV	65
plot_2networks	66
print.nethetsummary	67
q.matrix.diffregr	67
q.matrix.diffregr3	68
q.matrix.diffregr4	68
q.matrix3	69
q.matrix4	70
scatter_plot	70
screen_aic.glasso	72
screen_bic.glasso	73
screen_cv.glasso	74
screen_cv1se.lasso	75
screen_cvfix.lasso	75
screen_cvmin.lasso	76
screen_cvsqrt.lasso	77
screen_cvtrunc.lasso	77
screen_full	78
screen_shrink	79
shapiro_screen	79
sim_mix	80
sim_mix_networks	81
sparse_conc	82
summary.diffnet	82
summary.diffregr	83
summary.gmgmsa	83
summary.nethetclustering	84
sumoffdiag	84
symmkldist	85

t2cov.lr	85
t2diagcov.lr	86
test.sd	86
test.t2	87
tr	87
twosample_single_regr	88
w.kldist	88
ww.mat	89
ww.mat.diffregr	90
ww.mat2	90
ww.mat2.diffregr	91

Index 92

NetHet-package	<i>NetHet-package</i>
----------------	-----------------------

Description

A bioconductor package for high-dimensional exploration of biological network heterogeneity

Details

Includes: *Network-based clustering (MixGLasso) *Differential network (DiffNet) *Differential regression (DiffRegr) *Gene-set analysis based on graphical models (GGMGSA) *Plotting functions for exploring network heterogeneity

References

Stadler, N. and Mukherjee, S. (2013). Two-Sample Testing in High-Dimensional Models. Preprint <http://arxiv.org/abs/1210.4584>.

agg.pval	<i>P-value aggregation (Meinshausen et al 2009)</i>
----------	---

Description

P-value aggregation

Usage

```
agg.pval(gamma, pval)
```

Arguments

gamma	see Meinshausen et al 2009
pval	vector of p-values

Value

inf-quantile aggregated p-value

Author(s)

n.stadler

`agg.score.iriz.scale` *Irizarry aggregate score (scale)*

Description

Irizarry aggregate score (scale)

Usage`agg.score.iriz.scale(ttstat, geneset, gene.name)`**Arguments**

<code>ttstat</code>	no descr
<code>geneset</code>	no descr
<code>gene.name</code>	no descr

Value

no descr

Author(s)

n.stadler

`agg.score.iriz.shift` *Irizarry aggregate score (shift)*

Description

Irizarry aggregate score (shift)

Usage`agg.score.iriz.shift(ttstat, geneset, gene.name)`**Arguments**

<code>ttstat</code>	no descr
<code>geneset</code>	no descr
<code>gene.name</code>	no descr

Value

no descr

Author(s)

n.stadler

aggpval	<i>Meinshausen p-value aggregation</i>
---------	--

Description

Meinshausen p-value aggregation.

Usage

```
aggpval(pval, gamma.min = 0.05)
```

Arguments

pval	Vector of p-values.
gamma.min	See inf-quantile formula of Meinshausen et al 2009 (default=0.05).

Details

Inf-quantile formula for p-value aggregation presented in Meinshausen et al 2009.

Value

Aggregated p-value.

Author(s)

n.stadler

Examples

```
pval=runif(50)
aggpval(pval)
```

aic.glasso	<i>AIC.glasso</i>
------------	-------------------

Description

AIC.glasso

Usage

```
aic.glasso(x, lambda, penalize.diagonal = FALSE, plot.it = TRUE,
  use.package = "huge", include.mean = FALSE)
```

Arguments

x	no descr
lambda	no descr
penalize.diagonal	no descr
plot.it	no descr
use.package	no descr
include.mean	no descr

Value

no descr

Author(s)

n.stadler

beta.mat	<i>Compute beta-matrix</i>
----------	----------------------------

Description

Compute beta-matrix

Usage

```
beta.mat(ind1, ind2, sig1, sig2, sig)
```

Arguments

ind1	no descr
ind2	no descr
sig1	no descr
sig2	no descr
sig	no descr

Details

$\text{beta-matrix} = E[s_{\text{ind1}}(Y; \text{sig1}) s_{\text{ind2}}(Y; \text{sig2})' | \text{sig}]$

Value

no descr

Author(s)

n.stadler

beta.mat.diffregr *Computation beta matrix*

Description

Computation beta matrix

Usage

```
beta.mat.diffregr(ind1, ind2, beta1, beta2, beta, sig1, sig2, sig, Sig)
```

Arguments

ind1	no descr
ind2	no descr
beta1	no descr
beta2	no descr
beta	no descr
sig1	no descr
sig2	no descr
sig	no descr
Sig	no descr

Value

no descr

Author(s)

n.stadler

bic.glasso *BIC.glasso*

Description

BIC.glasso

Usage

```
bic.glasso(x, lambda, penalize.diagonal = FALSE, plot.it = TRUE,  
          use.package = "huge", include.mean = FALSE)
```

Arguments

x	no descr
lambda	no descr
penalize.diagonal	no descr
plot.it	no descr
use.package	no descr
include.mean	no descr

Value

no descr

Author(s)

n.stadler

buildDotPlotDataFrame *Build up dataframe for plotting dot plot with ggplot2*

Description

Internal function

Usage

```
buildDotPlotDataFrame(net.clustering, cluster.names, node.names)
```

Arguments

net.clustering	Clustering
cluster.names	Cluster names
node.names	Node names

Value

A data frame for plotting the dotPlot with ggplot2 is returned. Column P.Corr contains the partial correlations of each edge as a numeric, column Mean contains the minimum mean expression of the two proteins (e.g. if the edge is e(p1, p2), then the column contains $\min(\text{mean}(p1), \text{mean}(p2))$), column Edge contains the name of the edge as a character string of the form "p1-p2" and column Type contains the cluster name of the cluster that the edge belongs to as a character string.

 bwprun_mixglasso *bwprun_mixglasso*

Description

Mixglasso with backward pruning

Usage

```
bwprun_mixglasso(x, n.comp.min = 1, n.comp.max, lambda = sqrt(2 *
  nrow(x) * log(ncol(x)))/2, pen = "glasso.parcor",
  selection.crit = "mmdl", term = 10^{ -3 }, min.compsize = 5,
  init = "kmeans.hc", my.cl = NULL, modelname.hc = "VVV",
  nstart.kmeans = 1, iter.max.kmeans = 10, reinit.out = FALSE,
  reinit.in = FALSE, mer = TRUE, del = TRUE, ...)
```

Arguments

x	Input data matrix
n.comp.min	Minimum number of components. Take n.comp.min=1 !
n.comp.max	Maximum number of components
lambda	Regularization parameter. Default=sqrt(2*n*log(p))/2
pen	Determines form of penalty: glasso.parcor (default), glasso.invcov, glasso.invcor
selection.crit	Selection criterion. Default='mmdl'
term	Termination criterion of EM algorithm. Default=10 ⁻³
min.compsize	Stop EM if any(compsize)<min.compsize; Default=5
init	Initialization. Method used for initialization init='cl.init','r.means','random','kmeans','kmeans.hc','h' Default='kmeans.hc'
my.cl	Initial cluster assignments; need to be provided if init='cl.init' (otherwise this param is ignored). Default=NULL
modelname.hc	Model class used in hc. Default="VVV"
nstart.kmeans	Number of random starts in kmeans; default=1
iter.max.kmeans	Maximal number of iteration in kmeans; default=10
reinit.out	Re-initialization if compsize<min.compsize (at the start of algorithm) ?
reinit.in	Re-initialization if compsize<min.compsize (at the bwprun-loop level of algorithm) ?
mer	Merge closest comps for initialization
del	Delete smallest comp for initialization
...	Other arguments. See mixglasso_init

Details

This function runs mixglasso with various number of mixture components: It starts with a too large number of components and iterates towards solutions with smaller number of components by initializing using previous solutions.

Value

list consisting of

selcrit Selcrit for all models with number of components between n.comp.min and n.comp.max

res.init Initialization for all components

comp.name List of names of components. Indicates which states were merged/deleted during backward pruning

re.init.in Logical vector indicating whether re-initialization was performed or not

fit.mixgl.selcrit Results for model with optimal number of components. List see mixglasso_init

Author(s)

n.stadler

Examples

```
##generate data
set.seed(1)
n <- 1000
n.comp <- 3
p <- 10

# Create different mean vectors
Mu <- matrix(0,p,n.comp)

nonzero.mean <- split(sample(1:p),rep(1:n.comp,length=p))
for(k in 1:n.comp){
  Mu[nonzero.mean[[k]],k] <- -2/sqrt(ceiling(p/n.comp))
}

sim <- sim_mix_networks(n, p, n.comp, Mu=Mu)

##run mixglasso

fit <- bwprun_mixglasso(sim$data,n.comp=1,n.comp.max=5,selection.crit='bic')
plot(fit$selcrit,ylab='bic',xlab='Num.Comps',type='b')
```

cv.fold

Make folds

Description

Make folds

Usage

```
cv.fold(n, folds = 10)
```

Arguments

n	no descr
folds	no descr

Value

no descr

Author(s)

n.stadler

cv.glasso

Crossvalidation for GLasso

Description

Crossvalidation for GLasso

Usage

```
cv.glasso(x, folds = 10, lambda, penalize.diagonal = FALSE,  
plot.it = FALSE, se = TRUE, include.mean = FALSE)
```

Arguments

x	no descr
folds	no descr
lambda	lambda-grid (increasing!)
penalize.diagonal	no descr
plot.it	no descr
se	no descr
include.mean	no descr

Details

! lambda-grid has to be increasing (see glassopath)

Value

no descr

Author(s)

n.stadler

diffnet_multisplit *Differential Network*

Description

Differential Network

Usage

```
diffnet_multisplit(x1, x2, b.splits = 50, frac.split = 1/2,
  screen.meth = "screen_bic.glasso", include.mean = FALSE,
  gamma.min = 0.05, compute.evals = "est2.my.ev3",
  algorithm.mleggm = "glasso_rho0", method.compquadform = "imhof",
  acc = 1e-04, epsabs = 1e-10, epsrel = 1e-10, show.warn = FALSE,
  save.mle = FALSE, verbose = TRUE, mc.flag = FALSE,
  mc.set.seed = TRUE, mc.preschedule = TRUE,
  mc.cores = getOption("mc.cores", 2L), ...)
```

Arguments

x1	Data-matrix sample 1. You might need to center and scale your data-matrix.
x2	Data-matrix sample 1. You might need to center and scale your data-matrix.
b.splits	Number of splits (default=50).
frac.split	Fraction train-data (screening) / test-data (cleaning) (default=0.5).
screen.meth	Screening procedure. Options: 'screen_bic.glasso' (default), 'screen_cv.glasso', 'screen_shrink' (not recommended).
include.mean	Should sample specific means be included in hypothesis? Use include.mean=FALSE (default and recommended) which assumes $\mu_1=\mu_2=0$ and tests the hypothesis $H_0: \Omega_1=\Omega_2$.
gamma.min	Tuning parameter in p-value aggregation of Meinshausen et al (2009). (Default=0.05).
compute.evals	Method to estimate the weights in the weighted-sum-of-chi2s distribution. The default and (currently) the only available option is the method 'est2.my.ev3'.
algorithm.mleggm	Algorithm to compute MLE of GGM. The algorithm 'glasso_rho' is the default and (currently) the only available option.
method.compquadform	Method to compute distribution function of weighted-sum-of-chi2s (default='imhof').
acc	See ?davies (default 1e-04).
epsabs	See ?imhof (default 1e-10).
epsrel	See ?imhof (default 1e-10).
show.warn	Should warnings be showed (default=FALSE)?
save.mle	If TRUE, MLEs (inverse covariance matrices for samples 1 and 2) are saved for all b.splits. The median aggregated inverse covariance matrix is provided in the output as 'medwi'. The default is save.mle=FALSE.
verbose	If TRUE, show output progress.

mc.flag	If TRUE use parallel execution for each b.splits via function mclapply of package parallel.
mc.set.seed	See mclapply. Default=TRUE
mc.preschedule	See mclapply. Default=TRUE
mc.cores	Number of cores to use in parallel execution. Defaults to mc.cores option if set, or 2 otherwise.
...	Additional arguments for screen.meth.

Details

Remark:

* If include.mean=FALSE, then x_1 and x_2 have mean zero and DiffNet tests the hypothesis $H_0: \Omega_1 = \Omega_2$. You might need to center x_1 and x_2 . * If include.mean=TRUE, then DiffNet tests the hypothesis $H_0: \mu_1 = \mu_2 \ \& \ \Omega_1 = \Omega_2$ * However, we recommend to set include.mean=FALSE and to test equality of the means separately. * You might also want to scale x_1 and x_2 , if you are only interested in differences due to (partial) correlations.

Value

list consisting of

ms.pval	p-values for all b.splits
ss.pval	single-split p-value
medagg.pval	median aggregated p-value
meinshagg.pval	meinshausen aggregated p-value (meinshausen et al 2009)
teststat	test statistics for b.splits
weights.null distr	estimated weights
active.last	active-sets obtained in last screening-step
medwi	median of inverse covariance matrices over b.splits
sig.last	constrained mle (covariance matrix) obtained in last cleaning-step
wi.last	constrained mle (inverse covariance matrix) obtained in last cleaning-step

Author(s)

n.stadler

Examples

```
#####
##This example illustrates the use of Differential Network##
#####

##set seed
set.seed(1)

##sample size and number of nodes
n <- 40
p <- 10
```

```

##specifiy sparse inverse covariance matrices
gen.net <- generate_2networks(p,graph='random',n.nz=rep(p,2),
                             n.nz.common=ceiling(p*0.8))

invcov1 <- gen.net[[1]]
invcov2 <- gen.net[[2]]
plot_2networks(invcov1,invcov2,label.pos=0,label.cex=0.7)

##get corresponding correlation matrices
cor1 <- cov2cor(solve(invcov1))
cor2 <- cov2cor(solve(invcov2))

##generate data under null hypothesis (both datasets have the same underlying
## network)
library('mvtnorm')
x1 <- rmvnorm(n,mean = rep(0,p), sigma = cor1)
x2 <- rmvnorm(n,mean = rep(0,p), sigma = cor1)

##run diffnet (under null hypothesis)
dn.null <- diffnet_multisplit(x1,x2,b.splits=1,verbose=FALSE)
dn.null$ss.pval#single-split p-value

##generate data under alternative hypothesis (datasets have different networks)
x1 <- rmvnorm(n,mean = rep(0,p), sigma = cor1)
x2 <- rmvnorm(n,mean = rep(0,p), sigma = cor2)

##run diffnet (under alternative hypothesis)
dn.altn <- diffnet_multisplit(x1,x2,b.splits=1,verbose=FALSE)
dn.altn$ss.pval#single-split p-value
dn.altn$medagg.pval#median aggregated p-value

##typically we would choose a larger number of splits
# dn.altn <- diffnet_multisplit(x1,x2,b.splits=10,verbose=FALSE)
# dn.altn$ms.pval#multi-split p-values
# dn.altn$medagg.pval#median aggregated p-value
# plot(dn.altn)#histogram of single-split p-values

```

diffnet_pval

P-value calculation

Description

P-value calculation

Usage

```
diffnet_pval(x1, x2, x, sig1, sig2, sig, mu1, mu2, mu, act1, act2, act,
             compute.evals, include.mean, method.compquadform, acc, epsabs, epsrel,
             show.warn)
```

Arguments

x1	no descr
x2	no descr

x	no descr
sig1	no descr
sig2	no descr
sig	no descr
mu1	no descr
mu2	no descr
mu	no descr
act1	no descr
act2	no descr
act	no descr
compute.eval	no descr
include.mean	no descr
method.compquadform	no descr
acc	no descr
epsabs	no descr
epsrel	no descr
show.warn	no descr

Value

no descr

Author(s)

n.stadler

diffnet_singlesplit *Differential Network for user specified data splits*

Description

Differential Network for user specified data splits

Usage

```
diffnet_singlesplit(x1, x2, split1, split2,
  screen.meth = "screen_bic.glasso", compute.eval = "est2.my.ev3",
  algorithm.mleggm = "glasso_rho0", include.mean = FALSE,
  method.compquadform = "imhof", acc = 1e-04, epsabs = 1e-10,
  epsrel = 1e-10, show.warn = FALSE, save.mle = FALSE, ...)
```

Arguments

x1	Data-matrix sample 1. You might need to center and scale your data-matrix.
x2	Data-matrix sample 2. You might need to center and scale your data-matrix.
split1	Samples (condition 1) used in screening step.
split2	Samples (condition 2) used in screening step.
screen.meth	Screening procedure. Options: 'screen_bic.glasso' (default), 'screen_cv.glasso', 'screen_shrink' (not recommended).
compute.evals	Method to estimate the weights in the weighted-sum-of-chi2s distribution. The default and (currently) the only available option is the method 'est2.my.ev3'.
algorithm.mleggm	Algorithm to compute MLE of GGM. The algorithm 'glasso_rho' is the default and (currently) the only available option.
include.mean	Should sample specific means be included in hypothesis? Use include.mean=FALSE (default and recommended) which assumes $\mu_1=\mu_2=0$ and tests the hypothesis $H_0: \Omega_1=\Omega_2$.
method.compquadform	Method to compute distribution function of weighted-sum-of-chi2s (default='imhof').
acc	See ?davies (default 1e-04).
epsabs	See ?imhof (default 1e-10).
epsrel	See ?imhof (default 1e-10).
show.warn	Should warnings be showed (default=FALSE)?
save.mle	Should MLEs be in the output list (default=FALSE)?
...	Additional arguments for screen.meth.

Details

Remark:

* If include.mean=FALSE, then x1 and x2 have mean zero and DiffNet tests the hypothesis $H_0: \Omega_1=\Omega_2$. You might need to center x1 and x2. * If include.mean=TRUE, then DiffNet tests the hypothesis $H_0: \mu_1=\mu_2 \ \& \ \Omega_1=\Omega_2$ * However, we recommend to set include.mean=FALSE and to test equality of the means separately. * You might also want to scale x1 and x2, if you are only interested in differences due to (partial) correlations.

Value

list consisting of	
pval.onesided	p-value
pval.twosided	ignore this output
teststat	log-likelihood-ratio test statistic
weights.null distr	estimated weights
active	active-sets obtained in screening-step
sig	constrained mle (covariance) obtained in cleaning-step
wi	constrained mle (inverse covariance) obtained in cleaning-step
mu	mle (mean) obtained in cleaning-step

Author(s)

n.stadler

Examples

```
##set seed
set.seed(1)

##sample size and number of nodes
n <- 40
p <- 10

##specifiy sparse inverse covariance matrices
gen.net <- generate_2networks(p,graph='random',n.nz=rep(p,2),
                             n.nz.common=ceiling(p*0.8))

invcov1 <- gen.net[[1]]
invcov2 <- gen.net[[2]]
plot_2networks(invcov1,invcov2,label.pos=0,label.cex=0.7)

##get corresponding correlation matrices
cor1 <- cov2cor(solve(invcov1))
cor2 <- cov2cor(solve(invcov2))

##generate data under alternative hypothesis
library('mvtnorm')
x1 <- rmvnorm(n,mean = rep(0,p), sigma = cor1)
x2 <- rmvnorm(n,mean = rep(0,p), sigma = cor2)

##run diffnet
split1 <- sample(1:n,20)#samples for screening (condition 1)
split2 <- sample(1:n,20)#samples for screening (condition 2)
dn <- diffnet_singlesplit(x1,x2,split1,split2)
dn$pval.onesided#p-value
```

diffregr_multisplit *Differential Regression (multi-split version).*

Description

Differential Regression (multi-split version).

Usage

```
diffregr_multisplit(y1, y2, x1, x2, b.splits = 50, frac.split = 1/2,
  screen.meth = "screen_cvtrunc.lasso", gamma.min = 0.05,
  compute.evals = "est2.my.ev3.diffregr",
  method.compquadform = "imhof", acc = 1e-04, epsabs = 1e-10,
  epsrel = 1e-10, show.warn = FALSE, n.perm = NULL,
  mc.flag = FALSE, mc.set.seed = TRUE, mc.preschedule = TRUE,
  mc.cores = getOption("mc.cores", 2L), ...)
```

Arguments

<code>y1</code>	Response vector condition 1.
<code>y2</code>	Response vector condition 2.
<code>x1</code>	Predictor matrix condition 1.
<code>x2</code>	Predictor matrix condition 2.
<code>b.splits</code>	Number of splits (default=50).
<code>frac.split</code>	Fraction train-data (screening) / test-data (cleaning) (default=0.5).
<code>screen.meth</code>	Screening method (default='screen_cvtrunc.lasso').
<code>gamma.min</code>	Tuning parameter in p-value aggregation of Meinshausen et al (2009) (default=0.05).
<code>compute.evals</code>	Method to estimate the weights in the weighted-sum-of-chi2s distribution. The default and (currently) the only available option is the method 'est2.my.ev3.diffregr'.
<code>method.compquadform</code>	Algorithm for computing distribution function of weighted-sum-of-chi2 (default='imhof').
<code>acc</code>	See ?davies (default=1e-4).
<code>epsabs</code>	See ?imhof (default=1e-10).
<code>epsrel</code>	See ?imhof (default=1e-10).
<code>show.warn</code>	Show warnings (default=FALSE)?
<code>n.perm</code>	Number of permutation for "split-perm" p-value. Default=NULL, which means that the asymptotic approximation is used.
<code>mc.flag</code>	If TRUE use parallel execution for each b.splits via function mclapply of package parallel.
<code>mc.set.seed</code>	See mclapply. Default=TRUE
<code>mc.preschedule</code>	See mclapply. Default=TRUE
<code>mc.cores</code>	Number of cores to use in parallel execution. Defaults to mc.cores option if set, or 2 otherwise.
<code>...</code>	Other arguments specific to screen.meth.

Details

Intercepts in regression models are assumed to be zero ($\mu_1=\mu_2=0$). You might need to center the input data prior to running Differential Regression.

Value

List consisting of

<code>ms.pval</code>	p-values for all b.splits
<code>ss.pval</code>	single-split p-value
<code>medagg.pval</code>	median aggregated p-value
<code>meinshagg.pval</code>	meinshausen aggregated p-value (meinshausen et al 2009)
<code>teststat</code>	test statistics for b.splits
<code>weights.nulldistr</code>	estimated weights
<code>active.last</code>	active-sets obtained in last screening-step
<code>beta.last</code>	constrained mle (regression coefficients) obtained in last cleaning-step

Author(s)

n.stadler

Examples

```
#####
##This example illustrates the use of Differential Regression##
#####

##set seed
set.seed(1)

## Number of predictors and sample size
p <- 100
n <- 80

## Predictor matrices
x1 <- matrix(rnorm(n*p),n,p)
x2 <- matrix(rnorm(n*p),n,p)

## Active-sets and regression coefficients
act1 <- sample(1:p,5)
act2 <- c(act1[1:3],sample(setdiff(1:p,act1),2))
beta1 <- beta2 <- rep(0,p)
beta1[act1] <- 0.5
beta2[act2] <- 0.5

## Response vectors under null-hypothesis
y1 <- x1%*%as.matrix(beta1)+rnorm(n,sd=1)
y2 <- x2%*%as.matrix(beta1)+rnorm(n,sd=1)

## Diffregr (asymptotic p-values)
fit.null <- diffregr_multisplit(y1,y2,x1,x2,b.splits=5)
fit.null$ms.pval#multi-split p-values
fit.null$medagg.pval#median aggregated p-values

## Response vectors under alternative-hypothesis
y1 <- x1%*%as.matrix(beta1)+rnorm(n,sd=1)
y2 <- x2%*%as.matrix(beta2)+rnorm(n,sd=1)

## Diffregr (asymptotic p-values)
fit.alt <- diffregr_multisplit(y1,y2,x1,x2,b.splits=5)
fit.alt$ms.pval
fit.alt$medagg.pval

## Diffregr (permutation-based p-values; 100 permutations)
fit.alt.perm <- diffregr_multisplit(y1,y2,x1,x2,b.splits=5,n.perm=100)
fit.alt.perm$ms.pval
fit.alt.perm$medagg.pval
```

Description

Computation "split-asym"/"split-perm" p-values.

Usage

```
diffregr_pval(y1, y2, x1, x2, beta1, beta2, beta, act1, act2, act,
  compute.ivals, method.compquadform, acc, epsabs, epsrel, show.warn,
  n.perm)
```

Arguments

y1	Response vector condition 1.
y2	Response vector condition 2.
x1	Predictor matrix condition 1.
x2	Predictor matrix condition 2.
beta1	Regression coefficients condition 1.
beta2	Regression coefficients condition 2.
beta	Pooled regression coefficients.
act1	Active-set condition 1.
act2	Active-set condition 2.
act	Pooled active-set.
compute.ivals	Method for computation of weights.
method.compquadform	Method to compute distribution function of w-sum-of-chi2.
acc	See ?davies.
epsabs	See ?imhof.
epsrel	See ?imhof.
show.warn	Show warnings?
n.perm	Number of permutations.

Value

P-value, test statistic, estimated weights.

Author(s)

n.stadler

diffregr_singlesplit *Differential Regression (single-split version).*

Description

Differential Regression (single-split version).

Usage

```
diffregr_singlesplit(y1, y2, x1, x2, split1, split2,
  screen.meth = "screen_cvtrunc.lasso",
  compute.evals = "est2.my.ev3.diffregr",
  method.compquadform = "imhof", acc = 1e-04, epsabs = 1e-10,
  epsrel = 1e-10, show.warn = FALSE, n.perm = NULL, ...)
```

Arguments

y1	Response vector condition 1.
y2	Response vector condition 2.
x1	Predictor matrix condition 1.
x2	Predictor matrix condition 2.
split1	Samples condition 1 used in screening-step.
split2	Samples condition 2 used in screening-step.
screen.meth	Screening method (default='screen_cvtrunc.lasso').
compute.evals	Method to estimate the weights in the weighted-sum-of-chi2s distribution. The default and (currently) the only available option is the method 'est2.my.ev3.diffregr'.
method.compquadform	Algorithm for computing distribution function of weighted-sum-of-chi2 (default='imhof').
acc	See ?davies (default=1e-4).
epsabs	See ?imhof (default=1e-10).
epsrel	See ?imhof (default=1e-10).
show.warn	Show warnings (default=FALSE)?
n.perm	Number of permutation for "split-perm" p-value (default=NULL).
...	Other arguments specific to screen.meth.

Details

Intercepts in regression models are assumed to be zero ($\mu_1=\mu_2=0$). You might need to center the input data prior to running Differential Regression.

Value

List consisting of

`pval.onesided` "One-sided" p-value.
`pval.twosided` "Two-sided" p-value. Ignore all `"*.twosided` results.
`teststat` 2 times Log-likelihood-ratio statistics
`weights.nulldistr`
 Estimated weights of weighted-sum-of-chi2s.
`active` List of active-sets obtained in screening step.
`beta` Regression coefficients (MLE) obtained in cleaning-step.

Author(s)

n.stadler

Examples

```
##set seed
set.seed(1)

##number of predictors / sample size
p <- 100
n <- 80

##predictor matrices
x1 <- matrix(rnorm(n*p),n,p)
x2 <- matrix(rnorm(n*p),n,p)

##active-sets and regression coefficients
act1 <- sample(1:p,5)
act2 <- c(act1[1:3],sample(setdiff(1:p,act1),2))
beta1 <- beta2 <- rep(0,p)
beta1[act1] <- 0.5
beta2[act2] <- 0.5

##response vectors
y1 <- x1%*%as.matrix(beta1)+rnorm(n,sd=1)
y2 <- x2%*%as.matrix(beta2)+rnorm(n,sd=1)

##run diffregr
split1 <- sample(1:n,50)#samples for screening (condition 1)
split2 <- sample(1:n,50)#samples for screening (condition 2)
fit <- diffregr_singlesplit(y1,y2,x1,x2,split1,split2)
fit$pval.onesided#p-value
```

dot_plot	<i>Create a plot showing the edges with the highest partial correlation in any cluster.</i>
----------	---

Description

This function takes the output of `het_cv_glasso` or `mixglasso` and creates a plot of the highest scoring edges along the y axis, where, the edge in each cluster is represented by a circle whose area is proportional to the smallest mean of the two nodes that make up the edge, and the position along the y axis shows the partial correlation of the edge.

Usage

```
dot_plot(net.clustering, p.corr.thresh = 0.25, hard.limit = 50,
         display = TRUE, node.names = rownames(net.clustering$Mu),
         group.names = sort(unique(net.clustering$comp)),
         dot.size.range = c(3, 12))
```

Arguments

<code>net.clustering</code>	A network clustering object as returned by <code>het_cv_glasso</code> or <code>mixglasso</code> .
<code>p.corr.thresh</code>	Cutoff for the partial correlations; only edges with absolute partial correlation > <code>p.corr.thresh</code> (in any cluster) will be displayed.
<code>hard.limit</code>	Additional hard limit on the number of edges to display. If <code>p.corr.thresh</code> results in more edges than <code>hard.limit</code> , only <code>hard.limit</code> edges with the highest partial correlation are returned.
<code>display</code>	If TRUE, print the plot to the current output device.
<code>node.names</code>	Names for the nodes in the network.
<code>group.names</code>	Names for the clusters or groups.
<code>dot.size.range</code>	Graphical parameter for scaling the size of the circles (dots) representing an edge in each cluster.

Value

Returns a `ggplot2` object. If `display=TRUE`, additionally displays the plot.

Examples

```
n = 500
p = 10
s = 0.9
n.comp = 3

# Create different mean vectors
Mu = matrix(0,p,n.comp)

# Define non-zero means in each group (non-overlapping)
nonzero.mean = split(sample(1:p),rep(1:n.comp,length=p))

# Set non-zero means to fixed value
```

```

for(k in 1:n.comp){
  Mu[nonzero.mean[[k]],k] = -2/sqrt(ceiling(p/n.comp))
}

# Generate data
sim.result = sim_mix_networks(n, p, n.comp, s, Mu=Mu)
mixglasso.result = mixglasso(sim.result$data, n.comp=3)
mixglasso.clustering = mixglasso.result$models[[mixglasso.result$bic.opt]]

dot_plot(mixglasso.clustering, p.corr.thresh=0.5)

```

error.bars

Error bars for plotCV

Description

Error bars for plotCV

Usage

```
error.bars(x, upper, lower, width = 0.02, ...)
```

Arguments

x	no descr
upper	no descr
lower	no descr
width	no descr
...	no descr

Value

no descr

Author(s)

n.stadler

est2.my.ev2

Weights of sum-w-chi2

Description

Compute weights of sum-w-chi2 (2nd order simplification)

Usage

```
est2.my.ev2(sig1, sig2, sig, act1, act2, act, include.mean = FALSE)
```

Arguments

sig1	no descr
sig2	no descr
sig	no descr
act1	no descr
act2	no descr
act	no descr
include.mean	no descr

Details

*expansion of W in two directions ("dimf>dimg direction" & "dimf>dimg direction") *simplified computation of weights is obtained by assuming H0 and that $X_u \sim X_v$ holds

Value

no descr

Author(s)

n.stadler

est2.my.ev2.diffregr *Compute weights of sum-w-chi2 (2nd order simplification)*

Description

*expansion of W in two directions ("dimf>dimg direction" & "dimf>dimg direction") *simplified computation of weights is obtained by assuming H0 and that $X_u \sim X_v$ holds

Usage

```
est2.my.ev2.diffregr(y1, y2, x1, x2, beta1, beta2, beta, act1, act2, act)
```

Arguments

y1	no descr
y2	no descr
x1	no descr
x2	no descr
beta1	no descr
beta2	no descr
beta	no descr
act1	no descr
act2	no descr
act	no descr

Value

no descr

Author(s)

n.stadler

 est2.my.ev3

Compute weights of sum-of-weighted-chi2s

Description

Compute weights of sum-of-weighted-chi2s

Usage

```
est2.my.ev3(sig1, sig2, sig, act1, act2, act, include.mean = FALSE)
```

Arguments

sig1	MLE (covariance matrix) sample 1
sig2	MLE (covariance matrix) sample 2
sig	Pooled MLE (covariance matrix)
act1	Active-set sample 1
act2	Active-set sample 2
act	Pooled active-set
include.mean	Should the mean be included in the likelihood?

Details

*'2nd order simplification': 1) Factor out $(1-v_i)^{(d1+d2)}$ "expansion in $\dim f > \dim g$ direction (old terminology)" 2) Factor out $(1-\mu)^{d0}$ *simplified computation of weights is obtained without further invoking H0, or assuming $X_u \sim X_v$

Value

Eigenvalues of M, respectively the weights.

Author(s)

n.stadler

est2.my.ev3.diffregr *Compute weights of sum-of-weighted-chi2s*

Description

Compute weights of sum-of-weighted-chi2s

Usage

```
est2.my.ev3.diffregr(y1, y2, x1, x2, beta1, beta2, beta, act1, act2, act)
```

Arguments

y1	Response vector sample 1.
y2	Response vector sample 2.
x1	Predictor matrix sample 1.
x2	Predictor matrix sample 2.
beta1	MLE (regression coefficients) sample 1.
beta2	MLE (regression coefficients) sample 2.
beta	Pooled MLE (regression coefficients).
act1	Active-set sample 1
act2	Active-set sample 2
act	Pooled active-set

Details

*'2nd order simplification': 1) Factor out $(1-v_i)^{(d1+d2)}$ "expansion in $\dim f > \dim g$ direction (old terminology)" 2) Factor out $(1-\mu)^{d0}$ *simplified computation of weights is obtained without further invoking H0, or assuming $X_u \sim X_v$

Value

Eigenvalues of M, respectively the weights.

Author(s)

n.stadler

est2.ww.mat.diffregr *Estimate weights*

Description

Estimate weights

Usage

```
est2.ww.mat.diffregr(y1, y2, x1, x2, beta1, beta2, beta, act1, act2, act)
```

Arguments

y1	no descr
y2	no descr
x1	no descr
x2	no descr
beta1	no descr
beta2	no descr
beta	no descr
act1	no descr
act2	no descr
act	no descr

Details

estimate W-matrix (using plug-in estimates of Beta-matrix); calculate eigenvalues(W-matrix)

Value

no descr

Author(s)

n.stadler

 est2.ww.mat2

Weights of sum-w-chi2

Description

Compute weights of sum-w-chi2 (1st order simplification)

Usage

```
est2.ww.mat2(sig1, sig2, sig, act1, act2, act, include.mean = FALSE)
```

Arguments

sig1	no descr
sig2	no descr
sig	no descr
act1	no descr
act2	no descr
act	no descr
include.mean	no descr

Value

no descr

Author(s)

n.stadler

 est2.ww.mat2.diffregr *Estimate weights*

Description

Estimate weights

Usage

```
est2.ww.mat2.diffregr(y1, y2, x1, x2, beta1, beta2, beta, act1, act2, act)
```

Arguments

y1	no descr
y2	no descr
x1	no descr
x2	no descr
beta1	no descr
beta2	no descr
beta	no descr
act1	no descr
act2	no descr
act	no descr

Value

no descr

Author(s)

n.stadler

export_network	<i>Export networks as a CSV table.</i>
----------------	--

Description

This function takes the output of [het_cv_glasso](#) or [mixglasso](#) and exports it as a text table in CSV format, where each entry in the table records an edge in one group and its partial correlation.

Usage

```
export_network(net.clustering, file = "network_table.csv",
  node.names = rownames(net.clustering$Mu),
  group.names = sort(unique(net.clustering$comp)),
  p.corr.thresh = 0.2, ...)
```

Arguments

net.clustering	A network clustering object as returned by screen_cv.glasso or mixglasso .
file	Filename to save the network table under.
node.names	Names for the nodes in the network. If NULL, names from net.clustering will be used.
group.names	Names for the clusters or groups. If NULL, names from net.clustering will be used (by default these are integers 1:numClusters).
p.corr.thresh	Threshold applied to the absolute partial correlations. Edges that are below the threshold in all of the groups are not exported. Using a negative value will export all possible edges (including those with zero partial correlation).
...	Further parameters passed to write.csv .

Value

Function does not return anything.

Author(s)

Frank Dondelinger

Examples

```
n = 500
p = 10
s = 0.9
n.comp = 3

# Create different mean vectors
Mu = matrix(0,p,n.comp)

# Define non-zero means in each group (non-overlapping)
nonzero.mean = split(sample(1:p),rep(1:n.comp,length=p))

# Set non-zero means to fixed value
for(k in 1:n.comp){
  Mu[nonzero.mean[[k]],k] = -2/sqrt(ceiling(p/n.comp))
}

# Generate data
sim.result = sim_mix_networks(n, p, n.comp, s, Mu=Mu)
mixglasso.result = mixglasso(sim.result$data, n.comp=3)
mixglasso.clustering = mixglasso.result$models[[mixglasso.result$bic.opt]]

## Not run:
# Save network in CSV format suitable for Cytoscape import
export_network(mixglasso.clustering, file='nethet_network.csv',
              p.corr.thresh=0.25, quote=FALSE)

## End(Not run)
```

EXPStep.mix

Performs EStep

Description

Performs EStep

Usage

```
EXPStep.mix(logphi, mix.prob)
```

Arguments

logphi	no descr
mix.prob	no descr

Value

list consisting of

- u responsibilities
- LL loglikelihood

Author(s)

n.stadler

func.uinit	<i>Initialization of MixGLasso</i>
------------	------------------------------------

Description

Initialization of responsibilities

Usage

```
func.uinit(x, n.comp, init = "kmeans", my.cl = NULL,
           nstart.kmeans = 1, iter.max.kmeans = 10, modelname.hc = "EII")
```

Arguments

x	Observed data
n.comp	Number of mixture components
init	Method used for initialization init='cl.init','r.means','random','kmeans','kmeans.hc','hc'
my.cl	Initial cluster assignments; need to be provided if init='cl.init' (otherwise this param is ignored)
nstart.kmeans	Number of random starts in kmeans; default=1
iter.max.kmeans	Maximal number of iteration in kmeans; default=10
modelname.hc	Model class used in hc; default='EII'

Value

a list consisting of

- u responsibilities

Author(s)

n.stadler

generate_2networks *Generate sparse invcov with overlap*

Description

Generate two sparse inverse covariance matrices with overlap

Usage

```
generate_2networks(p, graph = "random", n.nz = rep(p, 2),
  n.nz.common = p, n.hub = 2, n.hub.diff = 1, magn.nz.diff = 0.8,
  magn.nz.common = 0.9, magn.diag = 0, emin = 0.1, verbose = FALSE)
```

Arguments

p	number of nodes
graph	'random' or 'hub'
n.nz	number of edges per graph (only for graph='random')
n.nz.common	number of edges uncommon between graphs (only for graph='random')
n.hub	number of hubs (only for graph='hub')
n.hub.diff	number of different hubs
magn.nz.diff	default=0.9
magn.nz.common	default=0.9
magn.diag	default=0
emin	default=0.1 (see ?huge.generator)
verbose	If verbose=FALSE then tracing output is disabled.

Value

Two sparse inverse covariance matrices with overlap

Examples

```
n <- 70
p <- 30

## Specifiy sparse inverse covariance matrices,
## with number of edges in common equal to ~ 0.8*p
gen.net <- generate_2networks(p,graph='random',n.nz=rep(p,2),
  n.nz.common=ceiling(p*0.8))

invcov1 <- gen.net[[1]]
invcov2 <- gen.net[[2]]

plot_2networks(invcov1, invcov2, label.pos=0, label.cex=0.7)
```

generate_inv_cov	<i>generate_inv_cov</i>
------------------	-------------------------

Description

Generate an inverse covariance matrix with a given sparsity and dimensionality

Usage

```
generate_inv_cov(p = 162, sparsity = 0.7)
```

Arguments

p	Dimensionality of the matrix.
sparsity	Determined the proportion of non-zero off-diagonal entries.

Details

This function generates an inverse covariance matrix, with at most $(1-\text{sparsity}) * p(p-1)$ non-zero off-diagonal entries, where the non-zero entries are sampled from a beta distribution.

Value

A p by p positive definite inverse covariance matrix.

Examples

```
generate_inv_cov(p=162)
```

getinvcov	<i>Generate an inverse covariance matrix with a given sparsity and dimensionality</i>
-----------	---

Description

Generate an inverse covariance matrix with a given sparsity and dimensionality

Usage

```
getinvcov(p, s, a.diff = 5, b.diff = 5, magn.diag = 0, emin = 0.1)
```

Arguments

p	Dimensionality
s	Sparsity
a.diff	binomial parameter
b.diff	binomial parameter
magn.diag	Magnitude
emin	e min

Value

Inverse covariance matrix Internal function

ggmgsa_multisplit *Multi-split GGMGSA (parallelized computation)*

Description

Multi-split GGMGSA (parallelized computation)

Usage

```
ggmgsa_multisplit(x1, x2, b.splits = 50, gene.sets, gene.names,
  gs.names = NULL, method.p.adjust = "fdr",
  order.adj.agg = "agg-adj", mc.flag = FALSE, mc.set.seed = TRUE,
  mc.preschedule = TRUE, mc.cores = getOption("mc.cores", 2L),
  verbose = TRUE, ...)
```

Arguments

x1	Expression matrix for condition 1 (mean zero is required).
x2	Expression matrix for condition 2 (mean zero is required).
b.splits	Number of random data splits (default=50).
gene.sets	List of gene-sets.
gene.names	Gene names. Each column in x1 (and x2) corresponds to a gene.
gs.names	Gene-set names (default=NULL).
method.p.adjust	Method for p-value adjustment (default='fdr').
order.adj.agg	Order of aggregation and adjustment of p-values. Options: 'agg-adj' (default), 'adj-agg'.
mc.flag	If TRUE use parallel execution for each b.splits via function mclapply of package parallel.
mc.set.seed	See mclapply. Default=TRUE
mc.preschedule	See mclapply. Default=TRUE
mc.cores	Number of cores to use in parallel execution. Defaults to mc.cores option if set, or 2 otherwise.
verbose	If TRUE, show output progress.
...	Other arguments (see diffnet_singlesplit).

Details

Computation can be parallelized over many data splits.

Value

List consisting of

medagg.pval	Median aggregated p-values
meinshagg.pval	Meinshausen aggregated p-values
pval	matrix of p-values before correction and adjustment, $\text{dim}(\text{pval})=(\text{number of gene-sets})\times(\text{number of splits})$
teststatmed	median aggregated test-statistic
teststatmed.bic	median aggregated bic-corrected test-statistic
teststatmed.aic	median aggregated aic-corrected test-statistic
teststat	matrix of test-statistics, $\text{dim}(\text{teststat})=(\text{number of gene-sets})\times(\text{number of splits})$
rel.edgeinter	normalized intersection of edges in condition 1 and 2
df1	degrees of freedom of GGM obtained from condition 1
df2	degrees of freedom of GGM obtained from condition 2
df12	degrees of freedom of GGM obtained from pooled data (condition 1 and 2)

Author(s)

n.stadler

Examples

```
#####
##This example illustrates the use of GGMGSA      ##
#####

## Generate networks
set.seed(1)
p <- 9#network with p nodes
n <- 40
hub.net <- generate_2networks(p,graph='hub',n.hub=3,n.hub.diff=1)#generate hub networks
invcov1 <- hub.net[[1]]
invcov2 <- hub.net[[2]]
plot_2networks(invcov1,invcov2,label.pos=0,label.cex=0.7)

## Generate data
library('mvtnorm')
x1 <- rmvnorm(n,mean = rep(0,p), sigma = cov2cor(solve(invcov1)))
x2 <- rmvnorm(n,mean = rep(0,p), sigma = cov2cor(solve(invcov2)))

## Run DiffNet
# fit.dn <- diffnet_multisplit(x1,x2,b.splits=2,verbose=FALSE)
# fit.dn$medagg.pval

## Identify hubs with 'gene-sets'
gene.names <- paste('G',1:p,sep='')
gsets <- split(gene.names,rep(1:3,each=3))

## Run GGM-GSA
```

```

fit.gmgsa <- ggmgsa_multisplit(x1,x2,b.splits=2,gsets, gene.names,verbose=FALSE)
summary(fit.gmgsa)
fit.gmgsa$medagg.pval#median aggregated p-values
p.adjust(apply(fit.gmgsa$pval,1,median),method='fdr')#or: first median aggregation,
#second fdr-correction

```

ggmgsa_singlesplit *Single-split GGMGSA*

Description

Single-split GGMGSA

Usage

```

ggmgsa_singlesplit(x1, x2, gene.sets, gene.names,
  method.p.adjust = "fdr", verbose = TRUE, ...)

```

Arguments

x1	centered (scaled) data for condition 1
x2	centered (scaled) data for condition 2
gene.sets	List of gene-sets.
gene.names	Gene names. Each column in x1 (and x2) corresponds to a gene.
method.p.adjust	Method for p-value adjustment (default='fdr').
verbose	If TRUE, show output progress.
...	Other arguments (see diffnet_singlesplit).

Value

List of results.

Author(s)

n.stadler

glasso.invcor	<i>Graphical Lasso based on inverse covariance penalty</i>
---------------	--

Description

Graphical Lasso based on inverse covariance penalty

Usage

```
glasso.invcor(s, rho, penalize.diagonal, term = 10^{ -3 })
```

Arguments

s	no descr
rho	no descr
penalize.diagonal	no descr
term	no descr

Value

w; wi; iter

Author(s)

n.stadler

glasso.invcov	<i>Graphical Lasso based on inverse correlation penalty</i>
---------------	---

Description

Graphical Lasso based on inverse correlation penalty

Usage

```
glasso.invcov(s, rho, penalize.diagonal, term = 10^{ -3 })
```

Arguments

s	no descr
rho	no descr
penalize.diagonal	no descr
term	no descr

Value

w; wi; iter

Author(s)

n.stadler

`glasso.parcor`*Graphical Lasso based on partial correlation penalty*

Description

Graphical Lasso based on partial correlation penalty

Usage

```
glasso.parcor(s, rho, penalize.diagonal, maxiter = 1000, term = 10^{
-3 }, verbose = FALSE)
```

Arguments

<code>s</code>	no descr
<code>rho</code>	no descr
<code>penalize.diagonal</code>	no descr
<code>maxiter</code>	no descr
<code>term</code>	no descr
<code>verbose</code>	set to TRUE to print out progress.

Value

w; wi; iter

Author(s)

n.stadler

`gsea.highdimT2`*GSA based on HighdimT2*

Description

GSA based on HighdimT2

Usage

```
gsea.highdimT2(x1, x2, gene.sets, gene.names, gs.names = NULL,
method = "test.sd", method.p.adjust = "fdr")
```

Arguments

x1	no descr
x2	no descr
gene.sets	no descr
gene.names	no descr
gs.names	no descr
method	no descr
method.p.adjust	no descr

Value

no descr

Author(s)

n.stadler

gsea.iriz

Irizarry approach for gene-set testing

Description

Irizarry approach for gene-set testing

Usage

```
gsea.iriz(x1, x2, gene.sets, gene.names, gs.names = NULL,
          method.p.adjust = "fdr", alternative = "two-sided")
```

Arguments

x1	Expression matrix (condition 1)
x2	Expression matrix (condition 2)
gene.sets	List of gene-sets
gene.names	Gene names
gs.names	Gene-set names
method.p.adjust	Method for p-value adjustment (default='fdr')
alternative	Default='two-sided' (uses two-sided p-values).

Details

Implements the approach described in "Gene set enrichment analysis made simple" by Irizarry et al (2011). It tests for shift and/or change in scale of the distribution.

Value

List consisting of

pval.shift	p-values measuring shift
pval.scale	p-values measuring scale
pval.combined	combined p-values (minimum of pval.shift and pval.scale)

Author(s)

n.stadler

Examples

```
n <- 100
p <- 20
x1 <- matrix(rnorm(n*p),n,p)
x2 <- matrix(rnorm(n*p),n,p)
gene.names <- paste('G',1:p,sep=' ')
gsets <- split(gene.names,rep(1:4,each=5))
fit <- gsea.iriz(x1,x2,gsets,gene.names)
fit$pvals.combined

x2[,1:3] <- x2[,1:3]+0.5#variables 1-3 of first gene-set are upregulated
fit <- gsea.iriz(x1,x2,gsets,gene.names)
fit$pvals.combined
```

gsea.iriz.scale	<i>Irizarry approach (scale only)</i>
-----------------	---------------------------------------

Description

Irizarry approach (scale only)

Usage

```
gsea.iriz.scale(x1, x2, gene.sets, gene.names, gs.names = NULL,
  method.p.adjust = "fdr", alternative = "two-sided")
```

Arguments

x1	no descr
x2	no descr
gene.sets	no descr
gene.names	no descr
gs.names	no descr
method.p.adjust	no descr
alternative	no descr

Value

no descr

Author(s)

n.stadler

gsea.iriz.shift	<i>Irizarry approach (shift only)</i>
-----------------	---------------------------------------

Description

Irizarry approach (shift only)

Usage

```
gsea.iriz.shift(x1, x2, gene.sets, gene.names, gs.names = NULL,  
method.p.adjust = "fdr", alternative = "two-sided")
```

Arguments

x1	no descr
x2	no descr
gene.sets	no descr
gene.names	no descr
gs.names	no descr
method.p.adjust	no descr
alternative	no descr

Value

no descr

Author(s)

n.stadler

gsea.t2cov	<i>GSA using T2cov-test</i>
------------	-----------------------------

Description

GSA using T2cov-test

Usage

```
gsea.t2cov(x1, x2, gene.sets, gene.names, gs.names = NULL,
           method = "t2cov.lr", method.p.adjust = "fdr")
```

Arguments

x1	expression matrix (condition 1)
x2	expression matrix (condition 2)
gene.sets	list of gene-sets
gene.names	gene names
gs.names	gene-set names
method	method for testing equality of covariance matrices
method.p.adjust	method for p-value adjustment (default: 'fdr')

Value

list of results

Author(s)

n.stadler

het_cv_glasso	<i>Cross-validated glasso on heterogeneous dataset with grouping</i>
---------------	--

Description

Run glasso on a heterogeneous dataset to obtain networks (inverse covariance matrices) of the variables in the dataset for each pre-specified group of samples.

Usage

```
het_cv_glasso(data, grouping = rep(1, dim(data)[1]), mc.flag = FALSE,
              use.package = "huge", normalise = FALSE, verbose = FALSE, ...)
```

Arguments

<code>data</code>	The heterogenous network data. Needs to be a <code>num.samples</code> by <code>dim.samples</code> matrix or dataframe.
<code>grouping</code>	The grouping of samples; a vector of length <code>num.samples</code> , with <code>num.groups</code> unique elements.
<code>mc.flag</code>	Whether to use parallel processing via package <code>mclapply</code> to distribute the glasso estimation over different groups.
<code>use.package</code>	'glasso' for glasso package, or 'huge' for huge package (default)
<code>normalise</code>	If TRUE, normalise the columns of the data matrix before running glasso.
<code>verbose</code>	If TRUE, output progress.
<code>...</code>	Further parameters to be passed to <code>screen_cv.glasso</code> .

Details

This function runs the graphical lasso with cross-validation to determine the best parameter lambda for each group of samples. Note that this function defaults to using package `huge` (rather than package `glasso`) unless otherwise specified, as it tends to be more numerically stable.

Value

Returns a list with named elements 'Sig', 'SigInv', 'Mu', 'Sigma.diag', 'group.names' and 'var.names'. The variables `Sig` and `SigInv` are arrays of size `dim.samples` by `dim.samples` by `num.groups`, where the first two dimensions contain the (inverse) covariance matrix for the network obtained by running glasso on group `k`. Variables `Mu` and `Sigma.diag` contain the mean and variance of the input data, and `group.names` and `var.names` contains the names for the groups and variables in the data (if specified as `colnames` of the input data matrix).

Examples

```
n = 100
p = 25

# Generate networks with random means and covariances.
sim.result = sim_mix_networks(n, p, n.comp=3)

test.data = sim.result$data
test.labels = sim.result$comp

# Reconstruct networks for each component
networks = het_cv_glasso(data=test.data, grouping=test.labels)
```

hugepath

Graphical Lasso path with huge package

Description

Graphical Lasso path with huge package

Usage

```
hugepath(s, rho.list, penalize.diagonal = NULL, trace = NULL)
```

Arguments

s	no descr
rholist	no descr
penalize.diagonal	no descr
trace	no descr

Value

no descr

Author(s)

n.stadler

inf.mat

Information Matrix of Gaussian Graphical Model

Description

Compute Information Matrix of Gaussian Graphical Model

Usage

```
inf.mat(Sig, include.mean = FALSE)
```

Arguments

Sig	Sig=solve(SigInv) true covariance matrix under H0
include.mean	no descr

Details

computes $E_0[s(Y;\Omega)s(Y;\Omega)']$ where $s(Y;\Omega)=(d/d\Omega) \text{LogLik}$

Value

no descr

Author(s)

n.stadler

invcov2parcor	<i>Convert inverse covariance to partial correlation</i>
---------------	--

Description

Convert inverse covariance to partial correlation

Usage

```
invcov2parcor(invcov)
```

Arguments

invcov	Inverse covariance matrix
--------	---------------------------

Value

The partial correlation matrix.

Examples

```
inv.cov = generate_inv_cov(p=25)
p.corr = invcov2parcor(inv.cov)
```

invcov2parcor_array	<i>Convert inverse covariance to partial correlation for several inverse covariance matrices collected in an array.</i>
---------------------	---

Description

Convert inverse covariance to partial correlation for several inverse covariance matrices collected in an array.

Usage

```
invcov2parcor_array(invcov.array)
```

Arguments

invcov.array	Array of inverse covariance matrices, of dimension numNodes by numNodes by numComps.
--------------	--

Value

Array of partial correlation matrices of dimension numNodes by numNodes by numComps

Examples

```
invcov.array = sapply(1:5, function(x) generate_inv_cov(p=25), simplify='array')
p.corr = invcov2parcor_array(invcov.array)
```

lambda.max	<i>Lambdamax</i>
------------	------------------

Description

Lambdamax

Usage

lambda.max(x)

Arguments

x	no descr
---	----------

Value

no descr

Author(s)

n.stadler

lambdagrid_lin	<i>Lambda-grid</i>
----------------	--------------------

Description

Lambda-grid (linear scale)

Usage

lambdagrid_lin(lambda.min, lambda.max, nr.gridpoints)

Arguments

lambda.min	no descr
lambda.max	no descr
nr.gridpoints	no descr

Value

no descr

Author(s)

n.stadler

lambdagrid_mult *Lambda-grid*

Description

Lambda-grid (log scale)

Usage

lambdagrid_mult(lambda.min, lambda.max, nr.gridpoints)

Arguments

lambda.min	no descr
lambda.max	no descr
nr.gridpoints	no descr

Value

no descr

Author(s)

n.stadler

loglik_mix *Log-likelihood for mixture model*

Description

Log-likelihood for mixture model

Usage

loglik_mix(x, mix.prob, Mu, Sig)

Arguments

x	no descr
mix.prob	no descr
Mu	no descr
Sig	no descr

Value

log-likelihood

Author(s)

n.stadler

logratio *Log-likelihood-ratio statistics used in DiffNet*

Description

Log-likelihood-ratio statistics used in Differential Network

Usage

```
logratio(x1, x2, x, sig1, sig2, sig, mu1, mu2, mu)
```

Arguments

x1	data-matrix sample 1
x2	data-matrix sample 2
x	pooled data-matrix
sig1	covariance sample 1
sig2	covariance sample 2
sig	pooled covariance
mu1	mean sample 1
mu2	mean sample 2
mu	pooled mean

Value

Returns a list with named elements 'twiceLR', 'sig1', 'sig2', 'sig'. 'twiceLR' is twice the log-likelihood-ratio statistic.

Author(s)

n.stadler

Examples

```
x1=matrix(rnorm(100),50,2)
x2=matrix(rnorm(100),50,2)
logratio(x1,x2,rbind(x1,x2),diag(1,2),diag(1,2),diag(1,2),c(0,0),c(0,0),c(0,0))$twiceLR
```

logratio.diffregr *Log-likelihood ratio statistics for Differential Regression.*

Description

Log-likelihood ratio statistics for Differential Regression.

Usage

```
logratio.diffregr(y1, y2, y, xx1, xx2, xx, beta1, beta2, beta)
```

Arguments

y1	Response vector condition 1.
y2	Response vector condition 2.
y	Pooled response vector.
xx1	Predictor matrix condition 1.
xx2	Predictor matrix condition 2.
xx	Pooled predictor matrix
beta1	Regression coefficients condition 1.
beta2	Regression coefficients condition 2.
beta	Pooled regression coefficients.

Value

2 times log-likelihood ratio statistics.

Author(s)

n.stadler

make_grid *Make grid*

Description

Make grid

Usage

```
make_grid(lambda.min, lambda.max, nr.gridpoints,
           method = "lambdagrid_mult")
```

Arguments

lambda.min	no descr
lambda.max	no descr
nr.gridpoints	no descr
method	no descr

Value

no descr

Author(s)

n.stadler

`mcov`*Compute covariance matrix*

Description

Compute covariance matrix

Usage`mcov(x, include.mean, covMethod = "ML")`**Arguments**

<code>x</code>	no descr
<code>include.mean</code>	no descr
<code>covMethod</code>	no descr

Value

no descr

Author(s)

n.stadler

`mixglasso`*mixglasso*

Description

mixglasso

Usage

```

mixglasso(x, n.comp, lambda = sqrt(2 * nrow(x) * log(ncol(x)))/2,
  pen = "glasso.parcor", init = "kmeans.hc", my.cl = NULL,
  modelName.hc = "VVV", nstart.kmeans = 1, iter.max.kmeans = 10,
  term = 10^{ -3 }, min.compsize = 5, save.allfits = FALSE,
  filename = "mixglasso_fit.rda", mc.flag = FALSE,
  mc.set.seed = FALSE, mc.preschedule = FALSE,
  mc.cores = getOption("mc.cores", 2L), ...)

```

Arguments

<code>x</code>	Input data matrix
<code>n.comp</code>	Number of mixture components. If <code>n.comp</code> is a vector, <code>mixglasso</code> will estimate a model for each number of mixture components, and return a list of models, as well as their BIC and MMDL scores and the index of the best model according to each score.
<code>lambda</code>	Regularization parameter. Default= $\sqrt{2*n*\log(p)}/2$
<code>pen</code>	Determines form of penalty: <code>glasso.parcor</code> (default) to penalise the partial correlation matrix, <code>glasso.invcov</code> to penalise the inverse covariance matrix (this corresponds to classical graphical lasso), <code>glasso.invcor</code> to penalise the inverse correlation matrix.
<code>init</code>	Initialization. Method used for initialization <code>init='cl.init','r.means','random','kmeans','kmeans.hc','h'</code> Default='kmeans'
<code>my.cl</code>	Initial cluster assignments; need to be provided if <code>init='cl.init'</code> (otherwise this param is ignored). Default=NULL
<code>modelName.hc</code>	Model class used in hc. Default="VVV"
<code>nstart.kmeans</code>	Number of random starts in kmeans; default=1
<code>iter.max.kmeans</code>	Maximal number of iteration in kmeans; default=10
<code>term</code>	Termination criterion of EM algorithm. Default= 10^{-3}
<code>min.compsize</code>	Stop EM if any(<code>compsize</code>)< <code>min.compsize</code> ; Default=5
<code>save.allfits</code>	If TRUE, save output of <code>mixglasso</code> for all k's.
<code>filename</code>	If <code>save.allfits</code> is TRUE, output of <code>mixglasso</code> will be saved as <code>paste(filename, _fit.mixgl_k.rda, sep='')</code> .
<code>mc.flag</code>	If TRUE use parallel execution for each <code>n.comp</code> via function <code>mclapply</code> of package <code>parallel</code> .
<code>mc.set.seed</code>	See <code>mclapply</code> . Default=FALSE
<code>mc.preschedule</code>	See <code>mclapply</code> . Default=FALSE
<code>mc.cores</code>	Number of cores to use in parallel execution. Defaults to <code>mc.cores</code> option if set, or 2 otherwise.
<code>...</code>	Other arguments. See <code>mixglasso_init</code>

Details

Runs mixture of graphical lasso network clustering with one or several numbers of mixture components.

Value

A list with elements:

<code>models</code>	List with each element <code>i</code> containing an S3 object of class 'nethetclustering' that contains the result of fitting the mixture graphical lasso model with <code>n.comps[i]</code> components. See the documentation of <code>mixglasso_ncomp_fixed</code> for the description of this object.
<code>bic</code>	BIC for all fits.
<code>mmdl</code>	Minimum description length score for all fits.

comp	Component assignments for all fits.
bix.opt	Index of model with optimal BIC score.
mmdl.opt	Index of model with optimal MMDL score.

Author(s)

n.stadler

Examples

```
#####
##This an example of how to use MixGLasso##
#####

##generate data
set.seed(1)
n <- 1000
n.comp <- 3
p <- 10

# Create different mean vectors
Mu <- matrix(0,p,n.comp)

nonzero.mean <- split(sample(1:p),rep(1:n.comp,length=p))
for(k in 1:n.comp){
  Mu[nonzero.mean[[k]],k] <- -2/sqrt(ceiling(p/n.comp))
}

sim <- sim_mix_networks(n, p, n.comp, Mu=Mu)

##run mixglasso
set.seed(1)
fit1 <- mixglasso(sim$data,n.comp=1:6)
fit1$bic
set.seed(1)
fit2 <- mixglasso(sim$data,n.comp=6)
fit2$bic
set.seed(1)
fit3 <- mixglasso(sim$data,n.comp=1:6,lambda=0)
set.seed(1)
fit4 <- mixglasso(sim$data,n.comp=1:6,lambda=Inf)
#set.seed(1)
#fit5 <- bwprun_mixglasso(sim$data,n.comp=1,n.comp.max=5,selection.crit='bic')
#plot(fit5$selcrit,ylab='bic',xlab='Num.Comps',type='b')

##compare bic
library('ggplot2')
plotting.frame <-
  data.frame(BIC= c(fit1$bic, fit3$bic, fit4$bic),
            Num.Comps=rep(1:6, 3),
            Lambda=rep(c('Default',
                          'Lambda = 0',
                          'Lambda = Inf'),
                       each=6))
```

```
p <- ggplot(plotting.frame) +
  geom_line(aes(x=Num.Comps, y=BIC, colour=Lambda))

print(p)
```

 mixglasso_init

mixglasso_init

Description

mixglasso_init (initialization and lambda set by user)

Usage

```
mixglasso_init(x, n.comp, lambda, u.init, mix.prob.init, gamma = 0.5,
  pen = "glasso.parcor", penalize.diagonal = FALSE, term = 10^{
  -3 }, miniter = 5, maxiter = 1000, min.compsize = 5,
  show.trace = FALSE)
```

Arguments

x	Input data matrix
n.comp	Number of mixture components
lambda	Regularization parameter
u.init	Initial responsibilities
mix.prob.init	Initial component probabilities
gamma	Determines form of penalty
pen	Determines form of penalty: glasso.parcor (default), glasso.invcov, glasso.invcor
penalize.diagonal	Should the diagonal of the inverse covariance matrix be penalized ? Default=FALSE (recommended)
term	Termination criterion of EM algorithm. Default=10 ⁻³
miniter	Minimal number of EM iteration before 'stop EM if any(compsize)<min.compsize' applies. Default=5
maxiter	Maximal number of EM iteration. Default=1000
min.compsize	Stop EM if any(compsize)<min.compsize; Default=5
show.trace	Should information during execution be printed ? Default=FALSE

Details

This function runs mixglasso; requires initialization (u.init,mix.prob.init)

Value

list consisting of

mix.prob	Component probabilities
Mu	Component specific mean vectors
Sig	Component specific covariance matrices
SigInv	Component specific inverse covariance matrices
iter	Number of EM iterations
loglik	Log-likelihood
bic	$-\loglik + \log(n) * DF / 2$
mmdl	$-\loglik + \text{penmmdl} / 2$
u	Component responsibilities
comp	Component assignments
compsize	Size of components
pi.comps	Component probabilities
warn	Warnings during EM algorithm

Author(s)

n.stadler

mixglasso_ncomp_fixed *mixglasso_ncomp_fixed*

Description

mixglasso_ncomp_fixed

Usage

```
mixglasso_ncomp_fixed(x, n.comp, lambda = sqrt(2 * nrow(x) *
  log(ncol(x)))/2, pen = "glasso.parcor", init = "kmeans.hc",
  my.cl = NULL, modelname.hc = "VVV", nstart.kmeans = 1,
  iter.max.kmeans = 10, term = 10^{ -3 }, min.compsize = 5, ...)
```

Arguments

x	Input data matrix
n.comp	Number of mixture components
lambda	Regularization parameter. Default= $\sqrt{2 * n * \log(p)} / 2$
pen	Determines form of penalty: glasso.parcor (default), glasso.invcov, glasso.invcor
init	Initialization. Method used for initialization init='cl.init', 'r.means', 'random', 'kmeans', 'kmeans.hc', 'h'. Default='kmeans'
my.cl	Initial cluster assignments; need to be provided if init='cl.init' (otherwise this param is ignored). Default=NULL
modelname.hc	Model class used in hc. Default="VVV"

nstart.kmeans Number of random starts in kmeans; default=1
 iter.max.kmeans Maximal number of iteration in kmeans; default=10
 term Termination criterion of EM algorithm. Default=10⁻³
 min.compsize Stop EM if any(compsize)<min.compsize; Default=5
 ... Other arguments. See mixglasso_init

Details

This function runs mixglasso

Value

see return mixglasso_init. list consisting of

mix.prob
 Mu
 Sig
 SigInv
 iter
 loglik
 bic -loglik+log(n)*DF/2
 mmdl -loglik+penmmdl/2
 u responsibilities
 comp component assignments
 compsize size of components
 pi.comps
 warn warnings during optimization

Author(s)

n.stadler

mle.ggm

MLE in GGM

Description

MLE in GGM

Usage

mle.ggm(x, wi, algorithm = "glasso_rho0", rho = NULL, include.mean)

Arguments

x	no descr
wi	no descr
algorithm	no descr
rho	no descr
include.mean	no descr

Value

no descr

Author(s)

n.stadler

MStepGlasso

MStep of MixGLasso

Description

MStep of MixGLasso

Usage

```
MStepGlasso(x, chromosome = NULL, u, v = NULL, lambda, gamma, pen,
  penalize.diagonal, equal.prob.trans = NULL, term, model = "hmm")
```

Arguments

x	no descr
chromosome	no descr
u	no descr
v	no descr
lambda	no descr
gamma	no descr
pen	no descr
penalize.diagonal	no descr
equal.prob.trans	no descr
term	no descr
model	no descr

Value

list consisting of mix.prob, Mu, Sig, SigInv

Author(s)

n.stadler

my.ev2.diffregr	<i>Computation eigenvalues</i>
-----------------	--------------------------------

Description

Computation eigenvalues

Usage

```
my.ev2.diffregr(Sig, act, act1, act2)
```

Arguments

Sig	no descr
act	no descr
act1	no descr
act2	no descr

Value

no descr

Author(s)

n.stadler

my.p.adjust	<i>P-value adjustment</i>
-------------	---------------------------

Description

P-value adjustment

Usage

```
my.p.adjust(p, method = "fdr")
```

Arguments

p	Vector of p-values.
method	Method for p-value adjustment (default='fdr').

Value

Vector of adjusted p-values.

Author(s)

n.stadler

`my.ttest`*T-test*

Description

T-test (equal variances)

Usage

```
my.ttest(x1, x2)
```

Arguments

x1 no descr

x2 no descr

Value

no descr

Author(s)

n.stadler

`my.ttest2`*T-test*

Description

T-test (unequal variances)

Usage

```
my.ttest2(x1, x2)
```

Arguments

x1 no descr

x2 no descr

Value

no descr

Author(s)

n.stadler

mytrunc.method	<i>Additional thresholding</i>
----------------	--------------------------------

Description

Additional thresholding

Usage

```
mytrunc.method(n, wi, method = "linear.growth", trunc.k = 5)
```

Arguments

n	no descr
wi	no descr
method	no descr
trunc.k	no descr

Value

no descr

Author(s)

n.stadler

perm.diffregr_pval	<i>Computation "split-perm" p-value.</i>
--------------------	--

Description

Computation "split-perm" p-value.

Usage

```
perm.diffregr_pval(y1, y2, x1, x2, act1, act2, act, n.perm)
```

Arguments

y1	Response vector condition 1.
y2	Response vector condition 2.
x1	Predictor matrix condition 1.
x2	Predictor matrix condition 2.
act1	Active-set condition 1.
act2	Active-set condition 2.
act	Pooled active-set.
n.perm	Number of permutations.

Value

Permutation based p-value.

Author(s)

n.stadler

perm.diffregr_teststat

Auxiliary function for computation of "split-perm" p-value.

Description

Auxiliary function for computation of "split-perm" p-value.

Usage

```
perm.diffregr_teststat(y1, y2, y12, x1, x2, x12)
```

Arguments

y1	Response vector condition 1.
y2	Response vector condition 2.
y12	Pooled response vector.
x1	Predictor matrix condition 1.
x2	Predictor matrix condition 2.
x12	Pooled predictor matrix

Value

Test statistic (log-likelihood-ratio statistic).

Author(s)

n.stadler

plot.diffnet	<i>Plotting function for object of class 'diffnet'</i>
--------------	--

Description

Plotting function for object of class 'diffnet'

Usage

```
## S3 method for class 'diffnet'  
plot(x, ...)
```

Arguments

x	object of class 'diffnet'
...	Further arguments.

Value

Histogram over multi-split p-values.

Author(s)

nicolas

plot.diffregr	<i>Plotting function for object of class 'diffregr'</i>
---------------	---

Description

Plotting function for object of class 'diffregr'

Usage

```
## S3 method for class 'diffregr'  
plot(x, ...)
```

Arguments

x	object of class 'diffregr'
...	Further arguments.

Value

Histogram over multi-split p-values.

Author(s)

nicolas

plot.gmgmsa	<i>Plotting function for object of class 'gmgmsa'</i>
-------------	---

Description

Plotting function for object of class 'gmgmsa'

Usage

```
## S3 method for class 'gmgmsa'  
plot(x, ...)
```

Arguments

x	object of class 'gmgmsa'
...	Further arguments.

Value

Boxplot of single-split p-values.

Author(s)

nicolas

plot.nethetclustering	<i>Plot networks</i>
-----------------------	----------------------

Description

This function takes the output of `screen_cv.glasso` or `mixglasso` and creates a network plot using the network library.

Usage

```
## S3 method for class 'nethetclustering'  
plot(x,  
  node.names = rownames(net.clustering$Mu),  
  group.names = sort(unique(net.clustering$comp)),  
  p.corr.thresh = 0.2, print.pdf = FALSE, pdf.filename = "networks",  
  ...)
```

Arguments

x	A network clustering object as returned by screen_cv.glasso or mixglasso .
node.names	Names for the nodes in the network. If NULL, names from net.clustering will be used.
group.names	Names for the clusters or groups. If NULL, names from net.clustering will be used (by default these are integers 1:numClusters).
p.corr.thresh	Threshold applied to the absolute partial correlations. Edges that are below the threshold in all of the groups are not displayed.
print.pdf	If TRUE, save the output as a PDF file.
pdf.filename	If print.pdf is TRUE, specifies the file name of the output PDF file.
...	Further arguments

Value

Returns NULL and prints out the networks (or saves them to pdf if print.pdf is TRUE. The networks are displayed as a series of nComps+1 plots, where in the first plot edge widths are shown according to the maximum partial correlation of the edge over all groups. The following plots show the edges for each group. Positive partial correlation edges are shown in black, negative ones in blue. If an edge is below the threshold on the absolute partial correlation, it is displayed in gray or light blue respectively.

plotCV

plotCV

Description

plotCV

Usage

```
plotCV(lambda, cv, cv.error, se = TRUE, type = "b", ...)
```

Arguments

lambda	no descr
cv	no descr
cv.error	no descr
se	no descr
type	no descr
...	no descr

Value

no descr

Author(s)

n.stadler

plot_2networks	<i>Plot two networks (GGMs)</i>
----------------	---------------------------------

Description

Plot two networks (GGMs)

Usage

```
plot_2networks(invcov1, invcov2, node.label = paste("X", 1:nrow(invcov1),
  sep = ""), main = c("", ""), ...)
```

Arguments

invcov1	Inverse covariance matrix of GGM1.
invcov2	Inverse covariance matrix of GGM2.
node.label	Names of nodes.
main	Vector (two elements) with network names.
...	Other arguments (see plot.network).

Value

Figure with two panels (for each network).

Author(s)

nicolas

Examples

```
n <- 70
p <- 30

## Specifiy sparse inverse covariance matrices,
## with number of edges in common equal to ~ 0.8*p
gen.net <- generate_2networks(p,graph='random',n.nz=rep(p,2),
  n.nz.common=ceiling(p*0.8))

invcov1 <- gen.net[[1]]
invcov2 <- gen.net[[2]]

plot_2networks(invcov1, invcov2, label.pos=0, label.cex=0.7)
```

```
print.nethetsummary Print function for object of class 'nethetsummary'
```

Description

Print function for object of class 'nethetsummary'

Usage

```
## S3 method for class 'nethetsummary'
print(x, ...)
```

Arguments

x	object of class 'nethetsummary'
...	Other arguments

Value

Function does not return anything.

Author(s)

frankd

```
q.matrix.diffregr Computation Q matrix
```

Description

Computation Q matrix

Usage

```
q.matrix.diffregr(Sig, a, b, s)
```

Arguments

Sig	no descr
a	no descr
b	no descr
s	no descr

Value

no descr

Author(s)

n.stadler

q.matrix.diffregr3 *Computation Q matrix*

Description

Computation Q matrix

Usage

```
q.matrix.diffregr3(beta.a, beta.b, beta, sig.a, sig.b, sig, Sig, act.a,
  act.b, ss)
```

Arguments

beta.a	no descr
beta.b	no descr
beta	no descr
sig.a	no descr
sig.b	no descr
sig	no descr
Sig	no descr
act.a	no descr
act.b	no descr
ss	no descr

Value

no descr

Author(s)

n.stadler

q.matrix.diffregr4 *Computation Q matrix*

Description

Computation Q matrix

Usage

```
q.matrix.diffregr4(b.mat, act.a, act.b, ss)
```

Arguments

b.mat	no descr
act.a	no descr
act.b	no descr
ss	no descr

Value

no descr

Author(s)

n.stadler

q.matrix3

Compute Q-matrix

Description

Compute Q-matrix

Usage

```
q.matrix3(sig, sig.a, sig.b, act.a, act.b, ss)
```

Arguments

sig	no descr
sig.a	no descr
sig.b	no descr
act.a	no descr
act.b	no descr
ss	no descr

Value

no descr

Author(s)

n.stadler

q.matrix4	<i>q.matrix4</i>
-----------	------------------

Description

q.matrix4

Usage

```
q.matrix4(b.mat, act.a, act.b, ss)
```

Arguments

b.mat	no descr
act.a	no descr
act.b	no descr
ss	no descr

Value

no descr

Author(s)

n.stadler

scatter_plot	<i>Create a scatterplot showing correlation between specific nodes in the network for each pre-specified group.</i>
--------------	---

Description

This function takes the output of [het_cv_glasso](#) or [mixglasso](#) and creates a plot showing the correlation between specified node pairs in the network for all groups. The subplots for each node pair are arranged in a numPairs by numGroups grid. Partial correlations associated with each node pair are also displayed.

Usage

```
scatter_plot(net.clustering, data, node.pairs, display = TRUE,
             node.names = rownames(net.clustering$Mu),
             group.names = sort(unique(net.clustering$comp)), cex = 1)
```

Arguments

net.clustering	A network clustering object as returned by <code>het_cv_glasso</code> or <code>mixglasso</code> .
data	Observed data for the nodes, a numObs by numNodes matrix. Note that nodes need to be in the same ordering as in node.names.
node.pairs	A matrix of size numPairs by 2, where each row contains a pair of nodes to display. If node.names is specified, names in node.pairs must correspond to elements of node.names.
display	If TRUE, print the plot to the current output device.
node.names	Names for the nodes in the network. If NULL, names from net.clustering will be used.
group.names	Names for the clusters or groups. If NULL, names from net.clustering will be used (by default these are integers 1:numClusters).
cex	Scale factor for text and symbols in plot.

Value

Returns a ggplot2 object. If display=TRUE, additionally displays the plot.

Examples

```
n = 500
p = 10
s = 0.9
n.comp = 3

# Create different mean vectors
Mu = matrix(0,p,n.comp)

# Define non-zero means in each group (non-overlapping)
nonzero.mean = split(sample(1:p),rep(1:n.comp,length=p))

# Set non-zero means to fixed value
for(k in 1:n.comp){
  Mu[nonzero.mean[[k]],k] = -2/sqrt(ceiling(p/n.comp))
}

# Generate data
sim.result = sim_mix_networks(n, p, n.comp, s, Mu=Mu)
mixglasso.result = mixglasso(sim.result$data, n.comp=3)
mixglasso.clustering = mixglasso.result$models[[mixglasso.result$bic.opt]]

# Specify edges
node.pairs = rbind(c(1,3), c(6,9),c(7,8))

# Create scatter plots of specified edges
scatter_plot(mixglasso.clustering, data=sim.result$data,
             node.pairs=node.pairs)
```

screen_aic.glasso *AIC-tuned glasso with additional thresholding*

Description

AIC-tuned glasso with additional thresholding

Usage

```
screen_aic.glasso(x, include.mean = TRUE, length.lambda = 20,
  lambdamin.ratio = ifelse(ncol(x) > nrow(x), 0.01, 0.001),
  penalize.diagonal = FALSE, plot.it = FALSE,
  trunc.method = "linear.growth", trunc.k = 5, use.package = "huge",
  verbose = FALSE)
```

Arguments

x	The input data. Needs to be a num.samples by dim.samples matrix.
include.mean	Include mean in likelihood. TRUE / FALSE (default).
length.lambda	Length of lambda path to consider (default=20).
lambdamin.ratio	Ratio lambda.min/lambda.max.
penalize.diagonal	If TRUE apply penalization to diagonal of inverse covariance as well. (default=FALSE)
plot.it	TRUE / FALSE (default)
trunc.method	None / linear.growth (default) / sqrt.growth
trunc.k	truncation constant, number of samples per predictor (default=5)
use.package	'glasso' or 'huge' (default).
verbose	If TRUE, output la.min, la.max and la.opt (default=FALSE).

Value

Returns a list with named elements 'rho.opt', 'wi', 'wi.orig'. Variable rho.opt is the optimal (scaled) penalization parameter ($\text{rho.opt} = 2 * \text{la.opt} / n$). The variables wi and wi.orig are matrices of size dim.samples by dim.samples containing the truncated and untruncated inverse covariance matrix.

Author(s)

n.stadler

Examples

```
n=50
p=5
x=matrix(rnorm(n*p),n,p)
wihat=screen_aic.glasso(x,length.lambda=5)$wi
```

screen_bic.glasso *BIC-tuned glasso with additional thresholding*

Description

BIC-tuned glasso with additional thresholding

Usage

```
screen_bic.glasso(x, include.mean = TRUE, length.lambda = 20,
  lambdamin.ratio = ifelse(ncol(x) > nrow(x), 0.01, 0.001),
  penalize.diagonal = FALSE, plot.it = FALSE,
  trunc.method = "linear.growth", trunc.k = 5, use.package = "huge",
  verbose = FALSE)
```

Arguments

x	The input data. Needs to be a num.samples by dim.samples matrix.
include.mean	Include mean in likelihood. TRUE / FALSE (default).
length.lambda	Length of lambda path to consider (default=20).
lambdamin.ratio	Ratio lambda.min/lambda.max.
penalize.diagonal	If TRUE apply penalization to diagonal of inverse covariance as well. (default=FALSE)
plot.it	TRUE / FALSE (default)
trunc.method	None / linear.growth (default) / sqrt.growth
trunc.k	truncation constant, number of samples per predictor (default=5)
use.package	'glasso' or 'huge' (default).
verbose	If TRUE, output la.min, la.max and la.opt (default=FALSE).

Value

Returns a list with named elements 'rho.opt', 'wi', 'wi.orig', Variable rho.opt is the optimal (scaled) penalization parameter ($\text{rho.opt}=2*\text{la.opt}/n$). The variables wi and wi.orig are matrices of size dim.samples by dim.samples containing the truncated and untruncated inverse covariance matrix.

Author(s)

n.stadler

Examples

```
n=50
p=5
x=matrix(rnorm(n*p),n,p)
wihat=screen_bic.glasso(x,length.lambda=5)$wi
```

screen_cv.glasso *Cross-validated glasso with additional thresholding*

Description

Cross-validated glasso with additional thresholding

Usage

```
screen_cv.glasso(x, include.mean = FALSE, folds = min(10, dim(x)[1]),
  length.lambda = 20, lambdamin.ratio = ifelse(ncol(x) > nrow(x), 0.01,
  0.001), penalize.diagonal = FALSE, trunc.method = "linear.growth",
  trunc.k = 5, plot.it = FALSE, se = FALSE, use.package = "huge",
  verbose = FALSE)
```

Arguments

x	The input data. Needs to be a num.samples by dim.samples matrix.
include.mean	Include mean in likelihood. TRUE / FALSE (default).
folds	Number of folds in the cross-validation (default=10).
length.lambda	Length of lambda path to consider (default=20).
lambdamin.ratio	Ratio lambda.min/lambda.max.
penalize.diagonal	If TRUE apply penalization to diagonal of inverse covariance as well. (default=FALSE)
trunc.method	None / linear.growth (default) / sqrt.growth
trunc.k	truncation constant, number of samples per predictor (default=5)
plot.it	TRUE / FALSE (default)
se	default=FALSE.
use.package	'glasso' or 'huge' (default).
verbose	If TRUE, output la.min, la.max and la.opt (default=FALSE).

Details

Run glasso on a single dataset, using cross-validation to estimate the penalty parameter lambda. Performs additional thresholding (optionally).

Value

Returns a list with named elements 'rho.opt', 'w', 'wi', 'wi.orig', 'mu'. Variable rho.opt is the optimal (scaled) penalization parameter (rho.opt=2*la.opt/n). Variable w is the estimated covariance matrix. The variables wi and wi.orig are matrices of size dim.samples by dim.samples containing the truncated and untruncated inverse covariance matrix. Variable mu is the mean of the input data.

Author(s)

n.stadler

Examples

```
n=50
p=5
x=matrix(rnorm(n*p),n,p)
wihat=screen_cv.glasso(x,folds=2)$wi
```

screen_cv1se.lasso *Cross-validated Lasso screening (lambda.1se-rule)*

Description

Cross-validated Lasso screening (lambda.1se-rule)

Usage

```
screen_cv1se.lasso(x, y)
```

Arguments

x	Predictor matrix
y	Response vector

Value

Active-set

Author(s)

n.stadler

Examples

```
screen_cv1se.lasso(matrix(rnorm(5000),50,100),rnorm(50))
```

screen_cvfix.lasso *Cross-validated Lasso screening and upper bound on number of predictors.*

Description

Cross-validated Lasso screening and upper bound on number of predictors

Usage

```
screen_cvfix.lasso(x, y, no.predictors = 10)
```

Arguments

x	Predictor matrix.
y	Response vector.
no.predictors	Upper bound on number of active predictors,

Details

Computes Lasso coefficients (cross-validation optimal lambda). Truncates smallest coefficients to zero such that there are no more than no.predictors non-zero coefficients

Value

Active-set.

Author(s)

n.stadler

Examples

```
screen_cvfix.lasso(matrix(rnorm(5000),50,100),rnorm(50))
```

screen_cvmin.lasso *Cross-validation lasso screening (lambda.min-rule)*

Description

Cross-validated Lasso screening (lambda.min-rule)

Usage

```
screen_cvmin.lasso(x, y)
```

Arguments

x	Predictor matrix
y	Response vector

Value

Active-set

Author(s)

n.stadler

Examples

```
screen_cvmin.lasso(matrix(rnorm(5000),50,100),rnorm(50))
```

screen_cvsqrt.lasso *Cross-validated Lasso screening and sqrt-truncation.*

Description

Cross-validated Lasso screening and sqrt-truncation.

Usage

```
screen_cvsqrt.lasso(x, y)
```

Arguments

x	Predictor matrix.
y	Response vector.

Details

Computes Lasso coefficients (cross-validation optimal lambda). Truncates smallest coefficients to zero, such that there are no more than sqrt(n) non-zero coefficients.

Value

Active-set.

Author(s)

n.stadler

Examples

```
screen_cvsqrt.lasso(matrix(rnorm(5000), 50, 100), rnorm(50))
```

screen_cvtrunc.lasso *Cross-validated Lasso screening and additional truncation.*

Description

Cross-validated Lasso screening and additional truncation.

Usage

```
screen_cvtrunc.lasso(x, y, k.trunc = 5)
```

Arguments

x	Predictor matrix.
y	Response vector.
k.trunc	Truncation constant="number of samples per predictor" (default=5).

Details

Computes Lasso coefficients (cross-validation optimal lambda). Truncates smallest coefficients to zero, such that there are no more than $n/k.trunc$ non-zero coefficients.

Value

Active-set.

Author(s)

n.stadler

Examples

```
screen_cvtrunc.lasso(matrix(rnorm(5000),50,100),rnorm(50))
```

screen_full

Screen_full

Description

Screen_full

Usage

```
screen_full(x, include.mean = NULL, length.lambda = NULL,
  trunc.method = NULL, trunc.k = NULL)
```

Arguments

x	no descr
include.mean	no descr
length.lambda	no descr
trunc.method	no descr
trunc.k	no descr

Value

no descr

Author(s)

n.stadler

screen_shrink	<i>Shrinkage approach for estimating Gaussian graphical model</i>
---------------	---

Description

Shrinkage approach for estimating Gaussian graphical model

Usage

```
screen_shrink(x, include.mean = NULL, trunc.method = "linear.growth",
             trunc.k = 5)
```

Arguments

x	The input data. Needs to be a num.samples by dim.samples matrix.
include.mean	Include mean in likelihood. TRUE / FALSE (default).
trunc.method	None / linear.growth (default) / sqrt.growth
trunc.k	truncation constant, number of samples per predictor (default=5)

Value

Returns a list with named elements 'rho.opt', 'wi', 'wi.orig'. Variable rho.opt=NULL (no tuning parameter involved). The variables wi and wi.orig are matrices of size dim.samples by dim.samples containing the truncated and untruncated inverse covariance matrix.

Author(s)

n.stadler

shapiro_screen	<i>Filter "non-normal" genes</i>
----------------	----------------------------------

Description

Filter "non-normal" genes

Usage

```
shapiro_screen(x1, x2, sign.level = 0.001)
```

Arguments

x1	expression matrix (condition 1)
x2	expression matrix (condition 2)
sign.level	sign.level in Shapiro-Wilk tests (default: sign.level=0.001)

Details

Discarding genes which have Shapiro-Wilk p-value (corrected for multiplicity) smaller than sign.level in either of the two conditions. We used sign.level=0.001 in the GGMSA paper.

Value

list consisting of

x1.filt expression matrix (condition 1) after filtering
 x2.filt expression matrix (condition 2) after filtering

Author(s)

n.stadler

sim_mix

Simulate from mixture model.

Description

Simulate from mixture model with multi-variate Gaussian or t-distributed components.

Usage

```
sim_mix(n, n.comp, mix.prob, Mu, Sig, dist = "norm", df = 2)
```

Arguments

n sample size
 n.comp number of mixture components ("comps")
 mix.prob mixing probabilities (need to sum to 1)
 Mu matrix of component-specific mean vectors
 Sig array of component-specific covariance matrices
 dist 'norm' for Gaussian components, 't' for t-distributed components
 df degrees of freedom of the t-distribution (not used for Gaussian distribution),
 default=2

Value

a list consisting of:

S component assignments
 X observed data matrix

Author(s)

n.stadler

Examples

```
n.comp = 4
p = 5 # dimensionality
Mu = matrix(rep(0, p), p, n.comp)
Sigma = array(diag(p), c(p, p, n.comp))
mix.prob = rep(0.25, n.comp)

sim_mix(100, n.comp, mix.prob, Mu, Sigma)
```

sim_mix_networks *sim_mix_networks*

Description

Generate inverse covariances, means, mixing probabilities, and simulate data from resulting mixture model.

Usage

```
sim_mix_networks(n, p, n.comp, sparsity = 0.7, mix.prob = rep(1/n.comp,
  n.comp), Mu = NULL, Sig = NULL, ...)
```

Arguments

n	Number of data points to simulate.
p	Dimensionality of the data.
n.comp	Number of components of the mixture model.
sparsity	Determines the proportion of non-zero off-diagonal entries.
mix.prob	Mixture probabilities for the components; defaults to uniform distribution.
Mu	Means for the mixture components, a p by n.comp matrix. If NULL, sampled from a standard Gaussian.
Sig	Covariances for the mixture components, a p by p by n.comp array. If NULL, generated using generate_inv_cov .
...	Further arguments passed to sim_mix .

Details

This function generates n.comp mean vectors from a standard Gaussian and n.comp covariance matrices, with at most $(1-sparsity)*p(p-1)/2$ non-zero off-diagonal entries, where the non-zero entries are sampled from a beta distribution. Then it uses [sim_mix](#) to simulate from a mixture model with these means and covariance matrices.

Means Mu and covariance matrices Sig can also be supplied by the user.

Value

A list with components: Mu Means of the mixture components. Sig Covariances of the mixture components. data Simulated data, a n by p matrix. S Component assignments, a vector of length n.

Examples

```
# Generate dataset with 100 samples of dimensionality 30, and 4 components
test.data = sim_mix_networks(n=100, p=30, n.comp=4)
```

sparse_conc	<i>Generates sparse inverse covariance matrices</i>
-------------	---

Description

Generates sparse inverse covariance matrices

Usage

```
sparse_conc(p, K, s, s.common, magn.nz = 0.5, scale.parcor = TRUE)
```

Arguments

p	Dimensionality of inverse covariance matrix
K	Number of inverse covariance matrices
s	Number of non-zero entries per inverse covariance matrix
s.common	Number of non-zero entries shared across different inverse covariance matrices
magn.nz	Magnitude of non-zero elements
scale.parcor	Should SigInv be scaled to have diagonal equal one, siginv=parcor ?

Value

SigInv: list of inverse covariance matrices

Author(s)

n.stadler

summary.diffnet	<i>Summary function for object of class 'diffnet'</i>
-----------------	---

Description

Summary function for object of class 'diffnet'

Usage

```
## S3 method for class 'diffnet'
summary(object, ...)
```

Arguments

object	object of class 'diffnet'
...	Other arguments.

Value

aggregated p-values

Author(s)

nicolas

summary.diffreg *Summary function for object of class 'diffreg'*

Description

Summary function for object of class 'diffreg'

Usage

```
## S3 method for class 'diffreg'
summary(object, ...)
```

Arguments

object	object of class 'diffreg'
...	Other arguments

Value

aggregated p-values

Author(s)

nicolas

summary.gmgsa *Summary function for object of class 'gmgsa'*

Description

Summary function for object of class 'gmgsa'

Usage

```
## S3 method for class 'gmgsa'
summary(object, ...)
```

Arguments

object	object of class 'gmgsa'
...	Other arguments

Value

aggregated p-values

Author(s)

nicolas

summary.nethetclustering

Summary function for object of class 'nethetclustering'

Description

Summary function for object of class 'nethetclustering'

Usage

```
## S3 method for class 'nethetclustering'  
summary(object, ...)
```

Arguments

object	object of class 'nethetclustering'
...	Other arguments

Value

Network statistics (a 'nethetsummary' object)

Author(s)

frankd

sumoffdiag

Sum of non-diag elements of a matrix

Description

Sum of non-diag elements of a matrix

Usage

```
sumoffdiag(m)
```

Arguments

m	no descr
---	----------

Value

Sum of non-diag elements

Author(s)

n.stadler

symmklldist	<i>Compute symmetric kull-back leibler distance</i>
-------------	---

Description

Compute symmetric kull-back leibler distance

Usage

```
symmklldist(mu1, mu2, sig1, sig2)
```

Arguments

mu1	no descr
mu2	no descr
sig1	no descr
sig2	no descr

Value

symmetric kull-back leibler distance

Author(s)

n.stadler

t2cov.lr	<i>Classical likelihood-ratio test</i>
----------	--

Description

Classical likelihood-ratio test (equality of covariance matrices)

Usage

```
t2cov.lr(x1, x2, include.mean = FALSE)
```

Arguments

x1	no descr
x2	no descr
include.mean	no descr

Value

no descr

Author(s)

n.stadler

t2diagcov.lr

Diagonal-restricted likelihood-ratio test

Description

Diagonal-restricted likelihood-ratio test

Usage

```
t2diagcov.lr(x1, x2, include.mean = FALSE)
```

Arguments

x1	no descr
x2	no descr
include.mean	no descr

Value

no descr

Author(s)

n.stadler

test.sd

High-Dim Two-Sample Test (Srivastava, 2006)

Description

High-Dim Two-Sample Test (Srivastava, 2006)

Usage

```
test.sd(x1, x2)
```

Arguments

x1	no descr
x2	no descr

Value

no descr

Author(s)

n.stadler

test.t2

HotellingsT2

Description

HotellingsT2

Usage

test.t2(x1, x2)

Arguments

x1	no descr
x2	no descr

Value

no descr

Author(s)

n.stadler

tr

Compute trace of matrix

Description

Compute trace of matrix

Usage

tr(m)

Arguments

m	no descr
---	----------

Value

trace of matrix

Author(s)

n.stadler

`twosample_single_regr` *old single-split function for diffregr*

Description

Old single-split function for diffregr

Usage

```
twosample_single_regr(y1, y2, x1, x2, n.screen.pop1 = 100,
  n.screen.pop2 = 100, screen.meth = "screen_cvmin.lasso",
  compute.evals = "est2.my.ev3.diffregr")
```

Arguments

<code>y1</code>	no descr
<code>y2</code>	no descr
<code>x1</code>	no descr
<code>x2</code>	no descr
<code>n.screen.pop1</code>	no descr
<code>n.screen.pop2</code>	no descr
<code>screen.meth</code>	no descr
<code>compute.evals</code>	no descr

Value

no descr

Author(s)

n.stadler

`w.kldist`

Distance between comps based on symm. kl-distance

Description

Distance between comps based on symm. kl-distance

Usage

```
w.kldist(Mu, Sig)
```

Arguments

<code>Mu</code>	no descr
<code>Sig</code>	no descr

Value

list consisting of
comp.kldist
min.comp.kldist

Author(s)

n.stadler

ww.mat

Weight-matrix and eigenvalues

Description

Calculates weight-matrix and eigenvalues

Usage

```
ww.mat(imat, act, act1, act2)
```

Arguments

imat	no descr
act	I_uv
act1	I_u
act2	I_v

Details

calculation based on true information matrix

Value

no descr

Author(s)

n.stadler

 ww.mat.diffregr

Computation M matrix and eigenvalues

Description

Computation M matrix and eigenvalues

Usage

```
ww.mat.diffregr(Sig, act, act1, act2)
```

Arguments

Sig	no descr
act	no descr
act1	no descr
act2	no descr

Value

no descr

Author(s)

n.stadler

 ww.mat2

Calculates eigenvalues of weight-matrix (using 1st order simplification)

Description

Calculates eigenvalues of weight-matrix (using 1st order simplification)

Usage

```
ww.mat2(imat, act, act1, act2)
```

Arguments

imat	no descr
act	I_uv
act1	I_u
act2	I_v

Details

calculation based on true information matrix

Value

no descr

Author(s)

n.stadler

ww.mat2.diffregr

Computation M matrix and eigenvalues

Description

Computation M matrix and eigenvalues

Usage

ww.mat2.diffregr(Sig, act, act1, act2)

Arguments

Sig	no descr
act	no descr
act1	no descr
act2	no descr

Value

no descr

Author(s)

n.stadler

Index

- * **Removed**
 - screen_shrink, 79
- * **examples**
 - screen_shrink, 79
- * **export**
 - screen_shrink, 79
- * **fixed.**
 - screen_shrink, 79
- * **internal**
 - agg.pval, 4
 - agg.score.iris.scale, 5
 - agg.score.iris.shift, 5
 - aic.glasso, 6
 - beta.mat, 7
 - beta.mat.diffregr, 8
 - bic.glasso, 8
 - buildDotPlotDataFrame, 9
 - cv.fold, 11
 - cv.glasso, 12
 - diffnet_pval, 15
 - error.bars, 25
 - est2.my.ev2, 25
 - est2.my.ev2.diffregr, 26
 - est2.my.ev3, 27
 - est2.my.ev3.diffregr, 28
 - est2.ww.mat.diffregr, 29
 - est2.ww.mat2, 30
 - est2.ww.mat2.diffregr, 30
 - EXPStep.mix, 32
 - func.uinit, 33
 - getinvcov, 35
 - glasso.invcov, 39
 - glasso.invcov, 39
 - glasso.parcov, 40
 - gsea.highdimT2, 40
 - gsea.iris.scale, 42
 - gsea.iris.shift, 43
 - gsea.t2cov, 44
 - hugepath, 45
 - inf.mat, 46
 - lambda.max, 48
 - lambda.grid.lin, 48
 - lambda.grid.mult, 49
 - loglik_mix, 49
 - logratio.diffregr, 51
 - make_grid, 51
 - mcov, 52
 - mixglasso_ncomp_fixed, 56
 - mle.ggm, 57
 - MStepGlasso, 58
 - my.ev2.diffregr, 59
 - my.p.adjust, 59
 - my.ttest, 60
 - my.ttest2, 60
 - mytrunc.method, 61
 - perm.diffregr_pval, 61
 - perm.diffregr_teststat, 62
 - plotCV, 65
 - q.matrix.diffregr, 67
 - q.matrix.diffregr3, 68
 - q.matrix.diffregr4, 68
 - q.matrix3, 69
 - q.matrix4, 70
 - screen_full, 78
 - screen_shrink, 79
 - shapiro_screen, 79
 - sparse_conc, 82
 - sumoffdiag, 84
 - symmklldist, 85
 - t2cov.lr, 85
 - t2diagcov.lr, 86
 - test.sd, 86
 - test.t2, 87
 - tr, 87
 - twosample_single_regr, 88
 - w.kldist, 88
 - ww.mat, 89
 - ww.mat.diffregr, 90
 - ww.mat2, 90
 - ww.mat2.diffregr, 91
- * **is**
 - screen_shrink, 79
- * **n=50**
 - screen_shrink, 79
- * **p=5**
 - screen_shrink, 79

- * **package**
 - screen_shrink, 79
- * **parcor**
 - screen_shrink, 79
- * **until**
 - screen_shrink, 79
- * **wihat=screen_shrink(x)\$wi**
 - screen_shrink, 79
- * **x=matrix(rnorm(n*p),n,p)**
 - screen_shrink, 79
- agg.pval, 4
- agg.score.iriz.scale, 5
- agg.score.iriz.shift, 5
- aggpval, 6
- aic.glasso, 6
- beta.mat, 7
- beta.mat.diffregr, 8
- bic.glasso, 8
- buildDotPlotDataFrame, 9
- bwprun_mixglasso, 10
- cv.fold, 11
- cv.glasso, 12
- diffnet_multisplit, 13
- diffnet_pval, 15
- diffnet_singlesplit, 16
- diffregr_multisplit, 18
- diffregr_pval, 20
- diffregr_singlesplit, 22
- dot_plot, 24
- error.bars, 25
- est2.my.ev2, 25
- est2.my.ev2.diffregr, 26
- est2.my.ev3, 27
- est2.my.ev3.diffregr, 28
- est2.ww.mat.diffregr, 29
- est2.ww.mat2, 30
- est2.ww.mat2.diffregr, 30
- export_network, 31
- EXPStep.mix, 32
- func.uinit, 33
- generate_2networks, 34
- generate_inv_cov, 35, 81
- getinvcov, 35
- ggmgsa_multisplit, 36
- ggmgsa_singlesplit, 38
- glasso.invcov, 39
- glasso.invcov, 39
- glasso.parcov, 40
- gsea.highdimT2, 40
- gsea.iriz, 41
- gsea.iriz.scale, 42
- gsea.iriz.shift, 43
- gsea.t2cov, 44
- het_cv_glasso, 24, 31, 44, 70, 71
- hugepath, 45
- inf.mat, 46
- invcov2parcor, 47
- invcov2parcor_array, 47
- lambda.max, 48
- lambdagrid_lin, 48
- lambdagrid_mult, 49
- loglik_mix, 49
- logratio, 50
- logratio.diffregr, 51
- make_grid, 51
- mcov, 52
- mixglasso, 24, 31, 52, 64, 65, 70, 71
- mixglasso_init, 55
- mixglasso_ncomp_fixed, 56
- mle.ggm, 57
- MStepGlasso, 58
- my.ev2.diffregr, 59
- my.p.adjust, 59
- my.ttest, 60
- my.ttest2, 60
- mytrunc.method, 61
- NetHet-package, 4
- perm.diffregr_pval, 61
- perm.diffregr_teststat, 62
- plot.diffnet, 63
- plot.diffregr, 63
- plot.ggmgsa, 64
- plot.nethetclustering, 64
- plot_2networks, 66
- plotCV, 65
- print.nethetsummary, 67
- q.matrix.diffregr, 67
- q.matrix.diffregr3, 68
- q.matrix.diffregr4, 68
- q.matrix3, 69
- q.matrix4, 70
- scatter_plot, 70
- screen_aic.glasso, 72

screen_bic.glasso, 73
screen_cv.glasso, 31, 64, 65, 74
screen_cv1se.lasso, 75
screen_cvfix.lasso, 75
screen_cvmin.lasso, 76
screen_cvsqrt.lasso, 77
screen_cvtrunc.lasso, 77
screen_full, 78
screen_shrink, 79
shapiro_screen, 79
sim_mix, 80, 81
sim_mix_networks, 81
sparse_conc, 82
summary.diffnet, 82
summary.diffregr, 83
summary.gmgmsa, 83
summary.nethetclustering, 84
sumoffdiag, 84
symmkldist, 85

t2cov.lr, 85
t2diagcov.lr, 86
test.sd, 86
test.t2, 87
tr, 87
twosample_single_regr, 88

w.kldist, 88
write.csv, 31
ww.mat, 89
ww.mat.diffregr, 90
ww.mat2, 90
ww.mat2.diffregr, 91