

Package ‘AnVIL’

April 6, 2026

Title Bioconductor on the AnVIL compute environment

Version 1.23.10

Description The AnVIL is a cloud computing resource developed in part by the National Human Genome Research Institute. The AnVIL package provides programatic access to the Dockstore, Leonardo, Rawls, TDR, and Terra RESTful programming interfaces. For platform-specific user-level functionality, see either the AnVILGCP or AnVILAz package.

License Artistic-2.0

Encoding UTF-8

Depends R (>= 4.6.0), dplyr, AnVILBase

Imports stats, utils, methods, futile.logger, GCPtools, jsonlite, httr, digest, rapiclient, yaml, tibble, shiny, DT, miniUI, htmltools, BiocBaseUtils

Suggests knitr, rmarkdown, testthat, withr, readr, BiocStyle, devtools, AnVILAz, AnVILGCP, lifecycle

Collate utilities.R authenticate.R api.R AnVIL-package.R Service.R Services.R Leonardo.R Terra.R Rawls.R Dockstore.R TDR.R gadgets.R zzz.R

URL <https://github.com/Bioconductor/AnVIL>

BugReports <https://github.com/Bioconductor/AnVIL/issues>

VignetteBuilder knitr

biocViews Infrastructure

RoxygenNote 7.3.3

Roxygen list(markdown = TRUE)

Date 2026-03-31

git_url <https://git.bioconductor.org/packages/AnVIL>

git_branch devel

git_last_commit 0433718

git_last_commit_date 2026-03-31

Repository Bioconductor 3.23

Date/Publication 2026-04-06

Author Marcel Ramos [aut, cre] (ORCID:

[<https://orcid.org/0000-0002-3242-0582>](https://orcid.org/0000-0002-3242-0582)),

Martin Morgan [aut] (ORCID: [<https://orcid.org/0000-0002-5874-8148>](https://orcid.org/0000-0002-5874-8148)),

Kayla Interdonato [aut],

Yubo Cheng [aut],

Nitesh Turaga [aut],

BJ Stubbs [ctb],

Vincent Carey [ctb],

Sehyun Oh [ctb],

Sweta Gopaulakrishnan [ctb],

Valerie Obenchain [ctb]

Maintainer Marcel Ramos <marcel.ramos@sph.cuny.edu>

Contents

AnVIL-package	2
.gadget_run	3
avworkspace_gadget	4
Service	5
Services	6
utilities	9

Index	10
--------------	-----------

AnVIL-package

AnVIL: Bioconductor on the AnVIL compute environment

Description

The AnVIL is a cloud computing resource developed in part by the National Human Genome Research Institute. The AnVIL package provides programatic access to the Dockstore, Leonardo, Rawls, TDR, and Terra RESTful programming interfaces. For platform-specific user-level functionality, see either the AnVILGCP or AnVILAz package.

Author(s)

Maintainer: Marcel Ramos <marcel.ramos@sph.cuny.edu> ([ORCID](#))

Authors:

- Martin Morgan ([ORCID](#))
- Kayla Interdonato
- Yubo Cheng
- Nitesh Turaga

Other contributors:

- BJ Stubbs [contributor]
- Vincent Carey [contributor]
- Sehyun Oh [contributor]
- Sweta Gopaulakrishnan [contributor]
- Valerie Obenchain [contributor]

See Also

Useful links:

- <https://github.com/Bioconductor/AnVIL>
- Report bugs at <https://github.com/Bioconductor/AnVIL/issues>

.gadget_run

Functions to implement AnVIL gadget interfaces

Description

Functions documented on this page are primarily intended for package developers wishing to implement gadgets (graphical interfaces) to navigating AnVIL-generated tables.

.gadget_run() presents the user with a tibble-navigating gadget, returning the value of DONE_FUN if a row of the tibble is selected, or NULL.

Usage

```
.gadget_run(title, tibble, DONE_FUN)
```

Arguments

title	character(1) (required) title to appear at the base of the gadget, e.g., "AnVIL Workspaces".
tibble	a tibble or data.frame to be displayed in the gadget.
DONE_FUN	a function of two arguments, tibble and row_selected. The tibble is the tibble provided as an argument to .gadget_run(). row_selected is the row selected in the gadget by the user. The function is only invoked when the user selects a valid row.

Value

.gadget_run() returns the result of DONE_FUN() if a row has been selected by the user, or NULL if no row is selected (the user presses Cancel, or Done prior to selecting any row).

Examples

```
tibble <- avworkspaces(platform = AnVILGCP::gcp())
DONE_FUN <- function(tibble, row_selected) {
  selected <- slice(tibble, row_selected)
  with(selected, paste0(namespace, "/", name))
}
.gadget_run("AnVIL Example", tibble, DONE_FUN)
```

avworkspace_gadget *Graphical user interfaces for common AnVIL operations*

Description

workspace() allows choice of workspace for subsequent use. It is the equivalent of displaying workspaces with avworkspaces(), and setting the selected workspace with avworkspace().

browse_workspace() uses browseURL() to open a browser window pointing to the Terra workspace.

table() allows choice of table in the current workspace (selected by avworkspace() or workspace()) to be returned as a tibble. It is equivalent to invoking avtables() to show available tables, and avtable() to retrieve the selected table.

workflow() allows choice of workflow for retrieval. It is the equivalent of avworkflows() for listing available workflows, and avworkflow_configuration_get() for retrieving the workflow.

Usage

```
avworkspace_gadget()
```

```
browse_workspace(use_avworkspace = TRUE)
```

```
avtable_gadget()
```

```
avworkflow_gadget()
```

Arguments

```
use_avworkspace
```

logical(1) when TRUE (default), use the selected workspace (via workspace() or avworkspace() if available). If FALSE or no workspace is currently selected, use workspace() to allow the user to select the workspace.

Value

workspace() returns the selected workspace as a character(1) using the format namespace/name, or character(0) if no workspace is selected.

browse_workspace() returns the status of a system() call to launch the browser, invisibly.

table() returns a tibble representing the selected AnVIL table.

`workflow()` returns an `avworkflow_configuration` object representing the inputs and outputs of the selected workflow. This can be edited and updated as described in the "Running an AnVIL workflow within R" vignette.

Examples

```
workspace()
browse_workspace(use_avworkspace = FALSE)
tbl <- table()
wkflw <- avworkflow_gadget()
```

Service *RESTful service constructor*

Description

RESTful service constructor

Usage

```
Service(
  service,
  host,
  config = httr::config(),
  authenticate = TRUE,
  api_url = character(),
  package = "AnVIL",
  schemes = "https",
  api_reference_url = api_url,
  api_reference_md5sum = character(),
  api_reference_version = character(),
  api_reference_headers = NULL,
  ...
)
```

Arguments

<code>service</code>	character(1) The Service class name, e.g., "terra".
<code>host</code>	character(1) host name that provides the API resource, e.g., "leonardo.dsde-prod.broadinstitute".
<code>config</code>	httr::config() curl options
<code>authenticate</code>	logical(1) use credentials from authentication service file 'auth.json' in the specified package?
<code>api_url</code>	optional character(1) url location of OpenAPI .json or .yaml service definition.
<code>package</code>	character(1) (default AnVIL) The package where 'api.json' yaml and (optionally) 'auth.json' files are located.

<code>schemes</code>	<code>character(1)</code> (default <code>'https'</code>) Specifies the transfer protocol supported by the API service.
<code>api_reference_url</code>	<code>character(1)</code> path to reference API. See Details.
<code>api_reference_md5sum</code>	<code>character(1)</code> the result of <code>tools::md5sum()</code> applied to the reference API.
<code>api_reference_version</code>	<code>character(1)</code> the version of the reference API. This is used to check that the version of the service matches the version of the reference API. It is usually set by the service generation function, e.g., <code>AnVIL::Rawls()</code> .
<code>api_reference_headers</code>	<code>character()</code> header(s) to be used (e.g., <code>c(Authorization = paste("Bearer", token))</code>) when retrieving the API reference for validation.
<code>...</code>	additional arguments passed to <code>rapiclient::get_api()</code>

Details

This function creates a RESTful interface to a service provided by a host, e.g., "leonardo.dsdeprod.broadinstitute.org". The function requires an OpenAPI `.json` or `.yaml` specification as well as an (optional) `.json` authentication token. These files are located in the source directory of a package, at `<package>/inst/service/<service>/api.json` and `<package>/inst/service/<service>/auth.json`, or at `api_url`.

When provided, the `api_reference_md5sum` is used to check that the file described at `api_reference_url` has the same checksum as an author-validated version.

The service is usually a singleton, created at the package level during `.onLoad()`.

Value

An object of class `Service`.

Examples

```
.MyService <- setClass("MyService", contains = "Service")

MyService <- function() {
  .MyService(Service("my_service", host="my.api.org"))
}
```

Services

RESTful services useful for AnVIL developers

Description

RESTful services useful for AnVIL developers

Usage

```

empty_object

operations(x, ..., .deprecated = FALSE)

## S4 method for signature 'Service'
operations(x, ..., auto_unbox = FALSE, .deprecated = FALSE)

schemas(x)

tags(x, .tags, .deprecated = FALSE)

## S4 method for signature 'Service'
x$name

Leonardo()

Terra()

Rawls()

Dockstore()

TDR()

```

Arguments

x	A Service instance, usually a singleton provided by the package and documented on this page, e.g., leonardo or terra.
...	additional arguments passed to methods or, for operations, Service-method, to the internal get_operation() function.
.deprecated	optional logical(1) include deprecated operations?
auto_unbox	logical(1) If FALSE (default) do not automatically 'unbox' R scalar values from JSON arrays to JSON scalars.
.tags	optional character() of tags to use to filter operations.
name	A symbol representing a defined operation, e.g., leonardo\$listRuntimes().

Format

An object of class list of length 0.

Details

Note the services Terra(), Rawls(), and Leonardo() require the GCPtools package for authentication to the Google Cloud Platform. See ?GCPtools::gcloud_access_token() for details.

When using \$ to select a service, some arguments appear in 'body' of the REST request. Specify these using the .__body__= argument, as illustrated for createBillingProjectFull(), below.

Value

`empty_object` returns a representation to be used as arguments in function calls expecting the empty json object `{}`.

`Leonardo()` creates the API of the Leonardo container deployment service at <https://leonardo.dsde-prod.broadinstitute.org/api-docs.yaml>.

`Terra()` creates the API of the Terra cloud computational environment at <https://api.firecloud.org/>.

`Rawls()` creates the API of the Rawls cloud computational environment at <https://rawls.dsde-prod.broadinstitute.org>.

`Dockstore()` represents the API of the Dockstore platform to share Docker-based tools in CWL or WDL or Nextflow at <https://dockstore.org>

`TDR()` creates the API of the Terra Data Repository to work with snapshot data in the Terra Data Repository at <https://data.terra.bio>.

Examples

```
empty_object
```

```
## Arguments to be used as the 'body' (`.__body__=`) of a REST query
Terra()$createBillingProjectFull      # 6 arguments...
## ... passed as `.__body__ = list(...)`
args(Terra()$createBillingProjectFull)
```

```
library(GCPtools)
if (gcloud_exists())
  Leonardo()
```

```
library(GCPtools)
if (gcloud_exists()) {
  tags(Terra())
  tags(Terra(), "Billing")
}
```

```
library(GCPtools)
if (gcloud_exists()) {
  tags(Rawls())
  tags(Rawls(), "billing")
}
```

```
Dockstore()
```

```
library(GCPtools)
if (gcloud_exists())
  TDR()
```

utilities

Utilities for managing library paths

Description

`add_libpaths()`: Add local library paths to `.libPaths()`.

Usage

```
add_libpaths(paths)
```

Arguments

`paths` `character()`: vector of directories to add to `.libPaths()`. Paths that do not exist will be created.

Value

`add_libpaths()`: updated `.libPaths()`, invisibly.

Examples

```
add_libpaths("/tmp/host-site-library")
```

Index

- * **datasets**
 - Services, [6](#)
- * **internal**
 - AnVIL-package, [2](#)
 - .DollarNames.Service (Services), [6](#)
 - .gadget_run, [3](#)
 - \$, Service-method (Services), [6](#)
 - add_libpaths (utilities), [9](#)
 - AnVIL (AnVIL-package), [2](#)
 - AnVIL-package, [2](#)
 - avtable_gadget (avworkspace_gadget), [4](#)
 - avworkflow_gadget (avworkspace_gadget), [4](#)
 - avworkspace_gadget, [4](#)
 - browse_workspace (avworkspace_gadget), [4](#)
 - Dockstore (Services), [6](#)
 - Dockstore-class (Services), [6](#)
 - empty_object (Services), [6](#)
 - Leonardo (Services), [6](#)
 - Leonardo-class (Services), [6](#)
 - operations (Services), [6](#)
 - operations, Dockstore-method (Services), [6](#)
 - operations, Leonardo-method (Services), [6](#)
 - operations, Rawls-method (Services), [6](#)
 - operations, Service-method (Services), [6](#)
 - operations, TDR-method (Services), [6](#)
 - operations, Terra-method (Services), [6](#)
 - Rawls (Services), [6](#)
 - Rawls-class (Services), [6](#)
 - schemas (Services), [6](#)
 - schemas, Rawls-method (Services), [6](#)
 - schemas, Service-method (Services), [6](#)
 - schemas, Terra-method (Services), [6](#)
 - Service, [5](#)
 - Service-class (Services), [6](#)
 - Services, [6](#)
 - show, Service-method (Services), [6](#)
 - tags (Services), [6](#)
 - TDR (Services), [6](#)
 - TDR-class (Services), [6](#)
 - Terra (Services), [6](#)
 - Terra-class (Services), [6](#)
 - utilities, [9](#)