

# Package ‘MatrixRider’

May 9, 2026

**Type** Package

**Title** Obtain total affinity and occupancies for binding site matrices on a given sequence

**Version** 1.45.0

**Date** 2015-11-02

**Author** Elena Grassi

**Maintainer** Elena Grassi <grassi.e@gmail.com>

**Description** Calculates a single number for a whole sequence that reflects the propensity of a DNA binding protein to interact with it. The DNA binding protein has to be described with a PFM matrix, for example gotten from Jaspar.

**biocViews** GeneRegulation, Genetics, MotifAnnotation

**License** GPL-3

**Depends** R (>= 3.1.2)

**Imports** methods, TFBSTools, IRanges, XVector, Biostrings

**Suggests** RUnit, BiocGenerics, BiocStyle, JASPAR2014

**LinkingTo** IRanges, XVector, Biostrings, S4Vectors

**NeedsCompilation** yes

**git\_url** <https://git.bioconductor.org/packages/MatrixRider>

**git\_branch** devel

**git\_last\_commit** 795d12a

**git\_last\_commit\_date** 2026-04-28

**Repository** Bioconductor 3.24

**Date/Publication** 2026-05-08

## Contents

MatrixRider-package . . . . .	2
getSeqOccupancy . . . . .	2

<b>Index</b>	<b>4</b>
--------------	----------

---

MatrixRider-package	<i>Calculate total affinity and occupancies for binding site matrices on a given sequence</i>
---------------------	---

---

### Description

Calculates a single number for a whole sequence that reflects the propensity of a DNA binding protein to interact with it. The DNA binding protein has to be described with a PFM matrix, for example gotten from Jaspas.

### Author(s)

Elena Grassi <elena.grassi@unito.it>

### Examples

```
library(JASPAR2014)
library(TFBSTools)
library(Biostrings)
pfm <- getMatrixByID(JASPAR2014,"MA0004.1")
## The following sequence has a single perfect match
## thus it gives the same results with all cutoff values.
sequence <- DNASTring("CACGTG")
getSeqOccupancy(sequence, pfm, 0.1)
getSeqOccupancy(sequence, pfm, 1)
```

---

getSeqOccupancy	<i>Computes the total affinity or the occupancy at a given cutoff</i>
-----------------	---

---

### Description

The affinity/occupancy is calculated on the given DNASTring for the given PFMatrix (or all the ones in the PFMatrix list given).

### Usage

```
getSeqOccupancy(sequence, pfm, cutoff)
```

### Arguments

sequence	A <a href="#">DNASTring</a> object with the sequence for which affinity will be computed.
pfm	A <a href="#">PFMatrix</a> or a <a href="#">PFMatrixList</a> object with the matrixes whose affinity will be calculated. The background ( <a href="#">bg.XMatrix-method</a> ) of the given pfm is used to perform affinity calculations.
cutoff	numeric(1); between 0 and 1 (included): 0 corresponds to total affinity (i.e. summing all the affinities) while 1 to summing only values corresponding to the perfect match for a given <a href="#">PFMatrix</a> . See vignette for details on how scores are calculated. If <b>MatrixRider</b> is installed, open the vignette with <code>vignette("MatrixRider")</code> .

**Value**

numeric; the resulting total affinity calculated on the given fasta. If a [PFMatrixList](#) has been passed then a named numeric vector with the affinities for all the PFMs. The vignette has all the details on the calculations (such as PFM to PWM conversion and pseudocounts).

**Examples**

```
library(JASPAR2014)
library(TFBSTools)
library(Biostrings)
pfm <- getMatrixByID(JASPAR2014,"MA0004.1")
## The following sequence has a single perfect match
## thus it gives the same results with all cutoff values.
sequence <- DNASTring("CACGTG")
getSeqOccupancy(sequence, pfm, 0.1)
getSeqOccupancy(sequence, pfm, 1)

pfm2 <- getMatrixByID(JASPAR2014,"MA0005.1")
pfms <- PFMatrixList(pfm, pfm2)
names(pfms) <- c(name(pfm), name(pfm2))
## This calculates total affinity for both the PFMatrixes.
getSeqOccupancy(sequence, pfms, 0)
```

# Index

## \* **MatrixRider**

MatrixRider-package, [2](#)

## \* **getSeqOccupancy**

getSeqOccupancy, [2](#)

bg, XMatrix-method, [2](#)

DNAStrng, [2](#)

getSeqOccupancy, [2](#)

getSeqOccupancy, DNAStrng, PFMatrix, numeric-method  
(getSeqOccupancy), [2](#)

getSeqOccupancy, DNAStrng, PFMatrixList, numeric-method  
(getSeqOccupancy), [2](#)

getSeqOccupancy-methods  
(getSeqOccupancy), [2](#)

MatrixRider (MatrixRider-package), [2](#)

MatrixRider-package, [2](#)

PFMatrix, [2](#)

PFMatrixList, [2](#), [3](#)