

Package ‘cogeqc’

May 8, 2026

Title Systematic quality checks on comparative genomics analyses

Version 1.17.0

Date 2022-01-26

Description cogeqc aims to facilitate systematic quality checks on standard comparative genomics analyses to help researchers detect issues and select the most suitable parameters for each data set. cogeqc can be used to asses: i. genome assembly and annotation quality with BUSCOs and comparisons of statistics with publicly available genomes on the NCBI; ii. orthogroup inference using a protein domain-based approach and; iii. synteny detection using synteny network properties. There are also data visualization functions to explore QC summary statistics.

License GPL-3

URL <https://github.com/almeidasilvaf/cogeqc>

BugReports <https://support.bioconductor.org/t/cogeqc>

biocViews Software, GenomeAssembly, ComparativeGenomics, FunctionalGenomics, Phylogenetics, QualityControl, Network

Encoding UTF-8

LazyData false

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

SystemRequirements BUSCO (>= 5.1.3) <<https://busco.ezlab.org/>>

Imports utils, graphics, stats, methods, reshape2, ggplot2, scales, ggtree, patchwork, igraph, rlang, ggbeeswarm, jsonlite, Biostrings

Depends R (>= 4.2.0)

Suggests testthat (>= 3.0.0), sessioninfo, knitr, BiocStyle, rmarkdown, covr

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/cogeqc>

git_branch devel

git_last_commit c553a45

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-08

Author Fabrício Almeida-Silva [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-5314-2964>>),

Yves Van de Peer [aut] (ORCID: <<https://orcid.org/0000-0003-4327-3730>>)

Maintainer Fabrício Almeida-Silva <fabricao_almeidasilva@hotmail.com>

Contents

cogeqc-package	3
assess_orthogroups	3
assess_synnet	4
assess_synnet_list	5
batch_summary	6
busco_is_installed	6
calculate_H	7
compare_genome_stats	8
compare_orthogroups	9
fit_sft	10
get_genome_stats	11
get_og_overlap	12
interpro_ath	13
interpro_bol	14
list_busco_datasets	14
og	15
og_overlap_model	15
plot_busco	16
plot_duplications	16
plot_genes_in_ogs	17
plot_genome_stats	18
plot_og_overlap	19
plot_og_sizes	19
plot_orthofinder_stats	20
plot_species_specific_ogs	21
plot_species_tree	21
read_busco	22
read_orthofinder_stats	23
read_orthogroups	23
run_busco	24
synnet	25
tree	26

Index

27

`cogeqc-package`*cogeqc: Systematic quality checks on comparative genomics analyses*

Description

cogeqc aims to facilitate systematic quality checks on standard comparative genomics analyses to help researchers detect issues and select the most suitable parameters for each data set. cogeqc can be used to assess: i. genome assembly and annotation quality with BUSCOs and comparisons of statistics with publicly available genomes on the NCBI; ii. orthogroup inference using a protein domain-based approach and; iii. synteny detection using synteny network properties. There are also data visualization functions to explore QC summary statistics.

Author(s)

Maintainer: Fabrício Almeida-Silva <fabricio_almeidasilva@hotmail.com> ([ORCID](#))

Authors:

- Yves Van de Peer <yves.vandeppeer@psb.vib-ugent.be> ([ORCID](#))

See Also

Useful links:

- <https://github.com/almeidasilvaf/cogeqc>
- Report bugs at <https://support.bioconductor.org/t/cogeqc>

`assess_orthogroups`*Assess orthogroup inference based on functional annotation*

Description

Assess orthogroup inference based on functional annotation

Usage

```
assess_orthogroups(  
  orthogroups = NULL,  
  annotation = NULL,  
  correct_overclustering = TRUE,  
  verbose = FALSE  
)
```

Arguments

orthogroups	A 3-column data frame with columns Orthogroup , Species , and Gene . This data frame can be created from the 'Orthogroups.tsv' file generated by OrthoFinder with the function <code>read_orthogroups()</code> .
annotation	A list of 2-column data frames with columns Gene (gene ID) and Annotation (annotation ID). The names of list elements must correspond to species names as in the second column of <i>orthogroups</i> . For instance, if there are two species in the <i>orthogroups</i> data frame named "SpeciesA" and "SpeciesB", <i>annotation</i> must be a list of 2 data frames, and each list element must be named "SpeciesA" and "SpeciesB".
correct_overclustering	Logical indicating whether to correct for overclustering in orthogroups. Default: TRUE.
verbose	Logical indicating whether to print progress messages. Default: FALSE.

Value

A data frame.

Examples

```
data(og)
data(interpro_ath)
data(interpro_bol)
# Subsetting annotation for demonstration purposes.
annotation <- list(Ath = interpro_ath[1:1000,], Bol = interpro_bol[1:1000,])
assess <- assess_orthogroups(og, annotation)
```

assess_synnet

Assess synteny network based on graph properties

Description

Assess synteny network based on graph properties

Usage

```
assess_synnet(synnet = NULL, cc_type = "average")
```

Arguments

synnet	Edge list for the synteny network in a 2-column data frame, with columns 1 and 2 representing names of loci in anchor 1 and anchor 2, respectively.
cc_type	Type of clustering coefficient to be calculated. One of 'global' or 'average'. Default: 'average'.

Details

Network score is the product of the network's clustering coefficient, node count, and R squared for the scale-free topology fit.

Value

A data frame with the following variables:

CC Numeric representing clustering coefficient.

Node_count Numeric representing number of nodes in the network.

Rsquared Numeric indicating the coefficient of determination for the scale-free topology fit.

Score Numeric representing network score, which is the product of 'CC' and 'Node_number'.

Examples

```
data(synnet)
assess_synnet(synnet)
```

assess_synnet_list *Assess list of synteny networks as in assess_synnet*

Description

Assess list of synteny networks as in assess_synnet

Usage

```
assess_synnet_list(synnet_list = NULL, cc_type = "average")
```

Arguments

- synnet_list A list of networks, each network being an edge list as a 2-column data frame, with columns 1 and 2 representing names of loci in anchor 1 and anchor 2, respectively.
- cc_type Type of clustering coefficient to be calculated. One of 'global' or 'average'. Default: 'average'.

Value

A data frame with the following variables:

CC Numeric representing clustering coefficient.

Node_count Numeric representing number of nodes in the network.

Rsquared Numeric indicating the coefficient of determination for the scale-free topology fit.

Score Numeric representing network score, which is the product of 'CC' and 'Node_number'.

Network Character of network name.

Examples

```
set.seed(123)
data(synnet)
net1 <- synnet
net2 <- synnet[-sample(1:10000, 500), ]
net3 <- synnet[-sample(1:10000, 1000), ]
synnet_list <- list(net1 = net1, net2 = net2, net3 = net3)
assess_synnet_list(synnet_list)
```

batch_summary	<i>BUSCO summary output for batch mode</i>
---------------	--

Description

This object was created with the function `read_busco()` using a batch run of BUSCO on the genomes of *Herbaspirillum seropedicae* SmR1 and *Herbaspirillum rubrisubalbicans* M1.

Usage

```
data(batch_summary)
```

Format

A 2-column data frame with the following variables:

Class Factor of BUSCO classes

Frequency Numeric with the percentage of BUSCOs in each class.

Lineage Character with the lineage dataset used.

File Character with the name of the FASTA file used.

Examples

```
data(batch_summary)
```

busco_is_installed	<i>Check if BUSCO is installed</i>
--------------------	------------------------------------

Description

Check if BUSCO is installed

Usage

```
busco_is_installed()
```

Value

Logical indicating whether BUSCO is installed or not.

Examples

```
busco_is_installed()
```

`calculate_H`*Calculate homogeneity scores for orthogroups*

Description

Calculate homogeneity scores for orthogroups

Usage

```
calculate_H(  
  orthogroup_df,  
  correct_overclustering = TRUE,  
  max_size = 200,  
  update_score = TRUE  
)
```

Arguments

`orthogroup_df` Data frame with orthogroups and their associated genes and annotation. The columns **Gene**, **Orthogroup**, and **Annotation** are mandatory, and they must represent Gene ID, Orthogroup ID, and Annotation ID (e.g., Interpro/PFAM), respectively.

`correct_overclustering` Logical indicating whether to correct for overclustering in orthogroups. Default: TRUE.

`max_size` Numeric indicating the maximum orthogroup size to consider. If orthogroups are too large, calculating Sorensen-Dice indices for all pairwise combinations could take a long time, so setting a limit prevents that. Default: 200.

`update_score` Logical indicating whether to replace scores with corrected scores or not. If FALSE, the dispersal term and corrected scores are returned as separate variables in the output data frame.

Details

Homogeneity is calculated based on pairwise Sorensen-Dice similarity indices between gene pairs in an orthogroup, and they range from 0 to 1. Thus, if all genes in an orthogroup share the same domain, the orthogroup will have a homogeneity score of 1. On the other hand, if genes in an orthogroup do not have any domain in common, the orthogroup will have a homogeneity score of 0. The percentage of orthogroups with size greater than **max_size** will be subtracted from the homogeneity scores, since too large orthogroups typically have very low scores. Additionally, users can correct for overclustering by penalizing protein domains that appear in multiple orthogroups (default).

Value

A 2-column data frame with the variables **Orthogroup** and **Score**, corresponding to orthogroup ID and orthogroup score, respectively. If **update_score = FALSE**, additional columns named **Dispersal** and **Score_c** are added, which correspond to the dispersal term and corrected scores, respectively.

Examples

```

data(og)
data(interpro_ath)
orthogroup_df <- merge(og[og$Species == "Ath", ], interpro_ath)
# Filter data to reduce run time
orthogroup_df <- orthogroup_df[1:10000, ]
H <- calculate_H(orthogroup_df)

```

compare_genome_stats *Compare user-defined assembly statistics with statistics of NCBI genomes*

Description

This function helps users analyze their genome assembly stats in a context by comparing metrics obtained by users with "reference" metrics in closely-related organisms.

Usage

```
compare_genome_stats(ncbi_stats = NULL, user_stats = NULL)
```

Arguments

ncbi_stats A data frame of summary statistics for a particular taxon obtained from the NCBI, as obtained with the function `get_genome_stats`.

user_stats A data frame with assembly statistics obtained by the user. A column named **accession** is mandatory, and it must contain unique identifiers for the genome(s) analyzed by the user. Dummy variables can be used as identifiers (e.g., "my_genome_001"), as long as they are unique. All other column containing assembly stats must have the same names as their corresponding columns in the data frame specified in **ncbi_stats**. For instance, stats on total number of genes and sequence length must be in columns named "gene_count_total" and "sequence_length", as in the **ncbi_stats** data frame.

Details

For each genome assembly statistic (e.g., "gene_count_total"), values in **user_stats** are compared to a distribution of values from **ncbi_stats**, and their percentile and rank in the distributions are reported.

Value

A data frame with the following variables:

accession character, unique identifier as in `user_stats$accession`.

variable character, name of the genome assembly metric (e.g., "CC_ratio").

percentile numeric, percentile in the distribution.

rank numeric, rank in the distribution (highest to lowest). For the variable "CC_ratio", ranks go from lowest to highest.

Examples

```
# Use case: user assembled a maize (Zea mays) genome

## Obtain stats for maize genomes on the NCBI
ncbi_stats <- get_genome_stats(taxon = "Zea mays")

## Create a data frame of stats for fictional maize genome
user_stats <- data.frame(
  accession = "my_lovely_maize",
  sequence_length = 2.4 * 1e9,
  gene_count_total = 50000,
  CC_ratio = 1
)

# Compare stats
compare_genome_stats(ncbi_stats, user_stats)
```

compare_orthogroups *Compare inferred orthogroups to a reference set*

Description

Compare inferred orthogroups to a reference set

Usage

```
compare_orthogroups(ref_orthogroups = NULL, test_orthogroups = NULL)
```

Arguments

ref_orthogroups

Reference orthogroups in a 3-column data frame with columns **Orthogroup**, **Species**, and **Gene**. This data frame can be created from the 'Orthogroups.tsv' file generated by OrthoFinder with the function read_orthogroups().

test_orthogroups

Test orthogroups that will be compared to *ref_orthogroups* in the same 3-column data frame format.

Details

This function compares a test set of orthogroups to a reference set and returns which orthogroups in the reference set are fully preserved in the test set (i.e., identical gene repertoire) and which are not. Species names (column 2) must be the same between reference and test set. If some species are not shared between reference and test sets, they will not be considered for the comparison.

Value

A 2-column data frame with the following variables:

Orthogroup Character of orthogroup IDs.

Preserved A logical vector of preservation status. It is TRUE if the orthogroup in the reference set is fully preserved in the test set, and FALSE otherwise.

Examples

```
set.seed(123)
data(og)
og <- og[1:5000, ]
ref <- og
# Shuffle genes to simulate a different set
test <- data.frame(
  Orthogroup = sample(og$Orthogroup, nrow(og), replace = FALSE),
  Species = og$Species,
  Gene = og$Gene
)
comparison <- compare_orthogroups(ref, test)

# Calculating percentage of preservation
sum(comparison$Preserved) / length(comparison$Preserved)
```

`fit_sft`*Goodness of fit test for the scale-free topology model*

Description

Goodness of fit test for the scale-free topology model

Usage

```
fit_sft(edges)
```

Arguments

`edges` A 2-column data frame with network edges represented in each. Columns 1 and 2 represent nodes 1 and 2 of each edge.

Value

A numeric scalar with the R squared for the scale-free topology fit.

Examples

```
data(synnet)
edges <- synnet
fit_sft(edges)
```

get_genome_stats	<i>Get summary statistics for genomes on NCBI using the NCBI Datasets API</i>
------------------	---

Description

Get summary statistics for genomes on NCBI using the NCBI Datasets API

Usage

```
get_genome_stats(taxon = NULL, filters = NULL)
```

Arguments

taxon	Taxon for which summary statistics will be retrieved, either as a character scalar (e.g., "brassicaceae") or as a numeric scalar representing NCBI Taxonomy ID (e.g., 3700).
filters	(optional) A list of filters to use when querying the API in the form of key-value pairs, with keys in list names and values in list elements (e.g., <code>list(filters.reference_only = "true")</code>), see examples for details).

Details

Possible filters for the **filters** parameter can be accessed at https://www.ncbi.nlm.nih.gov/datasets/docs/v2/reference-docs/rest-api/#get-/genome/taxon/-taxons-/dataset_report.

Value

A data frame with the following variables:

- accession** character, accession number.
- source** character, data source.
- species_taxid** numeric, NCBI Taxonomy ID.
- species_name** character, species' scientific name.
- species_common_name** character, species' common name.
- species_ecotype** character, species' ecotype.
- species_strain** character, species' strain.
- species_isolate** character, species' isolate.
- species_cultivar** character, species' cultivar.
- assembly_level** factor, assembly level ("Complete", "Chromosome", "Scaffold", or "Contig").
- assembly_status** character, assembly status.
- assembly_name** character, assembly name.
- assembly_type** character, assembly type.
- submission_date** character, submission date (YYYY-MM-DD).
- submitter** character, submitter name.
- sequencing_technology** character, sequencing technology.
- atypical** logical, indicator of wheter the genome is atypical.

refseq_category character, RefSeq category.

chromosome_count numeric, number of chromosomes.

sequence_length numeric, total sequence length.

ungapped_length numeric, ungapped sequence length.

contig_count numeric, number of contigs.

contig_N50 numeric, contig N50.

contig_L50 numeric, contig L50.

scaffold_N50 numeric, contig N50.

scaffold_L50 numeric, contig L50.

GC_percent numeric, GC percentage (0-100).

annotation_provider character, name of annotation provider.

annotation_release_date character, annotation release date (YYYY-MM-DD).

gene_count_total numeric, total number of genes.

gene_count_coding numeric, number of protein-coding genes.

gene_count_noncoding numeric, number of non-coding genes.

gene_count_pseudogene numeric, number of pseudogenes.

gene_count_other numeric, number of other genes.

CC_ratio numeric, ratio of the number of contigs to the number of chromosomes.

Examples

```
# Example 1: Search for A. thaliana genomes by tax ID
ex1 <- get_genome_stats(taxon = 3702)

# Example 2: Search for A. thaliana genomes by name
ex2 <- get_genome_stats(taxon = "Arabidopsis thaliana")

# Example 3: Search for chromosome-level Brassicaceae genomes
ex3 <- get_genome_stats(
  taxon = "brassicaceae",
  filters = list(filters.assembly_level = "chromosome")
)
```

get_og_overlap

Get number of shared orthogroups between species pairs

Description

Get number of shared orthogroups between species pairs

Usage

```
get_og_overlap(orthogroups)
```

Arguments

orthogroups A 3-column data frame with columns **Orthogroup**, **Species**, and **Gene**. This data frame can be created from the 'Orthogroups.tsv' file generated by OrthoFinder with the function `read_orthogroups()`.

Value

A data frame with the following variables:

sp1 Character, name of species 1.

sp2 Character, name of species 2.

og_overlap Numeric, number of shared orthogroups.

Examples

```
path <- system.file("extdata", "Orthogroups.tsv.gz", package = "cogeqc")
orthogroups <- read_orthogroups(path)
ov_df <- get_og_overlap(orthogroups)
```

interpro_ath

Intepro annotation for Arabidopsis thaliana's genes

Description

The annotation data were retrieved from PLAZA Dicots 5.0.

Usage

```
data(interpro_ath)
```

Format

A 2-column data frame:

Gene Character of gene IDs.

Annotation Character of Interpro domains.

References

Van Bel, M., Silvestri, F., Weitz, E. M., Kreft, L., Botzki, A., Coppens, F., & Vandepoele, K. (2021). PLAZA 5.0: extending the scope and power of comparative and functional genomics in plants. *Nucleic acids research*.

Examples

```
data(interpro_ath)
```

interpro_bol	<i>Intepro annotation for Brassica oleraceae's genes</i>
--------------	--

Description

The annotation data were retrieved from PLAZA Dicots 5.0.

Usage

```
data(interpro_bol)
```

Format

A 2-column data frame:

Gene Character of gene IDs.

Annotation Character of Interpro domains.

References

Van Bel, M., Silvestri, F., Weitz, E. M., Kreft, L., Botzki, A., Coppens, F., & Vandepoele, K. (2021). PLAZA 5.0: extending the scope and power of comparative and functional genomics in plants. *Nucleic acids research*.

Examples

```
data(interpro_bol)
```

list_busco_datasets	<i>List BUSCO data sets</i>
---------------------	-----------------------------

Description

List BUSCO data sets

Usage

```
list_busco_datasets()
```

Value

A hierarchically organized list of available data sets as returned by `busco --list-datasets`.

Examples

```
if(busco_is_installed()) {  
  list_busco_datasets()  
}
```

og

Orthogroups between Arabidopsis thaliana and Brassica oleraceae

Description

Data obtained from PLAZA Dicots 5.0.

Usage

data(og)

Format

A 3-column data frame with the following variables:

Orthogroup Orthogroup ID.

Species Abbreviation for species' name.

Gene Gene ID

References

Van Bel, M., Silvestri, F., Weitz, E. M., Kreft, L., Botzki, A., Coppens, F., & Vandepoele, K. (2021). PLAZA 5.0: extending the scope and power of comparative and functional genomics in plants. *Nucleic acids research*.

Examples

data(og)

og_overlap_model

Number of shared orthogroups between model organisms

Description

Orthogroups from a set of model organisms obtained from OrthoFinder2' example output, which was then passed to get_og_overlap() to get shared orthogroups.

Usage

data(og_overlap_model)

Format

A 3-column data frame with the following variables:

sp1 Character, name of species 1.

sp2 Character, name of species 2.

og_overlap Numeric, number of shared orthogroups.

References

Emms, D. M., & Kelly, S. (2019). OrthoFinder: phylogenetic orthology inference for comparative genomics. *Genome biology*, 20(1), 1-14.

Examples

```
data(og_overlap_model)
```

plot_busco	<i>Plot BUSCO summary output</i>
------------	----------------------------------

Description

Plot BUSCO summary output

Usage

```
plot_busco(summary_df = NULL)
```

Arguments

summary_df Data frame with BUSCO summary output as returned by read_busco().

Value

A ggplot object with a barplot of BUSCOs in each class.

Examples

```
# Single file
result_dir <- system.file("extdata", package = "cogeqc")
summary_df <- read_busco(result_dir)
# Batch mode
data(batch_summary)
plot_busco(summary_df)
plot_busco(batch_summary)
```

plot_duplications	<i>Plot species-specific duplications</i>
-------------------	---

Description

Plot species-specific duplications

Usage

```
plot_duplications(stats_list = NULL)
```

Arguments

`stats_list` A list of data frames with Orthofinder summary stats as returned by the function `read_orthofinder_stats`.

Value

A ggplot object with a barplot of number of species-specific duplications.

Examples

```
dir <- system.file("extdata", package = "cogeqc")
stats_list <- read_orthofinder_stats(dir)
plot_duplications(stats_list)
```

`plot_genes_in_ogs` *Plot percentage of genes in orthogroups for each species*

Description

Plot percentage of genes in orthogroups for each species

Usage

```
plot_genes_in_ogs(stats_list = NULL)
```

Arguments

`stats_list` A list of data frames with Orthofinder summary stats as returned by the function `read_orthofinder_stats`.

Value

A ggplot object with a barplot of percentages of genes in orthogroups for each species.

Examples

```
dir <- system.file("extdata", package = "cogeqc")
stats_list <- read_orthofinder_stats(dir)
plot_genes_in_ogs(stats_list)
```

plot_genome_stats *Plot statistics on genome assemblies on the NCBI*

Description

Plot statistics on genome assemblies on the NCBI

Usage

```
plot_genome_stats(ncbi_stats = NULL, user_stats = NULL)
```

Arguments

ncbi_stats A data frame of summary statistics for a particular taxon obtained from the NCBI, as obtained with the function `get_genome_stats`.

user_stats (Optional) A data frame with assembly statistics obtained by the user. Statistics in this data frame are highlighted in red if this data frame is passed. A column named **accession** is mandatory, and it must contain unique identifiers for the genome(s) analyzed by the user. Dummy variables can be used as identifiers (e.g., "my_genome_001"), as long as they are unique. All other column containing assembly stats must have the same names as their corresponding columns in the data frame specified in **ncbi_stats**. For instance, stats on total number of genes and sequence length must be in columns named "gene_count_total" and "sequence_length", as in the **ncbi_stats** data frame.

Value

A composition of ggplot objects made with patchwork.

Examples

```
# Example 1: plot stats on maize genomes on the NCBI
## Obtain stats for maize genomes on the NCBI
ncbi_stats <- get_genome_stats(taxon = "Zea mays")

plot_genome_stats(ncbi_stats)

## Plot stats
# Example 2: highlight user-defined stats in the distribution
## Create a data frame of stats for fictional maize genome
user_stats <- data.frame(
  accession = "my_lovely_maize",
  sequence_length = 2.4 * 1e9,
  gene_count_total = 50000,
  CC_ratio = 1
)

plot_genome_stats(ncbi_stats, user_stats)
```

plot_og_overlap	<i>Plot pairwise orthogroup overlap between species</i>
-----------------	---

Description

Plot pairwise orthogroup overlap between species

Usage

```
plot_og_overlap(overlap_df, add_numbers = FALSE, abbreviate_names = TRUE)
```

Arguments

overlap_df	A data frame with the number of shared orthogroups between species pairs as returned by <code>get_og_overlap()</code> .
add_numbers	Logical indicating whether to add numbers to each entry of the heatmap. Default: FALSE.
abbreviate_names	Logical indicating whether to abbreviate species names. Default: TRUE.

Value

A ggplot object with a heatmap displaying the number of shared orthogroups between species pairs.

Examples

```
data(og_overlap_model)
plot_og_overlap(og_overlap_model, add_numbers = TRUE)
```

plot_og_sizes	<i>Plot orthogroup sizes per species</i>
---------------	--

Description

Plot orthogroup sizes per species

Usage

```
plot_og_sizes(orthogroups = NULL, log = FALSE, max_size = NULL)
```

Arguments

orthogroups	A 3-column data frame with columns Orthogroup , Species , and Gene . This data frame can be created from the 'Orthogroups.tsv' file generated by OrthoFinder with the function <code>read_orthogroups()</code> .
log	Logical indicating whether to transform orthogroups sizes with natural logarithms. Default: FALSE.
max_size	Numeric indicating the maximum orthogroup size to consider. If this parameter is not NULL, orthogroups larger than <code>max_size</code> (e.g., 100) will not be considered. Default: NULL.

Value

A ggplot object with a violin plot.

Examples

```
data(og)
plot_og_sizes(og, log = TRUE)
plot_og_sizes(og, max_size = 100)
plot_og_sizes(og, log = TRUE, max_size = 100)
```

plot_orthofinder_stats

Plot a panel with a summary of Orthofinder stats

Description

This function is a wrapper for plot_species_tree, plot_duplications, plot_genes_in_ogs, plot_species_specific_ogs.

Usage

```
plot_orthofinder_stats(tree = NULL, stats_list = NULL, xlim = c(0, 1))
```

Arguments

tree	Tree object as returned by treeio::read.*, a family of functions in the treeio package to import tree files in multiple formats, such as Newick, Phylip, NEXUS, and others. If your species tree was inferred with Orthofinder (using STAG), the tree file is located in <i>Species_Tree/SpeciesTree_rooted_node_labels.txt</i> . Then, it can be imported with treeio::read_tree(path_to_file).
stats_list	(optional) A list of data frames with Orthofinder summary stats as returned by the function read_orthofinder_stats. If this list is given as input, nodes will be labeled with the number of duplications.
xlim	Numeric vector of x-axis limits. This is useful if your node tip labels are not visible due to margin issues. Default: c(0, 1).

Value

A panel of ggplot objects.

Examples

```
data(tree)
dir <- system.file("extdata", package = "cogeqc")
stats_list <- read_orthofinder_stats(dir)
plot_orthofinder_stats(tree, xlim = c(0, 1.5), stats_list = stats_list)
```

plot_species_specific_ogs
Plot number of species-specific orthogroups

Description

Plot number of species-specific orthogroups

Usage

```
plot_species_specific_ogs(stats_list = NULL)
```

Arguments

`stats_list` A list of data frames with Orthofinder summary stats as returned by the function `read_orthofinder_stats`.

Value

A ggplot object with a barplot of number of species-specific orthogroups for each species.

Examples

```
dir <- system.file("extdata", package = "cogeqc")
stats_list <- read_orthofinder_stats(dir)
plot_species_specific_ogs(stats_list)
```

plot_species_tree *Plot species tree*

Description

Plot species tree

Usage

```
plot_species_tree(tree = NULL, xlim = c(0, 1), stats_list = NULL)
```

Arguments

`tree` Tree object as returned by `treeio::read.*`, a family of functions in the **treeio** package to import tree files in multiple formats, such as Newick, Phylip, NEXUS, and others. If your species tree was inferred with Orthofinder (using STAG), the tree file is located in *Species_Tree/SpeciesTree_rooted_node_labels.txt*. Then, it can be imported with `treeio::read_tree(path_to_file)`.

`xlim` Numeric vector of x-axis limits. This is useful if your node tip labels are not visible due to margin issues. Default: `c(0, 1)`.

`stats_list` (optional) A list of data frames with Orthofinder summary stats as returned by the function `read_orthofinder_stats`. If this list is given as input, nodes will be labeled with the number of duplications.

Value

A ggtree/ggplot object with the species tree.

Examples

```
data(tree)
plot_species_tree(tree)
```

read_busco

Read and parse BUSCO's summary report

Description

Read and parse BUSCO's summary report

Usage

```
read_busco(result_dir = NULL)
```

Arguments

result_dir Path to the directory where BUSCO results are stored. This function will look for the short_summary* file (single run) or short_summary* file (batch mode).

Value

A data frame with the following variables:

Class BUSCO class. One of **Complete_SC**, **Complete_duplicate**, **Fragmented**, or **Missing**

Frequency Frequency of BUSCOs in each class. If BUSCO was run in batch mode, this variable will contain relative frequencies. If BUSCO was run for a single file, it will contain absolute frequencies.

Lineage Name of the lineage dataset used.

File (batch mode only) Name of the input FASTA file.

Examples

```
result_dir <- system.file("extdata", package = "cogeqc")
df <- read_busco(result_dir)
```

 read_orthofinder_stats

Read and parse Orthofinder summary statistics

Description

Read and parse Orthofinder summary statistics

Usage

```
read_orthofinder_stats(stats_dir = NULL)
```

Arguments

stats_dir Path to directory containing Orthofinder's comparative genomics statistics. In your Orthofinder results directory, this directory is named **Comparative_Genomics_Statistics**.

Value

A list of data frames with the following elements:

1. **stats** A data frame of summary stats per species with the following variables:
 - Species** Factor of species names.
 - N_genes** Numeric of number of genes.
 - N_genes_in_OGs** Numeric of number of genes in orthogroups.
 - Perc_genes_in_OGs** Numeric of percentage of genes in orthogroups.
 - N_ssOGs** Numeric of number of species-specific orthogroups.
 - N_genes_in_ssOGs** Numeric of number of genes in species-specific orthogroups.
 - Perc_genes_in_ssOGs** Numeric of percentage of genes in species-specific orthogroups.
 - Dups** Integer with number of duplications per species.
2. **duplications** A 2-column data frame with node IDs in the first column and number of gene duplications (50% support) in the second column.

Examples

```
stats_dir <- system.file("extdata", package = "cogeqc")
ortho_stats <- read_orthofinder_stats(stats_dir)
```

 read_orthogroups

Read and parse orthogroups file created by OrthoFinder

Description

This function converts the orthogroups file named **Orthogroups.tsv** to a parsed data frame.

Usage

```
read_orthogroups(orthogroups_path = NULL)
```

Arguments

orthogroups_path
Path to Orthogroups/Orthogroups.tsv file generated by OrthoFinder.

Value

A 3-column data frame with orthogroups, species IDs and gene IDs, respectively.

Author(s)

Fabricio Almeida-Silva

Examples

```
path <- system.file("extdata", "Orthogroups.tsv.gz", package = "cogeqc")
og <- read_orthogroups(path)
```

run_busco

Run BUSCO assessment of assembly and annotation quality

Description

Run BUSCO assessment of assembly and annotation quality

Usage

```
run_busco(
  sequence = NULL,
  outlabel = NULL,
  mode = c("genome", "transcriptome", "proteins"),
  lineage = NULL,
  auto_lineage = NULL,
  force = FALSE,
  threads = 1,
  output_path = NULL,
  download_path = tempdir()
)
```

Arguments

sequence	An object of class DNASTringSet/AAStringSet/RNAStringSet or path to FASTA file with the genome, transcriptome, or protein sequences to be analyzed. If there are many FASTA files in a directory, you can input the path to this directory, so BUSCO will be run in all FASTA files inside it.
outlabel	Character with a recognizable short label for analysis directory and files.
mode	Character with BUSCO mode. One of 'genome', 'transcriptome', or 'proteins'.
lineage	Character with name of lineage to be used.

auto_lineage	Character indicating whether BUSCO should determine optimum lineage path automatically. One of 'euk', 'prok', 'all', or NULL. If 'euk', it will determine optimum lineage path on eukaryote tree. If 'prok', it will determine optimum lineage path on non-eukaryote trees. If 'all', it will determine optimum lineage path for all trees. If NULL, it will not automatically determine lineage, and <i>lineage</i> must be manually specified. Default: NULL.
force	Logical indicating whether existing runs with the same file names should be overwritten. Default: FALSE.
threads	Numeric with the number of threads/cores to use. Default: 1.
outpath	Path to results directory. If NULL, results will be stored in the current working directory. Default: NULL.
download_path	Path to directory where BUSCO datasets will be stored after downloading. Default: tempdir().

Value

A character vector with the names of subdirectories and files in the results directory.

Examples

```
sequence <- system.file("extdata", "Hse_subset.fa", package = "cogeqc")
download_path <- paste0(tempdir(), "/datasets")
if(busco_is_installed()) {
  run_busco(sequence, outlabel = "Hse", mode = "genome",
            lineage = "burkholderiales_odb10",
            outpath = tempdir(), download_path = download_path)
}
```

synnet

Synteny network for Brassica oleraceae, B. napus, and B. rapa

Description

Synteny network for Brassica oleraceae, B. napus, and B. rapa

Usage

```
data(synnet)
```

Format

A 2-column data frame with the variables **anchor1** and **anchor2**, containing names of loci in anchor 1 and anchor 2, respectively.

References

Zhao, T., & Schranz, M. E. (2019). Network-based microsynteny analysis identifies major differences and genomic outliers in mammalian and angiosperm genomes. *Proceedings of the National Academy of Sciences*, 116(6), 2165-2174.

Examples

```
data(synnet)
```

```
tree
```

```
Species tree for model species
```

Description

The data used to create this object was retrieved from Orthofinder's example output for model species, available in https://bioinformatics.plants.ox.ac.uk/davidemms/public_data/.

Usage

```
data(tree)
```

Format

An object of class "phylo" as returned by `treeio::read.tree()`.

References

Emms, D. M., & Kelly, S. (2019). OrthoFinder: phylogenetic orthology inference for comparative genomics. *Genome biology*, 20(1), 1-14.

Examples

```
data(tree)
```

Index

* datasets

- batch_summary, 6
- interpro_ath, 13
- interpro_bol, 14
- og, 15
- og_overlap_model, 15
- synnet, 25
- tree, 26

* internal

- cogeqc-package, 3

- assess_orthogroups, 3
- assess_synnet, 4
- assess_synnet_list, 5

- batch_summary, 6
- busco_is_installed, 6

- calculate_H, 7
- cogeqc (cogeqc-package), 3
- cogeqc-package, 3
- compare_genome_stats, 8
- compare_orthogroups, 9

- fit_sft, 10

- get_genome_stats, 11
- get_og_overlap, 12

- interpro_ath, 13
- interpro_bol, 14

- list_busco_datasets, 14

- og, 15
- og_overlap_model, 15

- plot_busco, 16
- plot_duplications, 16
- plot_genes_in_ogs, 17
- plot_genome_stats, 18
- plot_og_overlap, 19
- plot_og_sizes, 19
- plot_orthofinder_stats, 20
- plot_species_specific_ogs, 21

- plot_species_tree, 21

- read_busco, 22
- read_orthofinder_stats, 23
- read_orthogroups, 23
- run_busco, 24

- synnet, 25

- tree, 26