

Package ‘eds’

May 8, 2026

Title eds: Low-level reader for Alevin EDS format

Version 1.15.0

Description This packages provides a single function, readEDS.

This is a low-level utility for reading in Alevin EDS format into R.

This function is not designed for end-users but instead the package is predominantly for simplifying package dependency graph for other Bioconductor packages.

Depends Matrix

Imports Rcpp

Suggests knitr, tximportData, testthat (>= 3.0.0)

LinkingTo Rcpp

SystemRequirements C++11

License GPL-2

Encoding UTF-8

URL <https://github.com/mikelove/eds>

biocViews Sequencing, RNASeq, GeneExpression, SingleCell

VignetteBuilder knitr

LazyData true

RoxygenNote 7.1.2

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/eds>

git_branch devel

git_last_commit 5731621

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-08

Author Avi Srivastava [aut, cre],
Michael Love [aut, ctb]

Maintainer Avi Srivastava <asrivastava@cs.stonybrook.edu>

Contents

readEDS	2
-------------------	---

Index**3**

readEDS	<i>A low-level utility function for quickly reading in Alevin EDS format</i>
---------	--

Description

This provides a simple utility for reading in EDS format. Note that most users will prefer to use `tximport` or `tximeta`. This function and package exist in order to simplify the dependency graph for other packages.

Usage

```
readEDS(numOfGenes, numOfOriginalCells, countMatFilename, tierImport = FALSE)
```

Arguments

<code>numOfGenes</code>	number of genes
<code>numOfOriginalCells</code>	number of cells
<code>countMatFilename</code>	pointer to the EDS file, <code>quants_mat.gz</code>
<code>tierImport</code>	whether the <code>countMatFilename</code> refers to a quants tier file

Value

a genes x cells sparse matrix, of the class `dgMatrix`

Examples

```
# point to files
dir0 <- system.file("extdata", package="tximportData")
samps <- list.files(file.path(dir0, "alevin"))
dir <- file.path(dir0, "alevin", samps[3], "alevin")
quant.mat.file <- file.path(dir, "quants_mat.gz")
barcode.file <- file.path(dir, "quants_mat_rows.txt")
gene.file <- file.path(dir, "quants_mat_cols.txt")

# readEDS() requires knowing the number of cells and genes
cell.names <- readLines(barcode.file)
gene.names <- readLines(gene.file)
num.cells <- length(cell.names)
num.genes <- length(gene.names)

# reading in the sparse matrix
mat <- readEDS(numOfGenes=num.genes,
              numOfOriginalCells=num.cells,
              countMatFilename=quant.mat.file)
```

Index

readEDS, [2](#)