

Package ‘omXplore’

May 9, 2026

Type Package

Title Vizualization tools for 'omics' datasets with R

Version 1.7.0

Description This package contains a collection of functions (written as shiny modules) for the visualisation and the statistical analysis of omics data. These plots can be displayed individually or embedded in a global Shiny module.

Additionally, it is possible to integrate third party modules to the main interface of the package omXplore.

License Artistic-2.0

Depends R (>= 4.5.0), methods

Imports DT, shiny, MSnbase, PSMATCH, SummarizedExperiment, MultiAssayExperiment, shinyBS, shinyjs, shinyjqui, RColorBrewer, gplots, plotly, visNetwork, tibble, grDevices, stats, utils, htmlwidgets, vioplot, graphics, FactoMineR, dendextend, dplyr, factoextra, tidyr, nipals, Biobase

Suggests knitr, rmarkdown, BiocStyle, testthat, Matrix, graph

biocViews Software, ShinyApps, MassSpectrometry, DataRepresentation, GUI, QualityControl

NeedsCompilation no

Collate 'mod_explore_graphs.R' 'Infos_adjacencyMatrix.R' 'Prostar_1x.R' 'convert_to_mae.R' 'doc-data.R' 'external_apps_examples.R' 'get_pep_prot_CC.R' 'mae_accessors.R' 'metacell_utils.R' 'mod_colorLegend.R' 'modules.R' 'omXplore_cc.R' 'omXplore_corrmatrix.R' 'omXplore_density.R' 'omXplore_format_DT.R' 'omXplore_heatmap.R' 'omXplore_intensity.R' 'omXplore_PCA_nipals.R' 'omXplore_pca.R' 'omXplore_plots_tracking.R' 'omXplore_tabExplorer.R' 'omXplore_variance.R' 'omXplore_view_dataset.R' 'palette.R' 'plot_boxplot.R' 'plot_heatmap.R' 'plot_pca.R' 'plot_violin.R' 'utils.R' 'zzz.R'

RoxygenNote 7.3.3

Encoding UTF-8

LazyData false

URL <https://github.com/edyp-lab/omXplore>,
<https://edyp-lab.github.io/omXplore/>

BugReports <https://github.com/edyp-lab/omXplore/issues>

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/omXplore>

git_branch devel

git_last_commit 2b3acd9

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-08

Author Samuel Wiczorek [aut, cre] (ORCID:
<https://orcid.org/0000-0002-5016-1203>),
 Thomas Burger [aut],
 Enora Fremy [ctb],
 Cyril Ariztegui [ctb],
 Manon Gaudin [ctb]

Maintainer Samuel Wiczorek <samuel.wiczorek@cea.fr>

Contents

accessors	3
BuildColorStyles	5
Build_enriched_qdata	5
color-legend	6
converters	7
corrmatrix	9
density-plot	10
ds-cc	11
ds-pca	12
ds-view	14
external_app	16
FormatDataForDT	17
format_DT	18
GetPkgVersion	19
globals	20
intensity-plots	20
is.listOf	22
omXplore-modules	22
omXplore_heatmap	23
omXplore_tabExplorer	25
palette	26
pep_prot_CC	27
pkgs.require2	29
plot-variance	29
plots_tracking	30
Prostar-1x-compatible	31
q_metadata	32

accessors	3
sub_R25	33
vdata	34

Index **35**

accessors	<i>Accessors functions</i>
-----------	----------------------------

Description

Functions used to access the additional plots in the instances of the class MultiAssayExperiment.

Usage

```

get_adjacencyMatrix(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_adjacencyMatrix(object)

get_design(object, ...)

## S4 method for signature 'MultiAssayExperiment'
get_design(object)

get_group(object, ...)

## S4 method for signature 'MultiAssayExperiment'
get_group(object)

get_metacell(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_metacell(object, slot.name = c("metacell", "qMetacell"))

get_cc(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_cc(object)

get_parentProtId(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_parentProtId(object)

get_colID(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_colID(object)

get_type(object, ...)

## S4 method for signature 'SummarizedExperiment'

```

```

get_type(object)

get_pkg_version(object, ...)

## S4 method for signature 'SummarizedExperiment'
get_pkg_version(object)

```

Arguments

object	An instance of class SummarizedExperiment.
...	Additional parameters
slot.name	The name of the slot dedicated to cell metadata to search. Default values are 'metacell' and 'qMetacell'

Value

See individual method description for the return value.

If exists, the slot value requested.

A DataFrame containing the adjacency matrix of the dataset

A data.frame containing the metadata of the dataset

A data.frame containing the metadata of the dataset

A data.frame containing the metadata of the dataset

A data.frame containing the metadata of the dataset

A data.frame containing the metadata of the dataset

A data.frame containing the metadata of the dataset

A data.frame containing the metadata of the dataset

A data.frame containing the metadata of the dataset

Examples

```

## -----
## Accessing slots from a MSnSet dataset
## -----
data(sub_R25)
se1 <- sub_R25[[1]]
parentProtId <- get_parentProtId(se1)
colID <- get_colID(se1)
type <- get_type(se1)
metacell <- get_metacell(se1)
conds <- get_group(sub_R25)

```

BuildColorStyles *Build color style for DT tables*

Description

This function builds a list which is used for styling DT tables with the function `DT::styleEqual()`

Usage

```
BuildColorStyles(type)
```

Arguments

type The type of dataset. Available values are protein and peptide

Value

A list

Examples

```
NULL
```

Build_enriched_qdata *Builds enriched assay with cell metadata info*

Description

If the cell metadata exists in the object of class `SummarizedExperiment`, then these information are added to the quantitative data so as to use styles with the functions of the package DT.

Usage

```
Build_enriched_qdata(obj)
```

Arguments

obj An instance of the class `SummarizedExperiment`

Value

A data.frame with new columns corresponding to the cell metadata (if exists)

Examples

```
NULL
```

`color-legend`*Color legend for DaparToolshed*

Description

Shows a legend based on the tags in the package 'DaparToolshed'

Usage

```
custom_metacell_colors()

colorLegend_ui(id)

colorLegend_server(
  id,
  presentTags = reactive({
    NULL
  }),
  hide.white = TRUE
)

colorLegend(dataIn = SummarizedExperiment::SummarizedExperiment())
```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>presentTags</code>	A vector of character() which correspond to the tags.
<code>hide.white</code>	A boolean() to indicate whether the white cells must be hidden or not.
<code>dataIn</code>	An instance of the class SummarizedExperiment.

Value

A vector
NA
NA
A shiny app

Examples

```
if (interactive()) {
  data(vdata)
  shiny::runApp(colorLegend(vdata[[1]]))
}
```

`converters`*Convert to enriched MultiAssayExperiment*

Description

The resulting object is an instance of the `MultiAssayExperiment` class.

Usage

```
convert_to_mae(obj)
MSnSet_to_mae(obj)
matrix_to_mae(obj)
df_to_mae(obj)
Compute_CC(obj)
QFeatures_to_mae(obj)
SE_to_mae(obj)
MAE_to_mae(obj)
Check_se_Consistency(obj)
list_to_se(l1)
Check_List_consistency(l1)
listOfLists_to_mae(obj, colData = NULL)
listOfSE_to_mae(obj)
Check_MSnSet_Consistency(obj)
matrix_to_se(obj)
df_to_se(obj)
MSnSet_to_se(obj)
Build_X_CC(se)
listOfMSnSet_to_mae(obj)
listOfmatrix_to_mae(obj)
listOfdf_to_mae(obj)
```

Arguments

obj	An object compliant with the formats accepted by omXplore
ll	A list
colData	A data.frame()
se	AN instance of the class SummarizedExperiment

Value

An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 An instance of SimpleList
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 A boolean(1)
 An enriched instance of the class SummarizedExperiment
 A boolean(1)
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 A boolean(1)
 An enriched instance of the class SummarizedExperiment
 An enriched instance of the class SummarizedExperiment
 An enriched instance of the class SummarizedExperiment
 An enriched instance of the class SummarizedExperiment
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment
 An enriched instance of the class MultiAssayExperiment

Examples

```

#-----
# Conversion of a MultiAssayExperiment instance
#-----
data(miniACC, package = "MultiAssayExperiment")
convert_to_mae(miniACC)

```

corrmatrix	<i>Displays a correlation matrix of the quantitative data of a numeric matrix.</i>
------------	--

Description

Displays a correlation matrix of the quantitative data of a numeric matrix.

Usage

```
omXplore_corrmatrix_ui(id)

omXplore_corrmatrix_server(
  id,
  dataIn = reactive({
    NULL
  }),
  i = reactive({
    1
  })
)

corrMatrix(data, rate = 0.5, showValues = FALSE)

omXplore_corrmatrix(dataIn, i)
```

Arguments

id	A character(1) which is the id of the shiny module.
dataIn	An instance of the class SummarizedExperiment
i	An integer which is the index of the assay in the param dataIn
data	An object of class 'matrix'
rate	The rate parameter to control the exponential law for the gradient of colors
showValues	A boolean which indicates whether to show values in the correlation plot.

Value

NA
 NA
 A plot
 A shiny app

Examples

```
if (interactive()) {
  data(vdata)
  omXplore_corrmatrix(vdata, 1)
}
```

density-plot	<i>Displays a correlation matrix of the quantitative data of a numeric matrix.</i>
--------------	--

Description

Displays a correlation matrix of the quantitative data of a numeric matrix.

Usage

```
omXplore_density_ui(id)

omXplore_density_server(
  id,
  dataIn = reactive({
    NULL
  }),
  i = reactive({
    1
  }),
  pal.name = reactive({
    NULL
  })
)

densityPlot(data, conds = NULL, pal.name = NULL)

omXplore_density(dataIn, i)
```

Arguments

id	A character(1) which is the id of the shiny module.
dataIn	An instance of the class SummarizedExperiment
i	An integer which is the index of the assay in the param obj
pal.name	A character(1) which is the name of the palette from the package RColorBrewer::RColorBrewer from which the colors are taken. Default value is 'Set1'.
data	A data.frame() of quantitative data
conds	A vector indicating the name of each sample.

Value

NA
 NA
 A plot
 A shiny app

Examples

```

if (interactive()) {
  data(vdata)
  shiny::runApp(omXplore_density(vdata, 1))
}

if (interactive()) {
  data(vdata)
  qdata <- SummarizedExperiment::assay(vdata[[1]])
  conds <- get_group(vdata)
  densityPlot(qdata, conds)
}

```

ds-cc

*plots_cc_ui and plots_cc_server***Description**

A shiny Module.

Usage

```

omXplore_cc_ui(id)

omXplore_cc_server(
  id,
  dataIn = reactive({
    NULL
  }),
  i = reactive({
    NULL
  })
)

omXplore_cc(dataIn, i)

```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>dataIn</code>	An instance of SummarizedExperiment class
<code>i</code>	An integer which is the index of the assay in the param obj

Value

A shiny module
A shiny plot
A shiny module
A shiny app
A shiny app

Examples

```
if (interactive()) {
  data(vdata)
  shiny::runApp(omXplore_cc(vdata, 1))
}
```

ds-pca

my_PCA

Description

Process a PCA, using `nipals` or `FactoMineR`, on a quantitative dataset.

This method plots a bar plot which represents the distribution of the number of missing values (NA) per lines (ie proteins).

- `wrapper_pca()`
- `plotPCA_Eigen_hc()`: plots the eigen values of PCA with the `plotly` library
- `plotPCA_Eigen()`: plots the eigen values of PCA
- `plotPCA_Var()`
- `plotPCA_Ind()`

Usage

```
my_PCA(
  X,
  scale.unit = TRUE,
  ncp = min(12, nrow(X) - 1, ncol(X)),
  ind.sup = NULL,
  quanti.sup = NULL,
  quali.sup = NULL,
  row.w = NULL,
  col.w = NULL,
  graph = FALSE,
  axes = c(1, 2),
  approach = "FM",
  gramschmidt = TRUE
)
```

```
omXplore_pca_ui(id)
```

```
omXplore_pca_server(id, dataIn, i)
```

```
omXplore_pca(dataIn, i)
```

```
wrapper_pca(
  qdata,
  group,
  var.scaling = TRUE,
  ncp = NULL,
```

```

    approach = "FM",
    gramschmidt = TRUE
  )

plotPCA_Eigen(res.pca)

plotPCA_Var(res.pca, chosen.axes = c(1, 2))

plotPCA_Ind(res.pca, chosen.axes = c(1, 2))

plotPCA_Eigen_hc(res.pca)

```

Arguments

X	a data.frame() of quantitative data
scale.unit	See FactoMineR::PCA()
ncp	See FactoMineR::PCA()
ind.sup	See FactoMineR::PCA()
quanti.sup	See FactoMineR::PCA()
quali.sup	See FactoMineR::PCA()
row.w	See FactoMineR::PCA()
col.w	See FactoMineR::PCA()
graph	See FactoMineR::PCA()
axes	See FactoMineR::PCA()
approach	a string corresponding to the package to use for PCA (if no NA, default is "FM" for FactoMineR)
gramschmidt	A boolean indicating whether to use Gram-Schmidt orthogonalization or not.
id	A character(1) which is the id of the shiny module.
dataIn	An instance of the class MultiAssayExperiment.
i	An integer which is the index of the assay in the param obj
qdata	A data.frame() of quantitative data
group	A vector with the name of samples
var.scaling	A boolean indicating whether to scale the data or not
res.pca	The result of the function FactoMineR::PCA()
chosen.axes	See the parameter 'axes' of the function factoextra::fviz_pca_var()

Value

res.pca a "PCA" "list" object

NA

NA

A shiny app

The result of the function FactoMineR::PCA()

A plot

A plot

A plot

A plot

Author(s)

Samuel Wiczorek, Enora Fremy

Examples

```

if (interactive()) {
  data(vdata)
  obj <- vdata[[1]]
  res.pca <- my_PCA(SummarizedExperiment::assay(obj), approach = "FM")
  plotPCA_Eigen(res.pca)
  plotPCA_Var(res.pca)
  plotPCA_Eigen_hc(res.pca)
  plotPCA_Ind(res.pca)
}

if (interactive()) {
  data(vdata)
  library(shiny)
  library(dplyr)
  library(plotly)
  # Replace missing values for the example
  sel <- is.na(SummarizedExperiment::assay(vdata, 1))
  SummarizedExperiment::assay(vdata[[1]])[sel] <- 0
  SummarizedExperiment::assay(vdata[[1]])[1, 1] <- NA
  omXplore_pca(vdata, 1)
}

if (interactive()) {
  data(vdata)
  obj <- vdata[[1]]
  res.pca <- wrapper_pca(qdata = SummarizedExperiment::assay(obj), group = get_group(obj))
  plotPCA_Eigen(res.pca)
  plotPCA_Var(res.pca)
  plotPCA_Eigen_hc(res.pca)
  plotPCA_Ind(res.pca)
}

```

ds-view

Bar plot of missing values per lines using plotly.

Description

This method plots a bar plot which represents the distribution of the number of missing values (NA) per lines (i.e. proteins).

Usage

```

view_dataset_ui(id)

view_dataset_server(
  id,
  dataIn = reactive({

```

```

      NULL
    }),
    addons = list(),
    verbose = FALSE
  )

view_dataset(dataIn = NULL, addons = NULL)

```

Arguments

id	A character(1) for the 'id' of the shiny module. It must be the same as for the '*_ui' function.
dataIn	An instance of the class MultiAssayExperiment.
addons	A list to configure the other shiny apps to integrate. Each item correspond to one package: <ul style="list-style-type: none"> • the name of the slot is the name of the package • the content of the slot is a vector composed of the generic name of the shiny app. Each of the apps listed here must be an exported app of the package. For example, given the value <code>addons = list(testPkg = c('foo', 'foo2'))</code>. That means that the package called "testPkg" must provide the four functions: <code>foo1_ui()</code>, <code>foo1_server()</code> and <code>foo2_ui()</code>, <code>foo2_server()</code>
verbose	A boolean for verbose mode. Default is FALSE.

Details

- distribution of the missing values per line,
- a bar plot which represents the distribution of the number of missing values (NA) per lines (i.e. proteins) and per conditions,
- Histogram of missing values.
- Variance : Builds a densityplot of the CV of entities in numeric matrix. The CV is calculated for each condition present in the dataset (see the slot 'Condition' in the `colData()` DataFrame)
- Heatmap:

The function [heatmapD\(\)](#)

The function `[]` is inspired from the function 'heatmap.2' that displays a numeric matrix. For more information, please refer to the help of the heatmap.2 function.

Value

NA

NA

NA

A shiny application which wraps the functions `view_dataset_ui()` and the `view_dataset_server()`

Missing values

#' - distribution of the missing values per line,

- a bar plot which represents the distribution of the number of missing values (NA) per lines (ie proteins) and per conditions,
- Histogram of missing values.

Author(s)

Samuel Wieczorek, Enora Fremy

Examples

```

if (interactive()) {
  library(shiny)
  library(omXplore)
  data(vdata)
  addons <- list(omXplore = c("extFoo1", "extFoo2"))
  runApp(omXplore::view_dataset(vdata, addons))

  omXplore::view_dataset(vdata)
}

if (interactive()) {
  data(vdata)
  view_dataset(vdata)
}

```

external_app

External module example

Description

Example for an external shiny module, well structured to be run within a workflow for MagellanNTK

Usage

```

extFoo1_ui(id)

extFoo1_server(
  id,
  dataIn = reactive({
    NULL
  }),
  i = reactive({
    NULL
  })
)

extFoo1(dataIn, i)

extFoo2_ui(id)

extFoo2_server(
  id,
  dataIn = reactive({
    NULL
  }),
  i = reactive({

```

```

        NULL
      })
    )

    extFoo2(dataIn, i)

```

Arguments

`id` A character(1) which is the id of the shiny module.

`dataIn` An object of instance `MultiAssayExperiment`

`i` An integer which is the index of the assay in the param obj

Value

NA

NA

NA

A shiny app

NA

NA

A shiny app

Examples

```

if (interactive()) {
  data(vdata)
  app1 <- extFoo1(vdata, 1)
  app2 <- extFoo2(vdata, 1)
  shiny::runApp(app1)
  shiny::runApp(app2)
}

```

FormatDataForDT

Constructs a dataset suitable to use with the module format_DT.

Description

This function builds the skeleton of a dataset which can be used by the module `formatDT`. It creates additional columns to be used to style the table. to colors cells.

Usage

```
FormatDataForDT(se, digits = 2)
```

Arguments

`se` An instance of the class `SummarizedExperiment`

`digits` An 'integer(1)' to specify the number of digits to display in the tables for numerical values. Default is 2.

Value

A data.frame

Examples

NULL

format_DT

formatDT_ui and formatDT_server

Description

A shiny Module.

See DT package homepage for more details about styling tables. If no style is precised, this module show the raw data. If any style is given, then the dataset must be well configured (I.e. it must contain the correct columns)

Usage

```
formatDT_ui(id)

formatDT_server(
  id,
  data = reactive({
    NULL
  }),
  data_nostyle = reactive({
    NULL
  }),
  withDLBtns = FALSE,
  showRownames = FALSE,
  dt_style = reactive({
    NULL
  }),
  filename = "Prostar_export",
  selection = "single"
)

formatDT(data)
```

Arguments

id	shiny id
data	A data.frame
data_nostyle	A data.frame() to be bind to the main data with no custom style
withDLBtns	A boolean to indicate whether to display download buttons or not.
showRownames	A boolean to indicate whether to show rownames.
dt_style	A list composed of:

- data : a data.frame
 - colors : a named vector
- filename A character(1) which is the default filename for download.
- selection A character(1) which indicates the type of selection. Default is 'single'.

Value

NA

NA

NA

NA

Examples

```
if (interactive()) {  
  data(vdata)  
  formatDT(vdata)  
}
```

GetPkgVersion	<i>Package version</i>
---------------	------------------------

Description

Gets the version number of a package

Usage

```
GetPkgVersion(pkg)
```

Arguments

pkg The name of the package

Value

A character(1) with the name of the package and its version number.

Examples

```
GetPkgVersion("omXplore")
```

`globals`*Global variables*

Description

Defines the global variables for the package omXplore

Usage

```
globals()
```

Value

A list

Examples

```
globals()
```

`intensity-plots`*Displays different intensity plots.*

Description

Displays different intensity plots.

Usage

```
omXplore_intensity_ui(id)

omXplore_intensity_server(
  id,
  dataIn = reactive({
    NULL
  }),
  i = reactive({
    1
  }),
  track.indices = reactive({
    NULL
  }),
  remoteReset = reactive({
    NULL
  }),
  is.enabled = reactive({
    TRUE
  })
)
```

```
omXplore_intensity(dataIn, i = NULL, withTracking = FALSE)
boxPlot(dataIn, conds, legend = NULL, pal = NULL, subset = NULL)
violinPlot(data, conds, subset = NULL, pal.name = "Set1")
```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>dataIn</code>	xxxx
<code>i</code>	An integer which is the index of the assay in the param obj
<code>track.indices</code>	A vector of integers which are the indices of lines to track.
<code>remoteReset</code>	An integer to activate the reset functions
<code>is.enabled</code>	A boolean that indicates whether the widgets should be enabled or disabled. Default is TRUE
<code>withTracking</code>	A boolean(1) indicating whether the tracking option is activated or not.
<code>conds</code>	A vector indicating the name of each sample.
<code>legend</code>	A vector of the conditions (one condition per sample).
<code>pal</code>	A basis palette for the boxes which length must be equal to the number of unique conditions in the dataset.
<code>subset</code>	A integer() vector of index indicating the indices of rows in the dataset to highlight
<code>data</code>	xxxx
<code>pal.name</code>	A character(1) which is the name of the palette from the package RColorBrewer::RColorBrewer from which the colors are taken. Default value is 'Set1'.

Value

NA
 NA
 A shiny app
 A boxplot
 A violin plot

Author(s)

Samuel Wieczorek, Anais Courtier, Enora Fremy

Examples

```
if (interactive()) {
  data(vdata)
  shiny::runApp(omXplore_intensity(vdata, 1))

  data(sub_R25)
  conds <- legend <- SummarizedExperiment::colData(sub_R25)$group
  pal <- ExtendPalette(length(unique(conds)))
  boxPlot(sub_R25[[1]], conds, legend, pal, seq_len(10))
}
```

```

    shiny::runApp(omXplore_intensity(sub_R25, 1, withTracking = TRUE))
  }

```

is.listOf	<i>Checks the class of a list's slots</i>
-----------	---

Description

Checks if all slots of the given list are of the same class.

Usage

```
is.listOf(object, obj.class = NULL)
```

Arguments

object	A list
obj.class	The name of the class to search in items of the list.

Value

A character (1) with the name of the package or NULL

Examples

```

ll <- as.list(LETTERS[1:3])
is.listOf(ll, "data.frame")
is.listOf(ll, "character")

```

omXplore-modules	<i>Shiny modules used by omXplore</i>
------------------	---------------------------------------

Description

These functions are relative to external modules that can be added into omXplore UI:

- `listShinyApps()`: Show the shiny modules recognized by omXplore and ready to be integrated in the UI of the function `view_dataset()`
- `listPlotModules()`: Show the shiny modules function names (only prefixes) recognized by omXplore and ready to use in the UI.
- `addModules()`: Add external shiny module(s) to the R global environment in such a way (specific prefix renaming of the functions) that it can be discovered by the function `view_dataset()` of the package omXplore during its launch.

Usage

```
addModules(addons = list())

listShinyApps(location = "both")

listPlotModules(location = "both")
```

Arguments

addons	A list in which each item: <ul style="list-style-type: none"> • is named by the name of a package containing the modules to add, • contains the name of the shiny modules to integrate (without <code>'_ui'</code> nor <code>'_server'</code> suffixes)
location	A character(0) to indicate which modules to list. Available values are: <code>'builtin'</code> , <code>'external'</code> and <code>'both'</code> (default).

Value

```
NA
A vector
A vector
```

Examples

```
listShinyApps()
listPlotModules()

#####
# Integration of a module in the package 'mypackage'
#####
addons <- list(omXplore = c("extFoo1", "extFoo2"))
addModules(addons)
```

omXplore_heatmap	<i>Displays a correlation matrix of the quantitative data of a numeric matrix.</i>
------------------	--

Description

This function is a wrapper to `heatmap.2()` that displays assay data in an instance of `SummarizedExperiment`. For more details, see `heatmap.2()`.

Usage

```
omXplore_heatmap_ui(id)

omXplore_heatmap_server(
  id,
  dataIn = reactive({
```

```

        NULL
    }},
    i = reactive({
        NULL
    })
)

omXplore_heatmap(dataIn, i)

heatmapD(
  qdata,
  conds,
  distance = "euclidean",
  cluster = "complete",
  dendro = FALSE
)

mv.heatmap(
  x,
  col = grDevices::heat.colors(100),
  srtCol = NULL,
  labCol = NULL,
  labRow = NULL,
  key = TRUE,
  key.title = NULL,
  main = NULL,
  ylab = NULL
)

heatmapForMissingValues(
  x,
  col = NULL,
  srtCol = NULL,
  labCol = NULL,
  labRow = NULL,
  key = TRUE,
  key.title = NULL,
  main = NULL,
  ylab = NULL
)

```

Arguments

id	A character(1) which is the id of the shiny module.
dataIn	An instance of a class MultiAssayExperiment.
i	An integer which is the index of the assay in the param obj
qdata	A data.frame() of quantitative data.
conds	A vector indicating the name of each sample.
distance	The distance used by the clustering algorithm to compute the dendrogram.
cluster	the clustering algorithm used to build the dendrogram.
dendro	A boolean to indicate if the dendrogram has to be displayed

x	A matrix or array containing the quantitative data.
col	Colors used for the image. Defaults to heat colors (heat.colors).
srtCol	Angle of column conds, in degrees from horizontal
labCol	Character vectors with column conds to use.
labRow	Character vectors with row conds to use.
key	Logical indicating whether a color-key should be shown.
key.title	Main title of the color key. If set to NA no title will be plotted.
main	Main title; default to none.
ylab	y-axis title; default to none.

Value

NA
 NA
 A shiny app
 A heatmap
 A heatmap
 A heatmap

Author(s)

Florence Combes, Samuel Wiczorek, Enora Fremy

Examples

```
if (interactive()) {
  data(vdata)
  omXplore_heatmap(vdata, 1)
}
```

omXplore_tabExplorer *Explore MultiAssayExperiment objects.*

Description

Explore MultiAssayExperiment objects.

Usage

```
omXplore_tabExplorer_ui(id)

omXplore_tabExplorer_server(
  id,
  dataIn = reactive({
    NULL
  }),
  i = reactive({
```

```

      NULL
    }},
    digits = reactive({
      3
    })
  )

  omXplore_tabExplorer(dataIn, i)

```

Arguments

<code>id</code>	A character(1) which is the id of the shiny module.
<code>dataIn</code>	An instance of the class <code>MultiAssayExperiment</code>
<code>i</code>	An integer which is the index of the assay in the param obj
<code>digits</code>	An integer for the number of digits shown in the table

Value

NA
 NA
 NA
 A shiny app

Examples

```

if (interactive()) {
  data(vdata)
  shiny::runApp(omXplore_tabExplorer(vdata, 1))
}

NULL

```

palette

Palette for samples.

Description

Builds a vector of `#conditions` colors for a set of samples. One color is given for a given condition. This function extends a base palette from the package `RColorBrewer::RColorBrewer` to 'n' colors. The colors in the returned palette are always in the same order

Usage

```

SampleColors(conds, pal.name = "Set1")

ExtendPalette(n, pal.name = "Set1")

GetColorsForConditions(conds, pal = NULL)

```

Arguments

conds	A character() of conditions. The length of the vector is the number of samples in the dataset.
pal.name	A character(1) which is the name of the palette from the package RColorBrewer::RColorBrewer from which the colors are taken. Default value is 'Set1'.
n	The number of desired colors in the palette
pal	A vector of HEX color code that form the basis palette from which to build the complete color vector for the conditions.

Value

A vector
 A vector
 A vector

Examples

```
if (interactive()) {
  #-----
  # Builds a palette for a dataset with 3 conditions
  # of 3 samples each.
  #-----

  conds <- c(rep("A", 3), rep("B", 3), rep("C", 3))
  SampleColors(conds)
  SampleColors(conds, "Dark2")

  #-----
  # Extend the default palette to 12 colors
  #-----

  ExtendPalette(12)

  data(vdata)
  conds <- get_group(vdata)
  GetColorsForConditions(conds, ExtendPalette(2))
}
```

 pep_prot_CC

Display a CC

Description

Display a CC
 Connected Components infos

Usage

```
buildGraph(cc = NULL, meta = NULL)

display.CC.visNet(g = NULL, layout = "layout_with_fr")

plotCCJitter(df)

GetCCInfos(cc)
```

Arguments

cc	A list of connected component
meta	A data.frame()
g	An instance of a graph
layout	A character(1) which is the layout used in visNetwork. Default value is 'layout_with_fr'
df	A data.frame()

Value

A list

A plot

A plot

A list of three items:

- One_One: the number of cc composed of one protein and one peptide
- One_Multi: the number of cc composed of one protein and several peptides
- Multi_Multi: the number of cc composed of several proteins and several (shared) peptides.

Author(s)

Thomas Burger, Samuel Wieczorek

Examples

```
if (interactive()) {
  data(sub_R25)
  se <- sub_R25[[1]]
  g <- buildGraph(get_cc(se)[[1]])
  display.CC.visNet(g)
}

if (interactive()) {
  data(sub_R25)
  GetCCInfos(get_cc(sub_R25[[1]]))
}
```

pkgs.require2	<i>Loads packages</i>
---------------	-----------------------

Description

Checks if a package is available to load it

Usage

```
pkgs.require2(ll.deps)
```

Arguments

ll.deps A character() vector which contains packages names

Value

NA

Author(s)

Samuel Wieczorek

Examples

```
pkgs.require2("omXplore")
```

plot-variance	<i>Variance plot</i>
---------------	----------------------

Description

A shiny module which plots the variance of samples

Usage

```
omXplore_variance_ui(id)
```

```
omXplore_variance_server(id, dataIn, i, pal.name = NULL)
```

```
CVDist(dataIn, conds, pal.name = NULL)
```

```
omXplore_variance(dataIn, i)
```

Arguments

id	A character(1) which is the id of the shiny module.
dataIn	An matrix
i	An integer which is the index of the assay in the param obj
pal.name	A character(1) which is the name of the palette from the package RColorBrewer::RColorBrewer from which the colors are taken. Default value is 'Set1'.
conds	A vector indicating the name of each sample.

Value

NA
 NA
 A plot
 A shiny app

Examples

```
if (interactive()) {
  data(vdata)
  shiny::runApp(omXplore_variance(vdata, 1))
}
```

plots_tracking

plots_tracking_ui and plots_tracking_server

Description

This shiny module provides a tool to select

Usage

```
plots_tracking_ui(id)

plots_tracking_server(
  id,
  dataIn = reactive({
    NULL
  }),
  remoteReset = reactive({
    NULL
  }),
  is.enabled = reactive({
    TRUE
  })
)

plots_tracking(obj)
```

Arguments

id	shiny id
remoteReset	A boolean(1) which indicates whether to show the 'Reset' button or not.
is.enabled	xxx
obj	An instance of the class MultiAssayExperiment

Value

NA
 A list (same structure as the parameter params)
 A shiny app

Examples

```
if (interactive()) {
  data(vdata)
  shiny::runApp(plots_tracking(vdata[[1]]))
}
NULL
```

Prostar-1x-compatible *Convert datasets exported by the package Prostar*

Description

Convert datasets exported by the package Prostar

Usage

```
SE_Compatibility_with_Prostar_1x(obj, se)
MAE_Compatibility_with_Prostar_1x(obj, mae)
```

Arguments

obj	An instance of the class MSnSet
se	An instance of the class SummarizedExperiment
mae	An instance of the class MultiAssayExperiment

Value

An enriched instance of the class SummarizedExperiment
 An enriched instance of the class MultiAssayExperiment

Examples

```
data(sub_R25)
```

q_metadata

Quantitative metadata vocabulary for entities

Description

This function gives the vocabulary used for the quantitative metadata of each entity in each condition.

Usage

```
metacell.def(level)
```

```
Parent(level, node = NULL)
```

```
Children(level, parent = NULL)
```

```
GetMetacellTags(metacells = NULL, level = NULL, onlyPresent = FALSE)
```

Arguments

level	A string corresponding to the type of object
node	The name of the node for which one wants its parent
parent	The name of the parent node
metacells	A data.frame() representing the cell metadata
onlyPresent	A boolean(1)

Value

A data.frame containing the different tags and corresponding colors for the level given in parameter

A list

A vector

A vector

A vector

Glossary

Peptide-level vocabulary

└ 'Any' ||||└ 1.0 'Quantified' |||||└ 1.1 "Quant. by direct id" (color 4, white) |||||└ 1.2 "Quant. by recovery" (color 3, lightgrey) ||||└ 2.0 "Missing" (no color) |||||└ 2.1 "Missing POV" (color 1) |||||└ 2.2 'Missing MEC' (color 2) ||||└ 3.0 'Imputed' |||||└ 3.1 'Imputed POV' (color 1) |||||└ 3.2 'Imputed MEC' (color 2)

Protein-level vocabulary: └ 'Any' ||||└ 1.0 'Quantified' |||||└ 1.1 "Quant. by direct id" (color 4, white) |||||└ 1.2 "Quant. by recovery" (color 3, lightgrey) ||||└ 2.0 "Missing" |||||└ 2.1 "Missing POV" (color 1) |||||└ 2.2 'Missing MEC' (color 2) ||||└ 3.0 'Imputed' |||||└ 3.1 'Imputed POV' (color 1) |||||└ 3.2 'Imputed MEC' (color 2) ||||└ 4.0 'Combined tags' (color 3bis, lightgrey)

Conversion to the glossary

A generic conversion
Conversion for Proline datasets
Conversion from Maxquant datasets

Author(s)

Thomas Burger, Samuel Wieczorek
Samuel Wieczorek

Examples

```
if (interactive()) {  
  metacell.def("protein")  
  metacell.def("peptide")  
}  
  
Parent("protein", "Missing")  
Parent("protein", "Missing POV")  
Parent("protein", c("Missing POV", "Missing MEC"))  
Parent("protein", c("Missing", "Missing POV", "Missing MEC"))  
  
Children("protein", "Missing")  
Children("protein", "Missing POV")  
Children("protein", c("Missing POV", "Missing MEC"))  
Children("protein", c("Missing", "Missing POV", "Missing MEC"))  
data(vdata)  
metacells <- get_metacell(vdata[[1]])  
level <- get_type(vdata[[1]])  
GetMetacellTags(metacells, level)
```

sub_R25

Feature example data

Description

sub_R25 is a protein subset of the dataset 'Exp1_R25_pept' in the package DAPARdata.

Format

An instance of the class MultiAssayExperiment

Value

An enriched instance of the class MultiAssayExperiment

Source

sub_R25 was built from the source code available in [inst/scripts/build_datasets.R](#)
The DAPARdata package: <https://github.com/edyp-lab/DAPARdata>

vdata

Feature example data

Description

vdata is a small object for testing and demonstration.

Format

An instance of the class `MultiAssayExperiment`

Value

An enriched instance of the class `MultiAssayExperiment`

Source

vdata was built from the source code available in [inst/scripts/build_datasets.R](#)

Index

- * **datasets**
 - vdata, 34
- * **data**
 - vdata, 34
- * **internal**
 - ds-cc, 11
 - plots_tracking, 30
- accessors, 3
- addModules (omXplore-modules), 22
- boxPlot (intensity-plots), 20
- Build_enriched_qdata, 5
- Build_X_CC (converters), 7
- BuildColorStyles, 5
- buildGraph (pep_prot_CC), 27
- Check_List_consistency (converters), 7
- Check_MSnSet_Consistency (converters), 7
- Check_se_Consistency (converters), 7
- Children (q_metadata), 32
- color-legend, 6
- colorLegend (color-legend), 6
- colorLegend_server (color-legend), 6
- colorLegend_ui (color-legend), 6
- Compute_CC (converters), 7
- convert_to_mae (converters), 7
- converters, 7
- corrMatrix (corrmatrix), 9
- corrmatrix, 9
- custom_metacell_colors (color-legend), 6
- CVDist (plot-variance), 29
- density-plot, 10
- densityPlot (density-plot), 10
- df_to_mae (converters), 7
- df_to_se (converters), 7
- display.CC.visNet (pep_prot_CC), 27
- ds-cc, 11
- ds-pca, 12
- ds-view, 14
- ExtendPalette (palette), 26
- external_app, 16
- extFoo1 (external_app), 16
- extFoo1_server (external_app), 16
- extFoo1_ui (external_app), 16
- extFoo2 (external_app), 16
- extFoo2_server (external_app), 16
- extFoo2_ui (external_app), 16
- format_DT, 18
- FormatDataForDT, 17
- formatDT (format_DT), 18
- formatDT_server (format_DT), 18
- formatDT_ui (format_DT), 18
- get_adjacencyMatrix (accessors), 3
- get_adjacencyMatrix, SummarizedExperiment-method (accessors), 3
- get_cc (accessors), 3
- get_cc, SummarizedExperiment-method (accessors), 3
- get_colID (accessors), 3
- get_colID, SummarizedExperiment-method (accessors), 3
- get_design (accessors), 3
- get_design, MultiAssayExperiment-method (accessors), 3
- get_group (accessors), 3
- get_group, MultiAssayExperiment-method (accessors), 3
- get_metacell (accessors), 3
- get_metacell, SummarizedExperiment-method (accessors), 3
- get_parentProtId (accessors), 3
- get_parentProtId, SummarizedExperiment-method (accessors), 3
- get_pkg_version (accessors), 3
- get_pkg_version, SummarizedExperiment-method (accessors), 3
- get_type (accessors), 3
- get_type, SummarizedExperiment-method (accessors), 3
- GetCCInfos (pep_prot_CC), 27
- GetColorsForConditions (palette), 26
- GetMetacellTags (q_metadata), 32
- GetPkgVersion, 19
- globals, 20

- heatmapD (omXplore_heatmap), 23
- heatmapD(), 15
- heatmapForMissingValues (omXplore_heatmap), 23
- intensity-plots, 20
- is.listOf, 22
- list_to_se (converters), 7
- listOfdf_to_mae (converters), 7
- listOfLists_to_mae (converters), 7
- listOfmatrix_to_mae (converters), 7
- listOfMSnSet_to_mae (converters), 7
- listOfSE_to_mae (converters), 7
- listPlotModules (omXplore-modules), 22
- listShinyApps (omXplore-modules), 22
- MAE_Compatibility_with_Prostar_1x (Prostar-1x-compatible), 31
- MAE_to_mae (converters), 7
- matrix_to_mae (converters), 7
- matrix_to_se (converters), 7
- metacell.def (q_metadata), 32
- MSnSet_to_mae (converters), 7
- MSnSet_to_se (converters), 7
- mv.heatmap (omXplore_heatmap), 23
- my_PCA (ds-pca), 12
- omXplore-modules, 22
- omXplore_cc (ds-cc), 11
- omXplore_cc_server (ds-cc), 11
- omXplore_cc_ui (ds-cc), 11
- omXplore_corrmatrix (corrmatrix), 9
- omXplore_corrmatrix_server (corrmatrix), 9
- omXplore_corrmatrix_ui (corrmatrix), 9
- omXplore_density (density-plot), 10
- omXplore_density_server (density-plot), 10
- omXplore_density_ui (density-plot), 10
- omXplore_heatmap, 23
- omXplore_heatmap_server (omXplore_heatmap), 23
- omXplore_heatmap_ui (omXplore_heatmap), 23
- omXplore_intensity (intensity-plots), 20
- omXplore_intensity_server (intensity-plots), 20
- omXplore_intensity_ui (intensity-plots), 20
- omXplore_pca (ds-pca), 12
- omXplore_pca_server (ds-pca), 12
- omXplore_pca_ui (ds-pca), 12
- omXplore_tabExplorer, 25
- omXplore_tabExplorer_server (omXplore_tabExplorer), 25
- omXplore_tabExplorer_ui (omXplore_tabExplorer), 25
- omXplore_variance (plot-variance), 29
- omXplore_variance_server (plot-variance), 29
- omXplore_variance_ui (plot-variance), 29
- palette, 26
- Parent (q_metadata), 32
- pep_prot_CC, 27
- pkgs.require2, 29
- plot-variance, 29
- plotCCJitter (pep_prot_CC), 27
- plotPCA_Eigen (ds-pca), 12
- plotPCA_Eigen_hc (ds-pca), 12
- plotPCA_Ind (ds-pca), 12
- plotPCA_Var (ds-pca), 12
- plots_tracking, 30
- plots_tracking_server (plots_tracking), 30
- plots_tracking_ui (plots_tracking), 30
- Prostar-1x-compatible, 31
- q_metadata, 32
- QFeatures_to_mae (converters), 7
- RColorBrewer::RColorBrewer, 10, 21, 26, 27, 30
- SampleColors (palette), 26
- SE_Compatibility_with_Prostar_1.x (Prostar-1x-compatible), 31
- SE_to_mae (converters), 7
- sub_R25, 33
- vdata, 34
- view_dataset (ds-view), 14
- view_dataset_server (ds-view), 14
- view_dataset_ui (ds-view), 14
- violinPlot (intensity-plots), 20
- wrapper_pca (ds-pca), 12