

Package ‘flowPloidyData’

May 7, 2026

Title Example Flow Cytometry Data
Version 1.39.0
Author Tyler Smith <tyler@plantarum.ca>
Maintainer Tyler Smith <tyler@plantarum.ca>
Description A collection of raw flow cytometry data for use in vignettes for the flowPloidy package.
License GPL-3
Encoding UTF-8
LazyData true
biocViews FlowCytometryData
Suggests knitr, rmarkdown, flowCore
VignetteBuilder knitr
git_url <https://git.bioconductor.org/packages/flowPloidyData>
git_branch devel
git_last_commit 8099dbb
git_last_commit_date 2026-04-28
Repository Bioconductor 3.24
Date/Publication 2026-05-07

Contents

flowPloidyData	1
Index	3

flowPloidyData	<i>Example flow cytometry datasets from analysis of ploidy in plants.</i>
----------------	---

Description

A list of LMD files from analyses of the plant leaf tissue samples, co-chopped with standards with known GC (e.g., tomato, soybean etc.).

Usage

```
flowPloidyFiles()
```

```
fpBad()
```

```
fpVac()
```

Format

The function `flowPloidyFiles` returns a vector of filenames corresponding to the LMD files provided by this package. Individual elements of this vector (e.g., `flowPloidyFiles()[1]`) can be passed to functions that load a single FCS file, such as `flowCore::read.FCS`. The entire vector can be passed to functions that load multiple files, such as `flowPloidy::histBatch`.

Each element is named with the filename (without the path), so that you can select an individual filename either by numeric index (i.e., `flowPloidyFiles()[7]`) or by name (`flowPloidyFiles()["248+S.LMD"]`). The names aren't meaningful to you, of course! I added them to provide a more robust way to select an individual file, as the order of files may change in package updates.

The individual files named in `flowPloidyFiles` are LMD files generated by a Beckman-Coulter Gallios flow cytometer. They represent a variety of samples, and some of them are low quality. They are not ideal data sets, but rather represent a range of data quality for assessing the performance of `flowPloidy`.

`fpBad()` and `fpVac()` each return the path to a single LMD file. These are particularly poor quality files that are used in some of the unit tests for `flowPloidy`. They're probably not useful to regular users.

Value

A named character vector of file names, including their full path in the local file system.

Examples

```
flowPloidyFiles() ## a character vector of file names

## Read in the first file:
library(flowCore)
fcs <- read.FCS(flowPloidyFiles()[1], dataset = 1,
               alter.names = TRUE)
```

Index

* datasets

flowPloidyData, 1

flowPloidyData, 1

flowPloidyFiles (flowPloidyData), 1

fpBad (flowPloidyData), 1

fpVac (flowPloidyData), 1