

# Package ‘scviR’

April 6, 2026

**Date** 2025-05-02

**Title** experimental interface from R to scvi-tools

**Version** 1.10.0

**Description** This package defines interfaces from R to scvi-tools. A vignette works through the totalVI tutorial for analyzing CITE-seq data. Another vignette compares outputs of Chapter 12 of the OSCA book with analogous outputs based on totalVI quantifications. Future work will address other components of scvi-tools, with a focus on building understanding of probabilistic methods based on variational autoencoders.

**License** Artistic-2.0

**Encoding** UTF-8

**Depends** R (>= 4.3), basilisk, shiny, SingleCellExperiment

**Imports** reticulate, BiocFileCache, utils, pheatmap, SummarizedExperiment, S4Vectors, limma, scater, stats, MatrixGenerics

**Suggests** knitr, testthat, reshape2, ggplot2, rhdf5, BiocStyle

**VignetteBuilder** knitr

**biocViews** Infrastructure, SingleCell, DataImport

**RoxygenNote** 7.3.3

**URL** <https://github.com/vjcitn/scviR>

**BugReports** <https://github.com/vjcitn/scviR/issues>

**git\_url** <https://git.bioconductor.org/packages/scviR>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 76c9278

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-04-05

**Author** Vincent Carey [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-4046-0063>>)

**Maintainer** Vincent Carey <stvjc@channing.harvard.edu>

## Contents

adtProfiles . . . . .	2
anndataR . . . . .	3
bsklenv . . . . .	3
cacheCiteseq5k10kPbmcs . . . . .	4
cacheCiteseq5k10kTutvae . . . . .	4
cacheCiteseqHDPdata . . . . .	5
cacheCiteseqHDPmodel . . . . .	5
clusters.adt . . . . .	6
clusters.rna . . . . .	6
exploreSubcl . . . . .	7
getCh12AllSce . . . . .	7
getCh12Sce . . . . .	8
getCiteseq5k10kPbmcs . . . . .	9
getCiteseqTutvae . . . . .	9
getPro5k10kAdata . . . . .	10
getSubclLM . . . . .	10
getSubclusteringFeatures . . . . .	11
getTotalVI5k10kAdata . . . . .	12
getTotalVINormalized5k10k . . . . .	12
MuDataR . . . . .	13
muonR . . . . .	13
pyHelp2 . . . . .	14
scanpyHelper . . . . .	14
scanpyR . . . . .	15
seviHelper . . . . .	15
seviR . . . . .	16
<b>Index</b>	<b>17</b>

---

adtProfiles	<i>produce a heatmap from a specialized CITE-seq SingleCellExperiment</i>
-------------	---

---

### Description

produce a heatmap from a specialized CITE-seq SingleCellExperiment

### Usage

```
adtProfiles(x, lb = -3, ub = 3, do_z = FALSE)
```

### Arguments

x	SingleCellExperiment instance that has an ‘se.averaged’ component in its meta-data
lb	numeric(1) lower bound on ‘breaks’ sequence for ComplexHeatmap::pheatmap, defaults to -3
ub	numeric(1) upper bound on ‘breaks’ sequence for ComplexHeatmap::pheatmap, defaults to 3
do_z	logical(1) if TRUE, divide the residuals by their standard deviation across clusters, defaults to false

**Value**

ComplexHeatmap::pheatmap instance  
side effect of pheatmap::pheatmap call

**Note**

See the OSCA book ch12.5.2 for the application.

**Examples**

```
ch12sce <- getCh12Sce()
adtProfiles(ch12sce)
adtProfiles(ch12sce, do_z = TRUE)
```

---

anndataR                      *basic interface to anndata*

---

**Description**

basic interface to anndata

**Usage**

```
anndataR()
```

**Value**

basiliskRun result with import from reticulate, typically a Module

**Examples**

```
ad <- anndataR()
ad
ad$read_h5ad
```

---

bsklenv                      *python declarations*

---

**Description**

python declarations

**Usage**

```
bsklenv
```

**Format**

An object of class BasiliskEnvironment of length 1.

---

cacheCiteseq5k10kPbmcs

*grab scvi-tools-processed PBMC CITE-seq data in anndata format (gzipped) from Open Storage Network*

---

### Description

grab scvi-tools-processed PBMC CITE-seq data in anndata format (gzipped) from Open Storage Network

### Usage

```
cacheCiteseq5k10kPbmcs()
```

### Value

invisibly, the path to the .h5ad file

### Note

Original h5ad files obtained using scvi-tools 0.18.0 `scvi.data.pbmcs_10x_cite_seq`, then processed according to steps in the scviR vignette, which follow the [scvi-tools tutorial](<https://colab.research.google.com/github/scvi-tools/tutorials/blob/0.18.0/totalVI.ipynb>) by Gayoso et al.

It may be advantageous to set `'options(timeout=3600)'` or to allow an even greater time for internet downloads, if working at a relatively slow network connection.

### Examples

```
h5path <- cacheCiteseq5k10kPbmcs()
cmeta <- rhdf5::h5ls(h5path)
dim(cmeta)
head(cmeta, 17)
```

---

cacheCiteseq5k10kTutvae

*Deprecated: grab scvi-tools VAE instance built on the PBMC datasets following the tutorial*

---

### Description

Deprecated: grab scvi-tools VAE instance built on the PBMC datasets following the tutorial

### Usage

```
cacheCiteseq5k10kTutvae()
```

### Value

invisibly, the path to the .zip file holding the fitted VAE and associated data

**Note**

the serialized model is obsolete

VAE construction followed tutorial at [‘https://docs.scvi-tools.org/en/stable/tutorials/notebooks/totalVI.html’](https://docs.scvi-tools.org/en/stable/tutorials/notebooks/totalVI.html).

It may be advantageous to set `‘options(timeout=3600)’` or to allow an even greater time for internet downloads, if working at a relatively slow network connection.

**Examples**

```
## Not run:
zpath <- cacheCiteseq5k10kTutvae()
td <- tempdir()
utils::unzip(zpath, exdir = td)
vaedir <- paste0(td, "/vae2_ov")
scvi <- scviR()
adm <- anndataR()
hpath <- cacheCiteseq5k10kPbmcs()
adata <- adm$read_h5ad(hpath)
mod <- scvi$model$`_totalvi`$TOTALVI$load(vaedir, adata) #, use_gpu = FALSE)
mod

## End(Not run)
```

---

cacheCiteseqHDPdata *retrieve and cache a 349-protein CITE-seq dataset as employed in scvi-tools tutorial*

---

**Description**

retrieve and cache a 349-protein CITE-seq dataset as employed in scvi-tools tutorial

**Usage**

```
cacheCiteseqHDPdata()
```

---

cacheCiteseqHDPmodel *grab scvi-tools muon-oriented VAE instance built on the PBMC datasets following the tutorial*

---

**Description**

grab scvi-tools muon-oriented VAE instance built on the PBMC datasets following the tutorial

**Usage**

```
cacheCiteseqHDPmodel()
```

**Value**

invisibly, the path to the .zip file holding the weights in pt format for the fitted VAE

**Note**

VAE construction followed tutorial at <https://docs.scvi-tools.org/en/stable/tutorials/notebooks/totalVI.html>.

We are using the scvi tutorial read early may 2025. The notebook uses "h5 format of single-cell multiomic data generated by Proteintech Genomics ... The data is from human resting PBMCs stained with the MultiPro® Human Discovery Panel (HDP) followed by processing using 10x Genomics Flex chemistry with Feature Barcoding Technology."

It may be advantageous to set `options(timeout=3600)` or to allow an even greater time for internet downloads, if working at a relatively slow network connection.

**Examples**

```
zpath <- cacheCiteseqHDPmodel()
td <- tempdir()
utils::unzip(zpath, exdir = td)
vaedir <- paste0(td, "/vae3_pt")
dir(vaedir)
```

---

clusters.adt	<i>ADT-based cluster labels for 7472 cells in OSCA chapter 12 analysis</i>
--------------	--

---

**Description**

ADT-based cluster labels for 7472 cells in OSCA chapter 12 analysis

**Usage**

```
clusters.adt
```

**Format**

```
factor
```

---

clusters.rna	<i>mRNA-based cluster labels for 7472 cells in OSCA chapter 12 analysis</i>
--------------	---

---

**Description**

mRNA-based cluster labels for 7472 cells in OSCA chapter 12 analysis

**Usage**

```
clusters.rna
```

**Format**

```
factor
```

---

exploreSubcl	<i>app to explore diversity in RNA-subclusters within ADT clusters</i>
--------------	--

---

**Description**

app to explore diversity in RNA-subclusters within ADT clusters

**Usage**

```
exploreSubcl(sce, inlist, adtcls)
```

**Arguments**

sce	a SingleCellExperiment with altExp with ADT quantification
inlist	list of SingleCellExperiments (SCEs) formed by <code>scrn::quickSubCluster</code>
adtcls	vector of ADT cluster assignments

**Value**

shinyApp instance

**Note**

TSNE should already be available in `altExp(sce)`; follow OSCA book 12.5.2. If using example, set `ask=FALSE`.

**Examples**

```
if (interactive()) {
  sce <- getCh12Sce()
  all.sce <- getCh12AllSce()
  data(clusters.adt)
  runApp(exploreSubcl(sce, all.sce, clusters.adt)) # trips up interactive pkgdown?
}
```

---

getCh12AllSce	<i>get list of cluster-specific SCE for 10k PBMC annotated as in OSCA book chapter 12</i>
---------------	---

---

**Description**

get list of cluster-specific SCE for 10k PBMC annotated as in OSCA book chapter 12

**Usage**

```
getCh12AllSce()
```

**Value**

SimpleList of SingleCellExperiment instances

**Note**

This is a list of `SingleCellExperiment` instances with data on a total of 7472 cells from a 10x CITE-seq experiment. An `altExp` component in each list element includes antibody-derived tag (ADT) counts on 17 proteins. The data are acquired and processed as described in ch 12 of the OSCA book, circa February 2023. List elements correspond to mRNA-based sub-clusters of ADT-based clusters.

**Examples**

```
ch12_allsce <- getCh12AllSce()
vapply(ch12_allsce, ncol, numeric(1))
```

---

getCh12Sce

*get SCE for 10k PBMC annotated as in OSCA book chapter 12*

---

**Description**

get SCE for 10k PBMC annotated as in OSCA book chapter 12

**Usage**

```
getCh12Sce(clear_cache = FALSE)
```

**Arguments**

`clear_cache`      logical(1) will delete relevant entries in available cache before continuing, defaults to FALSE

**Value**

`SingleCellExperiment` instance

**Note**

This is a `SingleCellExperiment` instance with data on 7472 cells from a 10x CITE-seq experiment. An `altExp` component includes antibody-derived tag (ADT) counts on 17 proteins. The data are acquired and processed as described in ch 12 of the OSCA book, circa February 2023. A metadata element (`se.averaged`) includes the result of averaging protein abundance estimates within ADT-based clusters, as is done to give rise to Figure 12.8 of the OSCA book.

**Examples**

```
ch12sce <- getCh12Sce()
ch12sce
```

---

getCiteseq5k10kPbmcs *helper to get the processed anndata for CITE-seq PBMCs from scvi-tools tutorial*

---

### Description

helper to get the processed anndata for CITE-seq PBMCs from scvi-tools tutorial

### Usage

```
getCiteseq5k10kPbmcs()
```

### Value

python reference to anndata

### Note

It may be advantageous to set 'options(timeout=3600)' or to allow an even greater time for internet downloads, if working at a relatively slow network connection.

### Examples

```
getCiteseq5k10kPbmcs()
```

---

getCiteseqTutvae *helper to get the tutorial VAE for PBMCs from scvi-tools tutorial*

---

### Description

helper to get the tutorial VAE for PBMCs from scvi-tools tutorial

### Usage

```
getCiteseqTutvae(use_gpu = FALSE)
```

### Arguments

use\_gpu            logical(1), defaulting to FALSE, passed to TOTALVI.load

### Value

python reference to anndata

### Note

March 2024 use\_gpu ignored

**Examples**

```
## Not run:
getCiteseqTutvae()

## End(Not run)
```

---

getPro5k10kAdata	<i>get an anndata reference to 5k10k protein after totalVI from tutorial</i>
------------------	--

---

**Description**

get an anndata reference to 5k10k protein after totalVI from tutorial

**Usage**

```
getPro5k10kAdata()
```

**Value**

python reference to anndata

**Note**

It may be advantageous to set ‘options(timeout=3600)’ or to allow an even greater time for internet downloads, if working at a relatively slow network connection.

**Examples**

```
getPro5k10kAdata()
```

---

getSubcILM	<i>get lmFit for heterogeneity across subclusters</i>
------------	---

---

**Description**

get lmFit for heterogeneity across subclusters

**Usage**

```
getSubcILM(inlist, clname)
```

**Arguments**

inlist	list of SingleCellExperiments (SCEs) formed by <code>scran::quickSubCluster</code>
clname	character(1) name of cluster SCE to assess

**Value**

limma::lmFit output

**Note**

It is assumed that 'logcounts' is an assay element, and that 'subcluster' is a colData element of each SCE in inlist

**Examples**

```
all.sce <- getCh12AllSce()
lm3 <- getSubclLM(all.sce, "3")
names(lm3)
```

---

getSubclusteringFeatures

*get lmFit F-stat based collection of n genes most varying in mean across subclusters*

---

**Description**

get lmFit F-stat based collection of n genes most varying in mean across subclusters

**Usage**

```
getSubclusteringFeatures(inlist, clname, n = 20)
```

**Arguments**

inlist	list of SingleCellExperiments (SCEs) formed by <code>scrans::quickSubCluster</code>
clname	character(1) name of cluster SCE to assess
n	numeric(1) number to preserve

**Value**

list with two elements, feat = rowData corresponding to variable genes, stats = topTable result

**Note**

Symbol will be taken from feat and placed in stats component if available

**Examples**

```
all.sce <- getCh12AllSce()
scl <- getSubclusteringFeatures(all.sce, "3", 10)
names(scl)
```

---

```
getTotalVI5k10kAdata
```

*get anndata reference to full totalVI processing of 5k10k data*

---

**Description**

get anndata reference to full totalVI processing of 5k10k data

**Usage**

```
getTotalVI5k10kAdata()
```

**Value**

python reference to anndata

**Examples**

```
full <- getTotalVI5k10kAdata()
full
```

---

```
getTotalVINormalized5k10k
```

*get matrices of normalized quantifications from full totalVI 5k10k from tutorial*

---

**Description**

get matrices of normalized quantifications from full totalVI 5k10k from tutorial

**Usage**

```
getTotalVINormalized5k10k()
```

**Value**

list of matrices

**Examples**

```
nm1ist <- getTotalVINormalized5k10k()
vapply(nm1ist, dim, numeric(2))
```

---

MuDataR	<i>basic interface to MuData</i>
---------	----------------------------------

---

**Description**

basic interface to MuData

**Usage**

```
MuDataR()
```

**Value**

basiliskRun result with import from reticulate, typically a Module

**Examples**

```
md <- MuDataR()
md
head(names(md))
```

---

muonR	<i>basic interface to muon</i>
-------	--------------------------------

---

**Description**

basic interface to muon

**Usage**

```
muonR()
```

**Value**

basiliskRun result with import from reticulate, typically a Module

**Examples**

```
md <- muonR()
md
head(names(md))
```

pyHelp2	<i>helper to get text from python help utility – may need handling through basilisk</i>
---------	---

---

**Description**

helper to get text from python help utility – may need handling through basilisk

**Usage**

```
pyHelp2(object)
```

**Arguments**

object            a reference to a python module typically with class 'python.builtin.module'

**Value**

character vector of lines from python help result

---

scanpyHelper	<i>shiny app that helps access documentation on python-accessible components</i>
--------------	--

---

**Description**

shiny app that helps access documentation on python-accessible components

**Usage**

```
scanpyHelper()
```

**Value**

shinyApp instance

---

scanpyR	<i>basic interface</i>
---------	------------------------

---

**Description**

basic interface

**Usage**

```
scanpyR()
```

**Value**

basiliskRun result with import from reticulate, typically a Module

**Examples**

```
sc <- scanpyR()
sc
sc$pp
```

---

scviHelper	<i>shiny app that helps access documentation on python-accessible components</i>
------------	--

---

**Description**

shiny app that helps access documentation on python-accessible components

**Usage**

```
scviHelper()
```

**Value**

shinyApp instance

---

`scviR`*basic interface*

---

**Description**

basic interface

**Usage**

```
scviR()
```

**Value**

basiliskRun result with import from reticulate, typically a Module

**Examples**

```
scvi <- scviR()
scvi
scvi$model
```

# Index

## \* datasets

- bsklenv, 3
- clusters.adt, 6
- clusters.rna, 6

- adtProfiles, 2
- anndataR, 3

- bsklenv, 3

- cacheCiteseq5k10kPbmcs, 4
- cacheCiteseq5k10kTutvae, 4
- cacheCiteseqHDPdata, 5
- cacheCiteseqHDPmodel, 5
- clusters.adt, 6
- clusters.rna, 6

- exploreSubcl, 7

- getCh12AllSce, 7
- getCh12Sce, 8
- getCiteseq5k10kPbmcs, 9
- getCiteseqTutvae, 9
- getPro5k10kAdata, 10
- getSubclLM, 10
- getSubclusteringFeatures, 11
- getTotalVI5k10kAdata, 12
- getTotalVINormalized5k10k, 12

- MuDataR, 13
- muonR, 13

- pyHelp2, 14

- scanpyHelper, 14
- scanpyR, 15
- scviHelper, 15
- scviR, 16