

# Package ‘spqn’

April 6, 2026

**Title** Spatial quantile normalization

**Version** 1.22.0

**Description** The spqn package implements spatial quantile normalization (SpQN). This method was developed to remove a mean-correlation relationship in correlation matrices built from gene expression data. It can serve as pre-processing step prior to a co-expression analysis.

**License** Artistic-2.0

**Imports** graphics, stats, utils, matrixStats

**Depends** R (>= 4.0), ggplot2, ggridges, SummarizedExperiment, BiocGenerics

**Suggests** BiocStyle, knitr, rmarkdown, tools, spqnData (>= 0.99.3), RUnit

**VignetteBuilder** knitr

**URL** <https://github.com/hansenlab/spqn>

**BugReports** <https://github.com/hansenlab/spqn/issues>

**biocViews** NetworkInference, GraphAndNetwork, Normalization

**git\_url** <https://git.bioconductor.org/packages/spqn>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 1495b7b

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-04-05

**Author** Yi Wang [cre, aut],  
Kasper Daniel Hansen [aut]

**Maintainer** Yi Wang <yiwangthu5@gmail.com>

## Contents

spqn-package . . . . .	2
normalize_correlation . . . . .	2
plot_IQR_condition_exp . . . . .	3
plot_signal_condition_exp . . . . .	4
qqplot_condition_exp . . . . .	4
<b>Index</b>	<b>6</b>

---

spqn-package                      *Spatial quantile normalization*

---

### Description

The spqn package implements spatial quantile normalization (SpQN). This method was developed to remove a mean-correlation relationship in correlation matrices built from gene expression data. It can serve as pre-processing step prior to a co-expression analysis.

### Details

See references for details on spatial quantile normalization.

The main function is `normalize_correlation`. We include a number of plotting functions for examining the mean-correlation relationship, see the vignette for examples.

### References

Y Wang, SC Hicks, KD Hansen (2020). *Co-expression analysis is biased by a mean-correlation relationship*. bioRxiv 2020.02.13.944777. doi:10.1101/2020.02.13.944777

---

normalize\_correlation    *Spatial quantile normalization (SpQN)*

---

### Description

This method was developed to remove a mean-correlation relationship in correlation matrices built from gene expression data. It can serve as pre-processing step prior to a co-expression analysis.

### Usage

```
normalize_correlation(cor_mat, ave_exp, ngrp, size_grp, ref_grp)
```

### Arguments

cor_mat	A (square and symmetric) correlation matrix.
ave_exp	A vector of expression levels, same length as the number of rows of the correlation matrix in cor_mat. For other types of data, ave_exp can be the vector corresponding to the row/column of the correlation matrix, whose dependency with the distribution of correlations need to be removed.
ngrp	Number of bins in each row/column to be used to partition the correlation matrix, integer.
size_grp	Size of the outer bins to be used to approximate the distribution of the inner bins, in order to smooth the normalization. Note that the product of size_grp and ngrp must be equal or larger than the row/column number of cor_mat, and there is no smoothness in the normalization when they are equal.
ref_grp	Location of the reference bin on the diagonal, whose distribution will be used as target distribution in the normalization, an integer.

**Value**

A normalized correlation matrix.

**Examples**

```
if(require(spcnData)){
  data(gtex.4k)
  cor_ori <- cor(t(assay(gtex.4k)))
  ave_logrpkm <- rowData(gtex.4k)$ave_logrpkm
  normalize_correlation(cor_ori, ave_exp = ave_logrpkm,
                        ngrp=10, size_grp=15, ref_grp=9)}
```

---

plot\_IQR\_condition\_exp

*Get and plot the IQRs of submatrices of the correlation matrix.*

---

**Description**

The `get_IQR_condition_exp` function computes the IQRs of a set of 10 by 10 same-size bins that partition the correlation matrix, ordered according to expression level.

The `plot_IQR_condition_exp` function plots the IQR for each bin among a set of 10 by 10 same-size bins that partition the correlation matrix, with IQR denoted by the width of boxes in the plot.

**Usage**

```
get_IQR_condition_exp(cor_mat, ave_exp)
plot_IQR_condition_exp(IQR_list)
```

**Arguments**

<code>cor_mat</code>	correlation matrix, generated by gene expression matrix, with genes sorted by average expression levels.
<code>ave_exp</code>	vector, average expression level of each gene for the normalized gene expression matrix.
<code>IQR_list</code>	List, output of <code>get_IQR_condition_exp</code> .

**Value**

A plot with boxes that shows the IQR of each bin

**Note**

The mnemonic for `condition_exp` is 'conditional on expression'.

**Examples**

```
if(require(spcnData)) {
  data(gtex.4k)
  cor_mat <- cor(t(assay(gtex.4k)))
  ave_logrpkm <- rowData(gtex.4k)$ave_logrpkm
  IQR_list <- get_IQR_condition_exp(cor_mat, ave_exp = ave_logrpkm)
  plot_IQR_condition_exp(IQR_list)
}
```

---

plot\_signal\_condition\_exp

*Plot the signal and background distribution of a correlation matrix.*

---

### Description

This function allows users to visualize the distributions of (assumed) signal and background, conditional on expression levels. The predicted signals are defined by the 0.1% highest correlations in each bin.

### Usage

```
plot_signal_condition_exp(cor_mat, ave_exp, signal)
```

### Arguments

cor_mat	Matrix, correlation matrix, generated by gene expression matrix
ave_exp	Vector, average expression level of each gene for the normalized expression matrix
signal	a value between 0 and 1 giving the fraction of correlations which should be considered signal. We often use a value of 0.001.

### Value

Invoked for the side effect of producing a plot.

### Note

The mnemonic for condition\_exp is ‘conditional on expression’.

### Examples

```
if(require(spqnData)) {
  data(gtex.4k)
  cor_mat <- cor(t(assay(gtex.4k)))
  ave_logrpkm <- rowData(gtex.4k)$ave_logrpkm
  plot_signal_condition_exp(cor_mat, ave_exp=ave_logrpkm, signal=0.05)}
```

---

qqplot\_condition\_exp *Q-Q plot for examing the distributions across submatrices of a correlation matrix.*

---

### Description

We partition the correlation matrix into 10x10 bins of equal size, with genes ordered according to expression level. As reference bin, we choose the (9,9) bin (ie. the almost-highest expressed genes). We then make a QQ-plot of the (i,j)’th submatrix vs. the (9,9) submatrix. See the SpQN paper for detail on these choices.

**Usage**

```
qqplot_condition_exp(cor_mat, ave_exp, i, j)
```

**Arguments**

<code>cor_mat</code>	Matrix, correlation matrix, generated by gene expression matrix.
<code>ave_exp</code>	Vector, average expression level of each gene for the normalized expression matrix.
<code>i</code>	Integer, row number of the submatrix (see details).
<code>j</code>	Integer, column number of the submatrix (see details).

**Value**

Invoked for the side effect of producing a plot.

**Note**

The mnemonic for `condition_exp` is 'conditional on expression'.

**Examples**

```
if(require(spqnData)) {  
  data(gtex.4k)  
  cor_mat <- cor(t(assay(gtex.4k)))  
  ave_logrpkm <- rowData(gtex.4k)$ave_logrpkm  
  qqplot_condition_exp(cor_mat, ave_exp=ave_logrpkm, 1, 1)  
}
```

# Index

## \* package

spqn-package, 2

get\_IQR\_condition\_exp

(plot\_IQR\_condition\_exp), 3

normalize\_correlation, 2

plot\_IQR\_condition\_exp, 3

plot\_signal\_condition\_exp, 4

qqplot\_condition\_exp, 4

spqn (spqn-package), 2

spqn-package, 2